UNCLASSIFIED

AD NUMBER

AD802114

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited. Document partially illegible.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; JUL 1966. Other requests shall be referred to Air Force Flight Dynamics Laboratory, FDTR, Wright-Patterson AFB, OH 45433. Document partially illegible. This document contains export-controlled technical data.

AUTHORITY

affdc ltr, 31 may 1973

THIS PAGE IS UNCLASSIFIED

AFFDL TR-66-57
VOLUME II

KC-135 POWER SPECTRAL VERTICAL GUST LOAD ANALYSIS

SUPPLEMENT RESULTS VOLUME II

ROBERT N. LATZ
THE BOEING COMPANY

TECHNICAL REPORT AFFDL-TR-66-57, VOLUME II
JULY, 1966

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Air Force Flight Dynamics Laboratory (FDTR), Wright-Patterson AFB, Ohio 45433.

AIR FORCE FLIGHT DYNAMICS LABORATORY
RESEARCH AND TECHNOLOGY DIVISION
AIR FORCE SYSTEMS COMMAND
WRIGHT-PATTERSON AIR FORCE BASE, OHIO

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

NOTICES

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Copies of this report should not be returned to the Research and Technology Division unless return is required by security considerations, contractual obligations, or notice on a specific document.

200 - September 1966 5-124

AFFDL TR-66-57
VOLUME II

KC-135 POWER SPECTRAL VERTICAL GUST LOAD ANALYSIS

SUPPLEMENT RESULTS VOLUME II

ROBERT N. LATZ
THE BOEING COMPANY

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Air Force Flight Dynamics Laboratory (FDTR), Wright-Patterson AFB, Ohio 45433.

FOREWORD

The program described in this report was conducted by the Structural Dynamics Unit, Structures Staff, Commercial Airplane Division, The Boeing Company, Renton, Washington. The program was monitored by Mr. Paul Hasty (FDTR), Air Force Flight Dynamics Laboratory, Research and Technology Division, Air Force Systems Command, Wright-Patterson Air Force Base, Ohio, under contract number AF33(615)-2454, "Investigation to Obtain Specific Design Calculations on Proven Transport Aircraft for the Verification of a Gust Design Procedure Based on Proven Spectral Techniques." The program was accomplished under system number 5(611367 62405334), project number 1367, "Structural Design Criteria", task number 136702, "Aerospace Vehicle Structural Loads Criteria." The time period covered by this final technical report is 1 July 1965 to 1 June 1966. The manuscript was released by the author on 1 April 1966 for publication as an RTD technical report.

Supervising consultant was Dr. John C. Houbolt of Aeronautical Research Associates of Princeton. Robert N. Latz conducted the analysis under the supervision of Arthur J. Kamm, Supervisor of the Structural Dynamics Unit.

This report has been given The Boeing Company document number D6-18252.

This technical report has been reviewed and is approved.

FRANCIS J. JANIK, JR.
Chief, Theoretical Mechanics Bran
Structures Division

ABSTRACT

This report presents the results of an analysis to obtain the stress response parameters (level of stress per level of turbulence) and zero-crossing rates at two wing stations and two body stations of the KC-135 airplane where the margins of safety for gusts are minimum. Five combinations of gross weight, speed, and altitude were selected. The results of the computer analysis present the effects of changes in scale of turbulence and upper cutoff frequency on the response parameters and zero-crossing rates. Results indicate a large reduction in stress response parameter and small reduction in zero-crossing rate with increasing scale of turbulence. Variations of upper cutoff frequency above the highest modal frequency used in the analysis indicate negligible change in either stress response parameter or zero-crossing rate. The ratios of incremental limit allowable stress to stress response parameter obtained over a wide range of gross weight, speed, and scale of turbulence result in a minimum value of 53. This document (volume I) presents the analyses and specific results described above. Volume II presents response parameters, zero-crossing rates, frequency response functions, and power spectra of bending moment, shear, and torsion.

(iv Blank)

CONTENTS

ILLUSTRATIONS

ILLUSTRATIONS (Continued)

TABLES

ABBREVIATIONS AND SYMBOLS

A	stress response parameter (rms value of incremental stress for a 1 fps rms random gust) (psi/fps)
N_o	zero-crossing rate (average number of times per second that the incremental stress crosses the 1g mean value with positive slope)
ω	frequency (radians per second)
$\lvert H(\omega) \rvert$	absolute value of frequency response function
$\Phi_I(\omega)$	gust spectrum
ω_c	upper cutoff frequency (radians per second)
Ω	reduced frequency (radians per foot)
L	scale of turbulence (feet)
σ	rms level of turbulence intensity (fps)
$\sigma_{W^{\eta}D}$	measure (fps) of the probability of exceeding limit stress. (It is equal to the ratio of incremental limit allowable stress to stress response parameter.)

SECTION I

INTRODUCTION

A program is being conducted by the U.S. Air Force to establish a simplified procedure to design airplanes for gusts based on power spectral density techniques. To verify the proposed gust procedure, specific design calculations for selected airplanes were obtained from several airplane manufacturers. The Boeing Company was selected to obtain design calculations for the KC-135 airplane and these design calculations are presented in this report.

The specific design calculations presented are stress response parameters (ratio of rms level of stress to rms level of turbulence), zero-crossing rates, and stress frequency response functions. These data are calculated at two wing stations and two body stations where the margins of safety for gusts are minimum. The free-free mode shapes of the airplane are also included.

In volume II are presented response parameters, zero-crossing rates, frequency response functions, and power spectra of bending moment, shear, and torsion.

SECTION II

ANALYSIS

1. Analysis Conditions:

a. The selection of flight conditions for analysis is based on two considerations. First, consideration is given to the gust design conditions used in the basic design of the KC-135 airplane (1). These are based on the use of the gust load formula (2). Second, consideration is given to the flight conditions that would result in minimum pitch stability, that contributes to high loads in random turbulence. The critical gust altitude of 24,000 feet was derived from the design gust analysis, and this altitude is selected for the present analysis. Past power-spectral analyses have shown that low pitch stability results in high loads. The conditions for low pitch stability are a high lift coefficient and an aft center of gravity. Since both of these conditions cannot be achieved simultaneously on the KC-135 airplane, five analysis conditions are selected to represent a wide range of gross weight, center of gravity, and speed.

b. Table I and figure 1 summarize the analysis conditions. Condition 1 is the maximum gross weight, maximum design speed condition and represents the maximum gust force input to the airplane. Using the gust load formula (2), this is the critical gust design condition for the inboard wing. It should be noted that the basic KC-135 wing is designed by maneuver rather than gust conditions. Analysis condition 2 represents a fuel transfer weight of the airplane. Analysis condition 3 represents the airplane with a full body and an empty wing, except for structural reserve fuel. Analysis condition 4 represents the operating-weight-empty airplane plus structural reserve fuel (the condition having the most-aft center of gravity). Analysis condition 5 represents the maximum-gross-weight airplane flying at the slowdown speed for severe gust. At this flight condition, the airplane is flying at maximum lift coefficient.

Table I. Summary of Analysis Conditions

Analysis condition number	Weight condition	Gross weight (lb)	Altitude (ft)	Equivalent airspeed (kn)	Mach number	Body fuel (lb)	Wing fuel (lb)
1	A	297,000	24,000	350	0.85	83,328	109,512
2	B	268,000	24,000	350	0.85	87,927	75,913
3	C	190 590	24,000	350	0.85	83,323	3,100
4	D	107,260	24,000	350	0.85	0	3,100
5	A	297,000	24,000	207	0.50	83,328	109,512



Figure 1. Speed-Altitude Conditions

2. Airplane Representation. The airplane used in this analysis is the KC-135. The airplane has a crew of four: pilot, copilot, navigator, and boom operator. It normally cruises at altitudes from 25,000 to 45,000 feet, gross weights to 297,000 pounds, and speeds to 525 knots (true air speed). The airplane has a wing span of 131 feet and an overall length of 136 feet. A two-view diagram is shown in figure 5, page 12. All major parts of the airplane except the fin and horizontal stabilizer are considered to be elastic in the analysis. Therefore, a rather comprehensive mass and stiffness description of the airplane is required. Simple beam-bending theory is used to represent the stiffness characteristics of the major components of the structure, such as the wing and forward and aft fuselage. The elastic axes are located approximately along the locus of shear centers of each component, except in the inboard portion of the wing where the elastic axis is determined from static tests.

a. Weights Data:

(1) The complete detailed description of panel weights (obtained from reference 3) used in this analysis is given in appendix I. The fuselage is divided into 18 weights panels and the panel weight and pitch inertia is determined for each panel. The wing semispan is divided into ten spanwise panels. Each of these panels are divided into five zones: leading edge, front spar, interspar, rear spar, and trailing edge. The weight and center of gravity are calculated for each zone and summed to give the total panel weight and center of gravity. The total panel-weight moments of inertia are computed by rotation and transfer of zone results into axes located parallel and perpendicular to the wing elastic axis.

(2) The mass properties for each engine, nacelle, and nacelle strut are combined and a lumped center of gravity is determined. Then, the nacelle mass moments of inertia are determined for axes located perpendicular and parallel to the airplane reference axis.

(3) Table II summarizes the weight conditions shown on the gross-weight-versus-center-of-gravity chart in figure 2.

Table II. Summary of Weight Conditions

Weight condition	Gross weight (lb)	CG (percent mac)	Fuel (lb)						
			Wing				Body		
			Outboard mains 1 & 4	Inboard mains 2 & 3	Center section	Outboard reserves	Forward	Aft	Upper
A	297,000	21.4	26,806	29,575	47,489	5,642	37,700	41,457	4,171
B	268,000	23.0	14,212	14,212	47,489	---	37,700	41,457	8,770
C	190,590	28.3	1,550	1,550	---	---	37,700	41,457	4,173
D	107,260	35.1	1,550	1,550	---	---	---	---	---
Capacity of tanks			26,806	29,575	47,489	5,642	37,700	41,457	14 131

Note: Fuel density at 6.5 pounds per gallon



Figure 2. Gross Weight Conditions Relative to Operational Center-of-Gravity Limits

b. Stiffness Data:

(1) The stiffness of each major component of the airplane (except nacelle struts) is described by a distribution of bending stiffness (EI) and torsional stiffness (GJ) along the elastic axis. The wing-section properties are computed using front and rear spar areas and all in-spar skin for both upper and lower surfaces. Values for modulus and shear modulus of elasticity (E and G) are 10.3×10^6 and 3.8×10^6 psi, respectively. The body-section properties are computed using stiffeners with full-skin effective in tension and a portion of skin effective in compression. The body cutout sections are analyzed individually by special analysis. The body center-section stiffness is estimated on the basis of variation of skin thickness, keel beam stiffness, and stringer size from body stations 620 through 820. The body stiffness is for the 2g dive maneuver condition (tension in the upper surface).

(2) The stiffness of the nacelle struts is calculated from the inertia of the nacelle-strut combination and the natural frequency and mode shapes obtained from ground shake tests (4, 5). The detailed stiffness data is given in appendix II.

c. Structural Damping Data:

(1) The structural damping used in this analysis is obtained from the ground vibration test of the 707-320B airplane. These values of damping are considered to be representative of the KC-135 airplane, since the structure of the two airplanes is similar. The values of structural damping coefficient are equal to twice the fraction of critical damping.

Mode	1	2	3	4	5	6	7	8
Structural damping coefficient	0.015	0.045	0.053	0.030	0.025	0.033	0.029	0.028

d. Aerodynamic Data:

(1) All of the basic aerodynamic data required for these analyses are obtained from a series of wind tunnel tests (6). Wind tunnel pressure-model test results are used to establish wing- and fuselage-airload distribution. The aerodynamic coefficients are corrected for model flexibility before they are used for full-scale airplane analysis, and are later refined to obtain final agreement between the aeroelastic analysis and actual airplane flight-load survey measurements.

(2) The unsteady aerodynamics are based on two-dimensional strip theory, based on wind tunnel model-pressure data, and are modified to include aerodynamic induction effects (7). These induction effects account for the aerodynamic pressure carryover between wing panels and between the wing and horizontal tail. This is accomplished by using a downwash matrix based on lifting-line theory. The dynamic downwash matrix includes pressure-carryover and pressure-transmittal functions to provide the proper magnitude and phasing of the carryover pressure. The section (or strip) aerodynamics for zero frequency are made to agree with the comparable aeroelastic solution. Included in the aerodynamics is the effect of gradual penetration into the gust.

(3) Body lift distribution is based on wind tunnel pressure-model data adjusted to make the rigid airplane pitch and lift derivatives match those used in the aeroelastic analysis. Detailed aerodynamic data are given in appendix III. The maximum lift correction due to compressibility occurs at mach 0.85.

3. Atmospheric Turbulence Representation:

a. There are two power spectra that are in current use to represent the atmosphere (8), and the following spectrum was selected by Dr. Houbolt for this analysis:

$$\Phi(\Omega) = \left(\frac{\sigma^2 L}{\pi}\right) \frac{1 + \frac{8}{3}(1.339\,L\Omega)^2}{\left[1 + (1.339\,L\Omega)^2\right]^{11/6}}$$

This power spectrum is plotted in figure 3 for scales of turbulence of 1,000, 3,000, and 5,000 feet. A value of 1 fps was used throughout the analysis for σ.

b. It is assumed that the turbulence is essentially "frozen" in space and is uniform normal to the line of flight of the airplane. The airplane passes over the turbulence much as an automobile would travel over a rough road. This approach assumes that the spanwise variation of turbulence (except for the effect of gradual penetration) is negligible.

4. Equations of Motion:

a. The airplane is represented by ten degrees of freedom: eight symmetrical free-free elastic modes, which are plotted in appendix IV, and rigid-airplane vertical translation and pitch. All flight control surfaces are assumed fixed in the 1g flight position. The response functions and zero-crossing rates are calculated from the following equations:

$$A = \int_0^{\omega_c} |H(\omega)|^2 \, \Phi_i(\omega) \, d\omega$$

$$N_o = \frac{1}{2\pi} \left[\frac{\int_0^{\omega_c} \omega^2 \, |H(\omega)|^2 \, \Phi_i(\omega) \, d\omega}{\int_0^{\omega_c} |H(\omega)|^2 \, \Phi_i(\omega) \, d\omega} \right]^{1/2}$$

b. To check the equations of motion, the loads are obtained from the equations of motion for a 1g gust condition and compared with those obtained from the aeroelastic solution. This is accomplished by first obtaining the



Figure 3. Analyticol Representotion of Atmospheric Spectra

equations of motion for zero-frequency gust input. Then the pitch- and elastic-mode generalized coordinate accelerations, the pitch and translation displacement, and all of the generalized coordinate velocities are equated to zero. The vertical translation acceleration is equated to 1g. To allow for an airplane moment balance, a tail load is added to the equations as an additional unknown. This tail load represents the change in tail lift required to balance the airplane while the airplane is flying through a gust that gives it a 1g acceleration. The solution of these equations gives the elastic mode deflections, the gust angle required for 1g acceleration, and the tail load required to balance the airplane. A comparison of wing loads is shown in figure 4 for analysis condition 1 (table 1).

c. The stress frequency response functions for the airplane structure are obtained from the complex frequency responses of the generalized coordinates. Shear, moment, and torsion coefficients are calculated for unit deflections of the generalized coordinates. These coefficients are multipled by the complex frequency responses of the generalized coordinates to obtain load frequency responses. The load frequency responses are multiplied by stress influence coefficients obtained from the airplane stress analysis to give the complex stress frequency response functions. The absolute value of these stress frequency-response functions is then used to obtain A and N_o. The stress frequency-response functions are given in complex form, and represent the ineremental stress relative to the gust velocity and 1g mean as shown below.





Figure 4. Comparison of Steady-State, Static, Elastic Solution with Aeroelastic Solution (Analysis Condition 1)

SECTION III

RESULTS AND DISCUSSION

Loads are obtained at two wing stations and two body stations where the gust margins are minimum. The margins of safety shown in table III are calculated using the gust load formula (2).

The wing and aft body are designed by maneuver conditions. The forward body is designed by braked-roll and pressurization conditions. However, for flight conditions, the margin of safety for gust for the forward body (which includes alleviation due to pitch) is less than for maneuver conditions. The fuselage and wing margins of safety are given in references 9 and 10, respectively.

Table III. Margins of Safety

Location	Segment number	Type of loading	Gust margins of safety
		WING	
27 percent semispan	10	Combined	0.20
27 percent semispan	14	Primarily tension	0.39
40.06 percent semispan (inboard of nacelle)	8	Combined	0.24
40.06 percent semispan (inboard of nacelle)	107	Combined	0.20
		BODY	
Body balance station 540	S-17	Shear load only	0.20
Body balance station 820	S-1	Tension load only	0.14

Figures 5 and 6 show these locations on the airplane. The curves of margin of safety in figure 6 are included to show the variation along the cross section of the wing. The margins of safety are based on the following equation:

$$\text{Margin of safety} = \frac{\text{Allowable ultimate principal stress}}{\text{Design ultimate principal stress}} - 1$$

The results of this investigation are response parameters A, zero-crossing rates N_0, stress transfer functions, and the ratios of incremental limit allowable stress to stress response parameter. The stress frequency-response functions are tabulated in appendix V.

The effects of variations in scale of turbulence on response parameters A and zero-crossing rates N_0 are shown in figures 7 and 8. The stress response parameters and zero-crossing rates are tabulated for each analysis



Figure 5. Locations at Which Stresses Are Obtained



Figure 6. Segment Locations and Typical Distributions of Margins of Safety



(a) 27 PERCENT SEMISPAN, SEGMENT NUMBER 10



(b) 27 PERCENT SEMISPAN, SEGMENT NUMBER 14

Figure 7. Response Parameters and Zero-Crossing Rates for Shear Stress



(a) 40.06 PERCENT SEMISPAN, SEGMENT NUMBER 8



(b) 40.06 PERCENT SEMISPAN, SEGMENT NUMBER 107

Figure 7 – – – Continued



Figure 7 – – – Concluded



(a) 27 PERCENT SEMISPAN, SEGMENT NUMBER 10



(b) 27 PERCENT SEMISPAN, SEGMENT NUMBER 14

Figure 8. Response Parameters and Zero Crossing Rates for Axial Stress



(a) 40.06 PERCENT SEMISPAN, SEGMENT NUMBER 8



(b) 40.06 PERCENT SEMISPAN, SEGMENT NUMBER 107

Figure 8 – – – Continued



Figure 8 --- Concluded

condition in appendix VI. The tabulated data show that changing the upper cutoff frequency from 10 to 15 and 20 cycles per second, as specified by Dr. Houbolt, has a negligible effect on A and N_o. This is due to the highest elastic modes in the analysis having frequencies less than 10 cps, resulting in little response above that frequency.

Zero-crossing rate versus the ratio of incremental limit allowable stress to stress response parameter is plotted in figures 9 and 10. It should be noted that the critical condition is that of maximum gross weight and high dynamic pressure combined with a scale of turbulence of 1,000 feet. These data are directly comparable to the $\sigma_{W''D}$ of reference 11, remembering that in that report the scale of turbulence is 2,500 feet and, whereas the KC-135 airplane is designed to a 2g load factor, the 720 airplane is designed to a 2.5g load factor. The consequence of this is that the KC-135 has lower margins of safety fc gust for the maximum gross weight conditions and a resultingly lower ratio of incremental limit allowable stress to stress response parameter.

The incremental limit allowable stresses tabulated in appendix VII are obtained from the stress interaction diagram for each section for which stresses are desired. few definitions follow:

1. Allowable stress: the maximum stress at which failure will occur

2. Limit allowable stress: the allowable stress divided by 1.50

3. Incremental stress: the increment of stress above the 1g flight stress

A typical stress interaction diagram is shown in figure 11. Curve 1 is a plot of the following equation:

$$\begin{pmatrix}\text{Limit allowable}\\ \text{shear principal stress}\end{pmatrix} = \sqrt{\left(\frac{\text{Axial skin tension stress}}{2}\right)^2 + (\text{Skin shear stress})^2}$$

Curve 2 is a plot of:

$$\begin{pmatrix}\text{Limit allowable}\\ \text{tensile principal stress}\end{pmatrix} = \left(\frac{\text{Axial skin tension stress}}{2}\right) + \sqrt{\left(\frac{\text{Axial skin}}{\text{tension stress}}{2}\right)^2 + \begin{pmatrix}\text{Skin}\\ \text{shear}\\ \text{stress}\end{pmatrix}^2}$$



Figure 9. Zero-Crossing Rates Versus $\sigma_W \eta_D$ (Linear Plot)



Figure 9 – – – Continued



Figure 9 – – – Concluded



Figure 10. Zero-Crossing Rates Versus $\sigma_W \eta_D$ (Semilog Plot)



Figure 10 --- Continued



Figure 10 – – – Concluded



Figure 11. Stress Interaction Diagram

As shown in figure 11, the stress interaction curve used in design is formed by portions of these two curves and represents the combination of axial tension and shear that give the lower of the limit allowable shear or tensile principal stresses. Curve 3, the stress interaction curve for compression and shear, is a plot of:

$$\left(\begin{array}{c}\text{Limit allowable}\\ \text{compression stress}\end{array}\right) = \frac{\left(\begin{array}{c}\text{Axial segment}\\ \text{compression stress}\end{array}\right)}{2} + \sqrt{\left[\frac{\left(\begin{array}{c}\text{Axial segment}\\ \text{compression stress}\end{array}\right)}{2}\right]^2 + \left[\left(\begin{array}{c}\text{Skin}\\ \text{shear}\\ \text{stress}\end{array}\right) \frac{\left(\begin{array}{c}\text{Limit allowable}\\ \text{compression stress}\end{array}\right)}{\left(\begin{array}{c}\text{Limit allowable}\\ \text{shear principal stress}\end{array}\right)}\right]^2}$$

The segment referred to in the equations includes the stringer area in addition to that of the skin; the area of both is used when computing compressive stresses. The limit allowable compressive stress is not a true principal stress, and its equation is an empirical variation of Moher's circle equation for compression principal stress. Knowing the limit allowable shear, tension, and compression stresses, the stress interaction diagram is drawn. The next step is to determine the incremental limit allowable stresses.

The incremental limit allowable stress is derived in the following manner: The 1g flight axial and shear stresses at a particular point in the wing are plotted as point G in figure 11. Point H in figure 11 is determined by drawing a line from point G having a slope equal to the ratio of axial stress response parameter to the shear stress response parameter. The slope of line G-H is based on the assumption of 100-percent correlation between axial and shear stress. The resulting incremental limit allowable axial and shear stresses are shown in the figure. A method of analysis which includes the effect of correlation between stresses is described in reference 11.

SECTION IV

CONCLUSIONS

The minimum value of $\sigma_W \eta_D$ for all the conditions investigated is 53, which is for the maximum-gross-weight high-speed flight condition and the 1,000-foot scale of turbulence.

The most critical (largest) value of stress response parameter is for the 1,000-foot scale of turbulence and the heavy gross weight, high-speed conditions. Reducing the gross weight, lowering the speed, and increasing the scale of turbulence reduces the value of the stress response parameter.

The largest zero-crossing rate is associated with the lowest-gross-weight airplane and is little affected by the scale of turbulence.

The stress response parameter and zero-crossing rate are little affected by the upper cutoff frequency, where the cutoff frequency is above the highest modal frequency included in the analysis.

APPENDIX I
WEIGHT DATA

Table IV. Weight Condition A (Maximum Zero Flap Weight; Gross Weight: 297,000 Pounds)

BODY

Panel number	Body balance station	Weight (lb)	Center-of-gravity location (in.)			Moment of inertia about cg ($lb\text{-}in.^2 \times 10^{-6}$)		
			Body balance station	Body buttock line	Body waterline[e]	Pitch	Roll	Yaw
1	130 to 259	2,771	220	0	218	4.45	3.95	3.57
2[a]	259 to 360	5,290	320	↑	207	15.5	14.6	11.3
3	360 to 420	9,810	393		189	12.1	18.1	12.6
4	420 to 480	11,715	450		182	11.9	20.5	15.7
5	480 to 540	11,482	510		181	10.4	18.8	15.3
6	540 to 620	11,633	571		182	12.3	31	15.9
7	620 to 755	3,055	689		210	11	11.2	9.33
8	755 to 820	1,500	802		208	3.68	5.47	2.88
9[b]	820 to 890	9,333	872		185	12.7	27.2	26.5
10	890 to 960	2,037	926		209	5.11	7.43	4.03
11	960 to 1020	11,823	989		183	10.1	18.7	15.9
12	1020 to 1080	10,717	1,050		189	8.61	15.9	13.7
13	1080 to 1140	10,042	1,110		184	8.56	16.3	12.2
14	1140 to 1200	10,004	1,170		189	10.6	18.3	12.4
15	1200 to 1280	5,958	1,223		191	5.47	9.94	7.57
16	1280 to 1360	1,252	1,321		217	2.58	3.79	2.55
17	1360 to 1440	5,035	1,406	↓	220	3.63	6.45	6.85
18[c]	1440 to 1676	9,697	1,569	0	288	130	113	102

WING/SIDE

1	0 to 70.5	14,177	732.2	36.5	182.7	47.1	7.73	51.7
2[d]	70.5 to 157.2	19,774	764.2	112.7	185.8	92.6	15	103
3	157.2 to 235.8	11,893	805.4	195.6	192.4	42.2	6.05	47.4
4	235.8 to 314.4	8,004	855.1	271.1	191.3	18.1	4.04	21
5	314.4 to 393	6,593	897.4	348.6	195.6	12.3	3.82	15.3
6	393.0 to 471.6	4,733	950.1	429.2	205.2	7.56	2.70	9.80
7	471.6 to 550.2	1,798	988.7	496.8	210.7	3.59	0.818	4.23
8	550.2 to 628.8	1,937	1,058.2	595.2	236.7	1.93	1.12	2.44
9	628.8 to 707.4	1,615	1,092	663.9	243.1	1.37	0.911	2.15
10	707.4 to 786.6	1,558	1,149.1	735.2	249.7	0.683	0.314	0.970

Fuel density at 6.5 pounds per gallon

Notes: a Includes nose gear in the UP position
b Includes tires, truck assembly, air, wheels, and side strut of main landing gear in the UP position
c Includes the horizontal tail, vertical tail, and refueling boom
d Includes inner cylinder, outer cylinder, trunnion, and landing gear support structure in wing
e Cruise condition

Table IV --- Concluded

TOTAL AIRPLANE

Airplane section	Weight (lb)	Center-of-gravity location (in.)			Moment of inertia about cg ($lb\text{-}in.^2 \times 10^{-6}$)		
		Body balance station	Body buttock line	Body waterline[e]	Pitch	Roll	Yaw
Body	133,154	858.4	0	196.9	19,200	452	19,200
Wing	142,164	823.8	212.4	192.9	1,770	3,960	5,650
Nacelles	10,938	713.7	322	159	16.9	2.64	15.7
Nacelles	10,744	898.1	552	197	16.2	2.60	15
Total/avg	297,000	837.9	0	193.6	21,400	15,300	35,900

Table V. Weight Condition B (Maximum Transfer Weight; Gross Weight: 268,000 Pounds)

BODY

Panel number	Body balance station	Weight (lb)	Center-of-gravity location (in.)			Moment of inertia about cg ($lb\text{-}in.^2 \times 10^{-6}$)		
			Body balance station	Body buttock line	Body waterline[e]	Pitch	Roll	Yaw
1	130 to 259	2,771	220	0	216	4.45	3.95	3.57
2[a]	259 to 360	5,290	320	↓	207	15.5	14.6	11.3
3	360 to 420	9,810	393		189	12.1	18.1	12.6
4	420 to 480	11,715	450		182	11.9	20.5	15.7
5	480 to 540	11,482	510		181	10.4	18.8	15.3
6	540 to 620	11,633	571		182	12.3	21	15.9
7	620 to 755	3,055	689		210	11	11.2	9.33
8	755 to 820	1,500	802		208	3.68	5.47	2.98
9[b]	820 to 890	9,333	872		185	12.7	7.2	26.5
10	890 to 960	2,037	926		209	5.11	7.43	4.03
11	960 to 1020	11,823	989		183	10.1	18.7	15.9
12	1020 to 1080	10,717	1,050		189	8.61	15.9	13.7
13	1080 to 1140	10,042	1,110		184	8.56	16.3	12.2
14	1140 to 1200	10,004	1,170		189	10.6	16.3	12.4
15	1200 to 1280	5,958	1,223		191	5.47	9.94	7.57
16	1280 to 1360	1,252	1,321		217	2.58	3.79	2.55
17	1360 to 1440	9,273	1,408	↓	233	6.38	11.6	11.8
18[c]	1440 to 1676	10,057	1,564	0	287	136	114	108

WING SIDE

1	0 to 70.5	14,177	732.2	36.5	182.7	47.1	7.73	51.7
2[d]	70.5 to 157.2	18,531	765.4	110.5	181	89	12.8	98.4
3	157.2 to 235.8	7,039	819.3	195.5	177.8	27	4.49	30.9
4	235.8 to 314.4	6,177	868.5	275.9	185.9	12.4	2.95	14.8
5	314.4 to 393	4,521	900	346.6	188.8	8.92	2.45	11.1
6	393.0 to 471.6	1,598	965.6	424.8	197	3.38	0.947	4.24
7	471.6 to 550.2	951	1,016	506.5	205.5	1.60	0.427	1.97
8	550.2 to 628.8	647	1,053.6	580.7	220.1	1.09	0.311	1.37
9	628.8 to 707.4	378	1,098.5	660	233.4	0.690	0.209	0.885
10	707.4 to 786.6	264	1,151.1	744.5	255.9	0.525	0.204	0.721

Fuel density at 6.5 pounds per gallon

Notes: a Includes nose gear in the UP position
b Includes tires, truck assembly, air, wheels, and side strut of main landing gear in the UP position
c Includes the horizontal tail, vertical tail, and refueling boom
d Includes inner cylinder, outer cylinder, trunnion, and landing gear support structure in wing
e Cruise condition

Table V --- Concluded

TOTAL AIRPLANE

Airplane section	Weight (lb)	Center-of-gravity location (in.)			Moment of inertia about cg ($lb\text{-}in.^2 \times 10^{-6}$)		
		Body balance station	Body buttock line	Body waterline[e]	Pitch	Roll	Yaw
Body	137,752	876.9	0	198.7	20,600	468	20,500
Wing	108,566	804.6	169.4	184.3	1,110	2,140	3,220
Nacelles	10,938	713.7	322	159	16.9	2.64	15.7
Nacelles	10,744	898.1	552	197	16.2	2.60	15
Total/avg	268,000	841.8	0	191.2	22,300	10,200	31,800

Table VI Weight Condition C (Intermediate Gross Weight with Structural Reserve Fuel; Gross Weight: 190,590 Pounds)

BODY

Panel number	Body balance station	Weight (lb)	Center-of-gravity location (in.)			Moment of inertia about cg ($lb\text{-}in.^2 \times 10^{-6}$)		
			Body balance station	Body buttock line	Body waterline[e]	Pitch	Roll	Yaw
1	130 to 259	2,771	220	0	218	4.45	3.95	3.57
2[a]	259 to 360	5,290	320	↑	207	15.5	14.6	11.3
3	360 to 420	9,810	393		189	12.1	18.1	12.6
4	420 to 480	11,715	450		182	11.9	20.5	15.7
5	480 to 540	11,482	510		181	10.4	18.8	15.3
6	540 to 620	11,633	571		182	12.3	21	15.9
7	620 to 755	3,055	689		210	11	11.2	9.33
8	755 to 820	1,500	802		208	3.68	5.47	2.88
9[b]	820 to 890	9,333	872		185	12.7	27.2	26.5
10	890 to 960	2,037	926		209	5.11	7.43	4.03
11	960 to 1020	11,023	909		183	10.1	18.7	15.9
12	1020 to 1080	10,717	1,050		189	8.61	15.9	13.7
13	1080 to 1140	10,042	1,110		184	8.56	16.3	12.2
14	1140 to 1200	10,004	1,170		189	10.6	18.3	12.4
15	1200 to 1280	5,956	1,223		191	5.47	9.94	7.57
16	1280 to 1360	1,252	1,321		217	2.58	3.79	2.55
17	1360 to 1440	5,035	1,406	↓	220	3.63	6.45	6.85
18[c]	1440 to 1676	9,699	1,569	0	288	130	113	102

WING/SIDE

1	0 to 70.5	1,645	746.3	45.6	173	6.13	1.10	6.73
2[d]	70.5 to 157.2	5,673	816	115.5	176.3	26.9	4.65	30.6
3	157.2 to 235.8	2,793	842.2	196.6	176.1	13.4	2.62	15.4
4	235.8 to 314.4	2,785	868.7	261	180.8	6.24	1.51	7.50
5	314.4 to 393	1,569	906.3	344.3	186.5	4.47	0.876	5.20
6	393.0 to 471.6	1,171	974.9	432.6	196.5	2.58	0.654	3.16
7	471.6 to 550.2	951	1,016	506.5	205.5	1.60	0.427	1.97
8	550.2 to 628.8	647	1,053.6	580.7	220.1	1.09	0.311	1.37
9	628.8 to 707.4	378	1,098.5	660	233.4	0.690	0.209	0.885
10	707.4 to 786.6	264	1,161.1	744.5	253.9	0.525	0.204	0.721

Fuel density at 6.5 pounds per gallon

Notes: a Includes nose gear in the UP position
b Includes tires, truck assembly, air, wheels, and side strut of main landing gear in the UP position
c Includes the horizontal tail, vertical tail, and refueling boom
d Includes inner cylinder, outer cylinder, trunnion, and landing gear support structure in wing
e Cruise condition

Table VI --- Concluded

TOTAL AIRPLANE

Airplane section	Weight (lb)	Center-of-gravity location (in.)			Moment of inertia about cg ($lb\text{-}in.^2 \times 10^{-6}$)		
		Body balance station	Body buttock line	Body waterline[e]	Pitch	Roll	Yaw
Body	133,156	858.4	0	196.9	19,200	452	19,200
Wing	35,752	870.5	243.7	184.4	422	1,020	1,420
Nacelles	10,938	713.7	322	159	16.9	2.64	15.7
Nacelles	10,744	898.1	552	197	16.2	2.60	15
Total/avg	190,590	854.6	0	192.4	20,000	8,030	27,400

Table VII. Weight Condition D (Operating Weight Empty with Structural Reserve Fuel; Gross Weight: 107,260 Pounds)

BODY

Panel number	Body balance station	Weight (lb)	Center-of-gravity location (in.)			Moment of inertia about cg ($lb\text{-}in.^2 \times 10^{-6}$)		
			Body balance station	Body buttock line	Body waterline[e]	Pitch	Roll	Yaw
1	130 to 259	2,771	220	0	218	4.45	3.95	3.57
2[a]	259 to 360	5,290	320		207	15.5	14.6	11.3
3	360 to 420	2,258	384		215	6.14	9.33	4.78
4	420 to 480	1,495	451		220	3.59	5.45	2.79
5	480 to 540	1,262	513		214	3.03	4.60	2.36
6	540 to 620	1,925	584		212	4.62	7.02	3.60
7	620 to 755	3,055	689		210	11	11.2	9.33
8	755 to 820	1,500	802		208	3.68	5.47	2.88
9[b]	820 to 890	9,333	872		185	12.7	27.2	26.5
10	890 to 960	2,037	926		209	5.11	7.43	4.03
11	960 to 1020	1,806	982		185	4.33	6.59	3.37
12	1020 to 1080	1,104	1,051		211	2.65	4.03	2.06
13	1080 to 1140	1,146	1,110		214	2.63	4.07	2.14
14	1140 to 1200	1,834	1,174		221	3.94	6.26	3.43
15	1200 to 1280	1,197	1,238		215	2.74	3.97	2.52
16	1280 to 1360	1,252	1,321		217	2.58	3.79	2.55
17	1360 to 1440	1,273	1,395		223	2.07	2.83	2.11
18[c]	1440 to 1676	9,288	1,574	0	291	121	111	95.3

WING/SIDE

1	0 to 70.5	1,645	746.3	45.6	173	6.13	1.10	6.73
2[d]	70.5 to 157.2	5,673	816	115.5	176.3	26.9	4.65	30.6
3	157.2 to 235.8	2,793	842.2	196.6	176.1	13.4	2.62	15.4
4	235.8 to 314.4	2,785	868.7	261	180.8	6.24	1.51	7.50
5	314.4 to 393	1,569	906.3	344.3	166.5	4.47	0.876	5.20
6	393.0 to 471.6	1,171	974.9	432.6	196.5	2.58	0.654	3.16
7	471.6 to 550.2	951	1,016	506.5	205.5	1.60	0.427	1.97
8	550.2 to 628.8	647	1,053.6	580.7	220.1	1.09	0.311	1.37
9	628.8 to 707.4	378	1,098.5	660	233.4	0.690	0.209	0.885
10	707.4 to 786.6	264	1,161.1	744.5	253.9	0.525	0.204	0.721

Fuel density at 6.5 pounds per gallon

Notes: a Includes nose gear in the UP position
b Includes tires, truck assembly, air, wheels, and side strut of main landing gear in the UP position
c Includes the horizontal tail, vertical tail, and refueling boom
d Includes inner cylinder, outer cylinder, trunnion, and landing gear support structure in wing
e Cruise condition

Table VII --- Concluded

TOTAL AIRPLANE

Airplane section	Weight (lb)	Center-of-gravity location (in.)			Moment of inertia about cg ($lb\text{-}in.^2 \times 10^{-6}$)		
		Body balance station	Body buttock line	Body waterline[e]	Pitch	Roll	Yaw
Body	49,826	900	0	221.4	9,300	381	9,810
Wing	35,752	870.5	243.7	134.4	422	1,020	1,420
Nacelles	10,938	713.7	322	159	16.9	2.64	15.7
Nacelles	10,744	898.1	552	197	16.2	2.60	15
Total/avg	107,260	871	0	200.3	10,700	7,910	18,100

APPENDIX II
STIFFNESS DATA



Figure 12. Wing Vertical-Bending and Torsion Stiffness



Figure 13. Wing Elastic-Axis Location



Figure 14. Body Vertical-Bending Section Moment of Inertia



Figure 15. Body Elastic-Axis Location

Table VIII. Nacelle Cantilever Mode Shapes and Frequencies

Location	Vertical bending		Side bending		
	Z (in.)	θ_y (rad.)	Y (in.)	θ_z (rad.)	θ_x (rad.)
MODE SHAPES					
Inboard nacelle	108	−1	1	0.0136	−0.0057
Outboard nacelle	98	−1	1	0.0150	−0.0061
FREQUENCIES (FROM REFERENCE 4)					
Inboard nacelle	4.44 cps		2.31 cps		
Outboard nacelle	4.81 cps		2.50 cps		



APPENDIX III
AERODYNAMIC DATA



Figure 16. Wing Lift Distribution



Figure 17. Local Center-of-Pressure Location



Figure 18. Body Lift Distribution (Mach 0.85)



Figure 19. Body Lift Distribution (Mach 0.50)

Table IX. Rigid-Airplane Derivatives $\left(\frac{1}{Radian}\right)$

Mach number	Analysis		Wind tunnel (from reference 6)	
	$C_{L\alpha}$	$C_{M\alpha}$	$C_{L\alpha}$	$C_{M\alpha}$
0.50	5.06	1.51	5.14	1.50
0.85	6.49	1.68	6.71	1.70

$L = qsC_{L\alpha}\alpha$

$M = qs\bar{c}C_{M\alpha}\alpha$

L = lift

M = pitching moment about body station 837.9

q = dynamic pressure

s = wing area = 2,433 square feet

α = angle of attack

c = wing mean aerodynamic chord = 241.8 inches

Table X. Rigid-Horizontal-Stabilizer Lift at 24,000-Foot Altitude

Mach number	Lift (lb/rad.)	For flexible horizontal stabilizer, multiply lift by:
0.50	61,068	0.971
0.80	183,156	0.923

Note: Horizontal stabilizer center of lift is at body balance station 1581.3.

APPENDIX IV
AIRPLANE FREE-FREE MODE SHAPES



Figure 20. Wing Vertical Displacement in the Normalized Free-Free Airplane Modes; 297,000-Pound Gross Weight (Weight Condition A)



Figure 21. Wing Torsional Displacement in the Normalized Free-Free Airplane Modes; 297,000-Pound Gross Weight (Weight Condition A)



Figure 22. Body Vertical Displacement in the Normalized Free-Free Airplane Modes; 297,000-Pound Gross Weight (Weight Condition A)

Table XI. Nacelle Mode Shapes (Weight Condition A)

Nacelle position	Displacement	Mode number							
		1	2	3	4	5	6	7	8
Inboard	$\bar{x}$	−1.78	−1.68	−3.89	−8.30	+2.31	+15.20	+7.51	−5.05
	$\bar{y}$	−5.42	+74.55	−8.49	−18.88	+0.84	+2.72	−0.16	−0.28
	$\bar{z}$	+0.27	−8.29	−16.25	−51.95	−31.09	+125.88	−6.64	+18.78
	θ_x	+0.0923	−0.4413	+0.0280	+0.0091	+0.0170	+0.0884	−0.0754	+0.0824
	θ_y	+0.0375	+0.0565	+0.1293	+0.3345	+0.0751	−1.0573	−0.1073	−0.2043
	θ_z	−0.0214	+1.0000	−0.1327	−0.3401	+0.0299	+0.1254	−0.0669	+0.0649
Outboard	$\bar{x}$	−3.37	−3.72	−10.29	−28.16	+4.64	−11.00	+8.47	−0.62
	$\bar{y}$	−11.32	+1.70	+70.74	−54.94	+12.57	+4.17	+0.98	+0.58
	$\bar{z}$	+42.33	+6.97	−21.99	−85.85	+41.71	−55.77	+12.70	−3.20
	θ_x	+0.2173	−0.0159	−0.5017	+0.2549	+0.1643	+0.0990	+0.3341	−0.1780
	θ_y	+0.0425	+0.1035	+0.3005	+0.8969	−0.3985	+0.5370	−0.3467	+0.2164
	θ_z	−0.0407	+0.0206	+1.0000	−0.8936	+0.3983	+0.1712	+0.3107	−0.1431

Note: Sign convention for nacelle cg positive displacements

$\bar{x}$	Aft	θ_x	Roll, bottom inboard
$\bar{y}$	Outboard	θ_y	Pitch, nose up
$\bar{z}$	Down	θ_z	Yaw, nose outboard



Figure 23. Wing Vertical Displacement in the Normalized Free-Free Airplane Modes; 268,000-Pound Gross Weight (Weight Condition B)



Figure 24. Wing Torsional Displacement in the Normalized Free-Free Airplane Modes; 268,000-Pound Gross Weight (Weight Condition B)



Figure 25. Body Vertical Displacement in the Normalized Free-Free Airplane Modes; 268,000-Pound Gross Weight (Weight Condition B)

Table XII. Nacelle Mode Shapes (Weight Condition B)

Nacelle position	Displacement	Mode number							
		1	2	3	4	5	6	7	8
Inboard	$\bar{x}$	−1.42	−0.73	−1.41	−7.79	−3.03	+3.82	+4.94	+5.54
	$\bar{y}$	−6.81	+73.67	+3.84	−2.47	+0.38	−1.12	+0.04	+0.22
	$\bar{z}$	+5.77	−2.51	−0.97	−39.67	−70.28	+51.44	+3.75	−5.20
	θ_x	+0.1234	−0.4220	−0.0095	−0.0217	+0.0084	+0.0541	−0.0174	−0.0462
	θ_y	+0.0248	+0.0225	+0.0353	+0.3295	+0.3905	−0.4251	−0.1930	−0.0489
	θ_z	−0.0578	+1.0000	+0.0629	−0.0641	+0.0141	+0.0667	−0.0139	−0.0354
Outboard	$\bar{x}$	−0.19	−0.56	−1.76	−19.06	+0.64	−13.20	+2.21	+0.51
	$\bar{y}$	−15.85	−6.20	+67.73	−3.85	+9.75	+1.29	−0.60	−1.11
	$\bar{z}$	+57.66	+5.46	+8.93	−29.74	+45.09	−26.40	+3.84	+3.04
	θ_x	+0.2614	+0.0571	−0.4315	−0.0129	+0.1461	+0.0487	+0.2417	+0.2426
	θ_y	−0.0576	+0.0029	+0.0251	+0.5765	−0.3259	+0.4707	−0.0855	−0.1253
	θ_z	−0.0944	−0.0763	+1.0000	−0.0890	+0.3251	+0.0688	+0.1982	+0.1886

Note: Sign convention for nacelle cg positive displacements

$\bar{x}$	Aft	θ_x	Roll, bottom inboard
$\bar{y}$	Outboard	θ_y	Pitch, nose up
$\bar{z}$	Down	θ_z	Yaw, nose outboard



Figure 26. Wing Vertical Displacement in the Normalized Free-Free Airplane Modes; 190,590-Pound Gross Weight (Weight Condition C)



Figure 27. Wing Torsional Displacement in the Normalized Free-Free Airplane Modes; 190,590-Pound Gross Weight (Weight Condition C)



Figure 28. Body Vertical Displacement in the Normalized Free-Free Airplane Modes; 190,590-Pound Gross Weight (Weight Condition C)

Table XIII. Nacelle Mode Shapes (Weight Condition C)

Nacelle position	Displacement	Mode number							
		1	2	3	4	5	6	7	8
Inboard	$\bar{x}$	−1.28	−0.72	−1.25	−7.34	−2.69	+4.01	+5.92	+5.88
	$\bar{y}$	−9.21	−73.66	+4.31	−2.15	−0.18	+1.10	ZERO	+0.35
	$\bar{z}$	+5.35	−2.51	−0.31	−38.49	−90.38	+45.24	+1.88	−4.77
	θ_x	+0.1256	−0.4218	−0.0100	−0.0195	−0.0053	+0.0570	ZERO	−0.0530
	θ_y	+0.0219	+0.0222	+0.0298	+0.3146	+0.5241	−0.3998	−0.2097	−0.0338
	θ_z	−0.0632	+1.0000	+0.0709	−0.0561	−0.0079	+0.0687	−0.0001	−0.0386
Outboard	$\bar{x}$	+0.04	−0.53	−1.37	−17.78	+14.83	−12.19	+4.54	+3.14
	$\bar{y}$	−16.83	−6.91	+67.23	−1.85	+6.36	+1.68	−1.26	−1.68
	$\bar{z}$	+57.98	+5.93	+11.59	−23.53	+62.89	−21.60	+1.54	+0.51
	θ_x	+0.2724	+0.0636	−0.4198	−0.9065	+0.1306	+0.0688	+0.2679	+0.2479
	θ_y	−0.0665	+0.0010	+0.0081	+0.5188	−0.7789	+0.4108	−0.1317	−0.1838
	θ_z	−0.1049	−0.0849	+1.0000	−0.0430	+0.2427	+0.0944	+0.2075	+0.1816

Note: Sign convention for nacelle cg positive displacements

$\bar{x}$	Aft	θ_x	Roll, bottom inboard
$\bar{y}$	Outboard	θ_y	Pitch, nose up
$\bar{z}$	Down	θ_z	Yaw, nose outboard



Figure 29. Wing Vertical Displacement in the Normalized Free-Free Airplane Modes; 107,260-Pound Gross Weight (Weight Condition D)



Figure 30. Wing Torsional Displacement in the Normalized Free-Free Airplane Modes; 107,260-Pound Gross Weight (Weight Condition D)



Figure 31. Body Vertical Displacement in the Normalized Free-Free Airplane Modes; 107,260-Pound Gross Weight (Weight Condition D)

Table XIV. Nacelle Mode Shapes (Weight Condition D)

Nacelle position	Displacement	Mode number							
		1	2	3	4	5	6	7	8
Inboard	$\bar{x}$	−1.53	−0.79	−1.64	−7.12	+5.13	+5.05	+5.54	+5.79
	$\bar{y}$	−10.75	+73.58	+4.77	−2.22	+1.48	+0.66	+0.25	+0.59
	$\bar{z}$	−1.92	−3.27	−3.52	−33.41	+94.06	+21.32	−2.44	−5.21
	θ_x	+0.1351	−0.4204	−0.0103	−0.0231	+0.0622	+0.0611	−0.0393	−0.0778
	θ_y	+0.0366	+0.0251	+0.0465	+0.2945	−0.6963	−0.2944	−0.0972	+0.0486
	θ_z	−0.0833	+1.0000	+0.0793	−0.0604	+0.0801	+0.0639	−0.0288	−0.0552
Outboard	$\bar{x}$	−0.16	−0.57	−1.84	− 18.93	−15.69	−7.66	+5.19	+5.52
	$\bar{y}$	−19.48	−8.26	+66.64	−3.14	−0.43	+2.00	−1.66	−1.75
	$\bar{z}$	+54.51	+6.54	+13.17	−28.40	−47.22	−5.98	+0.48	−1.07
	θ_x	+0.2969	+0.0759	−0.4062	−0.0146	−0.0133	+0.1489	+0.2558	+0.2235
	θ_y	−0.0653	+0.0004	+0.0144	+0.5663	+0.7015	+0.1928	−0.1739	−0.2063
	θ_z	−0.1371	−0.1016	+1.0000	−0.0763	−0.0202	+0.1700	+0.1889	+0.1589

Note: Sign convention for nacelle cg positive displacements

$\bar{x}$	Aft	θ_x	Roll, bottom inboard
$\bar{y}$	Outboard	θ_y	Pitch, nose up
$\bar{z}$	Down	θ_z	Yaw, nose outboard

APPENDIX V
STRESS FREQUENCY RESPONSE FUNCTIONS

Table XV Stress Frequency Response Functions (Analysis Condition 1)

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMISPAN 27 SEGMENT NUMBER 10

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				FREQUENCY
REAL	IMAGINARY	REAL	IMAGINARY			CPS
0.847215-01	0.35385E 02	-0.60681E 00	0.30363E 03	0.	-0.	0.10
0.24347E 02	0.29947E 02	0.19898E 03	0.26210E 03	-0.	-0.	0.20
0.44132E 02	0.83697E 01	0.37620E 03	0.76906E 02	-0.	-0.	0.30
0.55393E 02	-0.51332E 01	0.47339E 03	-0.19261E 02	-0.	0.	0.40
0.53094E 02	-0.16505E 02	0.45739E 03	-0.14192E 03	-0.	0.	0.50
0.46190E 02	-0.22434E 02	0.40073E 03	-0.19748E 03	-0.	0.	0.60
0.41253E 02	-0.27016E 02	0.35800E 03	-0.24096E 03	-0.	0.	0.70
0.38231E 02	-0.31773E 02	0.32986E 03	-0.28530E 03	-0.	0.	0.80
0.36571E 02	-0.37815E 02	0.31144E 03	-0.33932E 03	-0.	0.	0.90
0.35926E 02	-0.59253E 02	0.29597E 03	-0.51720E 03	-0.	0.	1.00
0.36653E 02	-0.57188E 02	0.27761E 03	-0.80276E 03	-0.	0.	1.10
0.33495E 02	-0.12897E 03	0.20941E 03	-0.10256E 04	0.	-0.	1.20
0.22848E 02	-0.16771E 03	0.98360E 02	-0.12780E 04	0.	-0.	1.30
-0.42896E 01	-0.18946E 03	-0.14204E 03	-0.14050E 04	0.	-0.	1.40
-0.32143E 02	-0.20625E 03	-0.36351E 03	-0.14789E 04	0.	-0.	1.47
-0.75685E 03	-0 17111E 03	-0.69482E 03	-0.10976E 04	0.	-0.	1.50
-0.19911E 03	-0.35902E 02	-0.13332E 04	-0.10140E 03	-0.	-0.	1.55
-0.23925E 03	0.46462E 02	-0.16662E 04	0.48830E 03	-0.	0.	1.60
-0.18287E 03	0.70084E 02	-0.11743E 04	0.40670E 03	-0.	0.	1.65
-0.70840E 02	0.66637E 02	-0.36373E 03	0.30779E 03	-0.	0.	1.80
-0.45308E 02	0.62249E 02	-0.20150E 03	0.23180E 03	-0.	0.	1.90
-0.30738E 02	0.63716E 02	-0.12039E 03	0.17513E 03	-0.	0.	2.00
-0.20436E 02	0.69880E 02	-0.77273E 02	0.12793E 03	-0.	0.	2.10
-0.96218E 01	0.74699E 02	-0.54149E 02	0.67179E 02	-0.	0.	2.20
0.14082E 02	0.70093E 02	-0.52018E 02	0.70081E 02	0.	0.	2.30
0.17233E 02	0.77041E 02	-0.52613E 02	0.46193E 02	0.	0.	2.39
0.24472E 02	0.79877E 02	-0.63530E 02	0.36245E 02	0.	0.	2.50
0.34041E 02	0.79724E 02	-0.85646E 02	0.35754E 02	0.	0.	2.60
0.39009E 02	0.72921E 02	-0.97472E 02	0.56486E 02	0.	0.	2.70
0.50533E 02	0.63392E 02	-0.12910E 03	0.10032E 03	0.	0.	2.80
0.50381E 02	0.69316E 02	-0.12646E 03	0.11476E 03	0.	0.	2.90
0.49535E 02	0.84011E 02	-0.84240E 02	0.97083E 02	0.	0.	2.99
0.54631E 02	0.10597E 03	-0.63312E 02	0.66091E 02	0.	0.	3.00
0.10102E 03	0.10496E 03	-0.68865E 02	0.56672E 02	0.	0.	3.05
0.16744E 03	-0.10530E 03	-0.96249E 02	0.14603E 03	0.	-0.	3.10
0.29234E 03	-0.16149E 03	-0.14615E 03	0.14327E 03	0.	-0.	3.20
-0.28309E 02	-0.11812E 03	0.16352E 02	0.11391E 03	-0.	-0.	3.30
-0.56137E 02	-0.93940E 02	0.26914E 32	0.96733E 02	-0.	-0.	3.40
-0.71372E 02	-0.85784E 02	0.30791E 02	0.90310E 02	-0.	-0.	3.50
-0.81036E 02	-0.83382E 02	0.33323E 02	0.87505E 02	-0.	-0.	3.60
-0.88238E 02	-0.82515E 02	0.36221E 02	0.60883E 02	-0.	-0.	3.70
-0.10972E 03	-0.71410E 02	0.43080E 02	0.62441E 02	-0.	-0.	3.80
-0.15204E 03	0.89707E 02	0.53821E 02	0.43047E 02	-0.	0.	3.90
-0.20169E 03	0.16767E 03	0.10323E 02	0.61216E 02	-0.	0.	3.99
-0.16605E 03	0.21643E 03	0.47720E 01	0.77443E 02	-0.	0.	4.00
-0.70035E 02	0.97863E 02	0.14542E 02	0.62131E 02	-0.	0.	4.05
0.75312E 02	0.12316E 02	0.47708E 02	0.42110E 02	0.	-0.	4.10
0.67726E 02	-0.54085E 01	0.47620E 02	0.32363E 02	0.	-0.	4.20
0.74912E 02	-0.10415E 02	0.44216E 02	0.25340E 02	0.	-0.	4.30
0.10327E 02	-0.10380E 02	0.42629E 02	0.18653E 02	0.	-0.	4.40
0.18707E-00	-0.92066E 01	0.47327E 02	0.11468E 02	-0.	-0.	4.50
-0.35289E 01	-0.84821E 01	0.60177E 02	0.20729E 01	-0.	-0.	4.60
-0.49874E 01	-0.67778E 01	0.73033E 02	-0.33318E 02	-0.	0.	4.70
-0.69816E 01	-0.61227E 01	0.95124E 02	-0.82493E 02	-0.	0.	4.80
-0.72581E 01	-0.69439E 01	0.84297E 02	-0.85831E 02	-0.	0.	4.90
-0.70801E 01	-0.44116E 01	-0.17810E 02	-0.36016E 02	0.	0.	5.00
-0.78159E 01	-0.37278E 01	-0.30270E 02	-0.13876E 02	0.	-0.	5.10
-0.91329E 01	-0.25388E 01	-0.22972E 02	-0.77197E 01	-0.	-0.	5.20
-0.10893E 02	-0.11493E 01	-0.20631E 02	-0.36667E 01	-0.	-0.	5.30
-0.13055E 02	0.38635E 01	-0.23939E 02	0.10526E 02	-0.	-0.	5.40
-0.17386E 02	0.60353E 01	-0.35203E 02	0.16962E 02	-0.	0.	5.50
-0.18059E 02	0.89105E 01	-0.37039E 02	0.23569E 02	-0.	0.	5.60
-0.18167E 02	0.12317E 02	-0.37163E 02	0.33000E 02	-0.	0.	5.70
-0.17110E 02	0.13721E 02	-0.33713E 02	0.38920E 02	-0.	0.	5.80
-0.20813E 01	0.49234E 01	0.13415E 02	0.93671E 01	-0.	0.	5.90
-0.14308E 01	0.36368E 01	0.13768E 02	0.31784E 01	-0.	0.	6.00
-0.27608E 01	0.38199E 01	0.11144E 02	0.13424E-00	-0.	0.	6.10
-0.32960E 01	0.43900E 01	0.73713E 01	-0.66774E 00	-0.	0.	6.20
-0.28733E 01	0.51455E 01	0.48944E 01	-0.17366E 01	-0.	0.	6.30
-0.11105E 01	0.48479E 01	0.42603E 01	-0.23299E 01	-0.	0.	6.40
0.81682E 00	0.37366E 01	0.33497E 01	-0.28373E 01	-0.	0.	6.50
0.76789E 01	0.	0.22131E 01	0.	0.	0.	6.60

Table XV - - - Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 10 C.P.S
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMISPAN: 27 SEGMENT NUMBER 14

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				FREQUENCY
REAL	IMAGINARY	REAL	IMAGINARY			
0.629636-02	0.107096E 03	-0.732168 00	0.279596 03	0.	-0.	0.
0.721592E 02	0.913296E 02	0.180957E 03	0.297056 03	-0.	-0.	0.1000
0.132038E 03	0.264746E 02	0.335994E 03	0.716056 02	-0.	-0.	0.2000
0.146796E 03	-0.144086E 02	0.429959E 03	-0.356296 02	-0.	-0.	0.3000
0.140186E 03	-0.491996E 02	0.415925E 03	-0.128796 03	-0.	-0.	0.4000
0.119227E 03	-0.873136E 02	0.363465E 03	-0.179216 03	-0.	-0.	0.5000
0.129098E 03	-0.811216E 02	0.324088E 03	-0.218646 03	-0.	-0.	0.6000
0.114146E 03	-0.951116E 02	0.299934E 03	-0.250916 03	-0.	-0.	0.7000
0.108607E 03	-0.112356E 03	0.282036E 03	-0.306106 03	-0.	-0.	0.8000
0.104516E 03	-0.170536E 03	0.271316E 03	-0.446356 03	-0.	-0.	0.9000
0.101096E 03	-0.268076E 03	0.251926E 03	-0.726496 03	-0.	-0.	1.0000
0.854056E 02	-0.546896E 03	0.190226E 03	-0.930696 03	0.	-0.	1.1000
0.526996E 02	-0.439776E 03	0.874276E 02	-0.113976 04	0.	-0.	1.2000
-0.222296E 02	-0.489546E 03	-0.128906E 03	-0.127506 04	0.	-0.	1.3000
-0.996356E 02	-0.524116E 03	-0.331606E 03	-0.134216 04	0.	-0.	1.4000
-0.287126E 03	-0.413906E 03	-0.630956E 03	-0.990076 03	0.	-0.	1.5000
-0.507736E 03	-0.745676E 02	-0.139146E 04	-0.920166 02	-0.	-0.	1.6000
-0.583046E 03	0.117496E 03	-0.191206E 04	0.370936 03	-0.	-0.	1.7000
-0.428346E 03	0.147506E 03	-0.106506E 04	0.370096 03	-0.	-0.	1.8000
-0.144046E 03	0.122616E 03	-0.530886E 03	0.279326 03	-0.	-0.	1.9000
-0.880426E 02	0.105296E 03	-0.182866E 03	0.210356 03	-0.	-0.	2.0000
-0.599796E 02	0.955276E 02	-0.109046E 03	0.159036 03	-0.	-0.	2.1000
-0.359816E 02	0.922206E 02	-0.701246E 02	0.116116 03	-0.	-0.	2.2000
-0.195276E 02	0.886066E 02	-0.491396E 02	0.791136 02	-0.	-0.	2.3000
0.498246E 01	0.882906E 02	-0.472056E 02	0.635266 02	0.	-0.	2.4000
0.820116E 01	0.810726E 02	-0.477456E 02	0.419196 02	0.	-0.	2.5000
0.150726E 02	0.820536E 02	-0.594676E 02	0.328916 02	0.	-0.	2.6000
0.178786E 02	0.[illegible] 02	-0.777216E 02	0.324486 02	0.	-0.	2.7000
0.197916E 02	0.803796E 02	-0.886946E 02	0.512996 02	0.	-0.	2.8000
0.224606E 02	0.840926E 02	-0.117166E 03	0.910376 02	0.	-0.	2.9000
0.222146E 02	0.972276E 02	-0.114766E 03	0.104146 03	0.	-0.	3.0000
0.301426E 02	0.109946E 03	-0.764466E 02	0.881026 02	0.	-0.	3.1000
0.483256E 02	0.125146E 03	-0.574346E 02	0.599766 02	0.	-0.	3.2000
0.102826E 03	0.119066E 03	-0.624756E 02	0.514296 02	0.	-0.	3.3000
0.173926E 03	-0.168606E 03	-0.873436E 02	0.134356 03	0.	-0.	3.4000
0.302566E 03	-0.172366E 03	-0.132636E 03	0.130626 03	0.	-0.	3.5000
-0.321336E 02	-0.134276E 03	0.146396E 02	0.103376 03	-0.	-0.	3.6000
-0.678336E 02	-0.119036E 03	0.244266E 02	0.577746 02	-0.	-0.	3.7000
-0.847006E 02	-0.120696E 03	0.279436E 02	0.819546 02	-0.	-0.	3.8000
-0.103966E 03	-0.124186E 03	0.304216E 02	0.794096 02	-0.	-0.	3.9000
-0.120966E 03	-0.128166E 03	0.328706E 02	0.734016 02	-0.	-0.	4.0000
-0.174396E 01	-0.869476E 02	0.409096E 02	0.566646 02	-0.	-0.	4.1000
-0.740916E 03	0.161936E 03	0.488536E 02	0.488886 02	-0.	0.	4.2000
-0.239436E 03	0.244106E 03	0.994966E 01	0.535526 02	-0.	-0.	4.3000
-0.203906E 03	0.294756E 03	0.433056E 01	0.702786 02	-0.	-0.	4.4000
-0.906716E 02	0.191836E 03	0.131966E 02	0.591056 02	-0.	-0.	4.5000
0.834326E 02	0.454706E 02	0.432946E 02	0.382216 02	0.	-0.	4.6000
0.408346E 02	0.194926E 02	0.432146E 02	0.293706 02	0.	-0.	4.7000
0.382866E 02	0.924096E 01	0.401256E 02	0.230036 02	0.	-0.	4.8000
0.248636E 02	0.312206E 01	0.386056E 02	0.169276 02	0.	-0.	4.9000
0.199416E 02	0.732596E 01	0.429486E 02	0.108616 02	-0.	-0.	5.0000
0.252516E 02	-0.158776E 01	0.546096E 02	0.260676 01	-0.	-0.	5.1000
0.321306E 02	-0.334876E 02	0.662946E 02	-0.485676 02	-0.	-0.	5.2000
0.444126E 02	-0.500926E 02	0.863226E 02	-0.748606 02	-0.	-0.	5.3000
0.984746E 02	-0.314396E 02	0.764976E 02	-0.779076 02	-0.	-0.	5.4000
-0.715306E 02	-0.217536E 02	-0.161626E 02	-0.326046 02	0.	-0.	5.5000
-0.288796E 02	-0.830466E 01	-0.274696E 02	-0.336816 02	0.	-0.	5.6000
-0.248046E 02	-0.278176E 01	-0.208466E 02	-0.700506 01	-0.	-0.	5.7000
-0.735126E 02	0.326906E 00	-0.187236E 02	-0.332936 01	-0.	-0.	5.8000
-0.297956E 02	0.107956E 02	-0.217426E 02	0.955236 01	-0.	-0.	5.9000
-0.333186E 02	0.193066E 02	-0.319466E 02	0.133936 02	-0.	-0.	6.0000
-0.345786E 02	0.213766E 02	-0.334126E 02	0.232046 02	-0.	-0.	6.1000
-0.346806E 02	0.206996E 02	-0.337246E 02	0.324876 02	-0.	-0.	6.2000
-0.373466E 02	0.315816E 02	-0.309566E 02	0.395136 02	-0.	-0.	6.3000
0.429386E-00	0.118716E 02	0.121746E 02	0.850056 01	-0.	-0.	6.4000
0.311066E 01	0.797366E 01	0.142916E 02	0.287976 01	-0.	-0.	6.5000
0.821006E 00	0.430266E 01	0.101156E 02	0.121026-00	-0.	-0.	6.6000
-0.785916E-00	0.599336E 01	0.668996E 01	-0.707456 00	-0.	-0.	6.7000
-0.608166E-01	0.546996E 01	0.334916E 01	-0.137596 01	-0.	-0.	6.8000
0.156826E 01	0.599996E 01	0.386616E 01	-0.211436 01	-0.	-0.	6.9000
0.299026E 01	0.730676E 01	0.322136E 01	-0.259296 01	-0.	-0.	7.0000
0.560006E 01	0.	0.280846E 01	0.	0.	0.	7.1000

Table XV --- Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT:	297,000 LB	CUTOFF FREQUENCY:	10 CPS
ALTITUDE:	24,000 FT		
MACH NUMBER:	0.85		

PERCENT SEMISPAN: 40.06 SEGMENT NUMBER 8

INCREMENTAL SHEAR STRESS REAL	INCREMENTAL SHEAR STRESS IMAGINARY	INCREMENTAL AXIAL STRESS REAL	INCREMENTAL AXIAL STRESS IMAGINARY			FREQUENCY CPS
-0.13427E-00	0.73716E 02	-0.12409E 01	0.27097E 03	0.	0.	[illegible]
0.49237E 02	0.63100E 02	0.18950E 03	0.24197E 03	0.	0.	0.30
0.90530E 02	0.18692E 02	0.33099E 03	0.75329E 02	0.	0.	0.35
0.11400E 03	-0.99961E 01	0.43606E 03	-0.36907E 02	0.	-0.	0.44
0.11057E 03	-0.73006E 02	0.42277E 03	-0.13336E 03	0.	-0.	0.50
0.96627E 02	-0.46699E 02	0.37131E 03	-0.18676E 03	0.	-0.	0.60
0.86442E 02	-0.56777E 02	0.33236E 03	-0.22910E 03	0.	-0.	0.70
0.80023E 02	-0.67210E 02	0.30607E 03	-0.27272E 03	0.	-0.	0.80
0.76207E 02	-0.80304E 02	0.28059E 03	-0.32993E 03	0.	-0.	0.90
0.74177E 02	-0.12327E 03	0.27612E 03	-0.49920E 03	0.	-0.	1.00
0.72555E 02	-0.20155E 03	0.25167E 03	-0.77403E 03	0.	-0.	1.10
0.60560E 02	-0.26390E 03	0.17001E 03	-0.90754E 03	0.	-0.	1.20
0.34717E 02	-0.33621E 03	0.62019E 02	-0.12291E [illegible]	0.	-0.	1.30
-0.24606E 02	-0.57509E 03	-0.17309E 03	-0.15415E 04	-0.	-0.	1.40
-0.82606E 02	-0.40102E 03	-0.39572E 03	-0.14033E 04	-0.	-0.	1.45
-0.17080E 03	-0.31401E 03	-0.71632E 03	-0.10109E 04	-0.	-0.	1.47
-0.40766E 03	0.44464E 02	-0.15137E 04	-0.45779E 02	-0.	-0.	1.50
-0.46533E 03	0.10699E 03	-0.16147E 04	0.63392E 03	-0.	0.	1.55
-0.34223E 03	0.13051E 03	-0.11241E 04	0.40837E 03	-0.	0.	1.60
-0.11973E 03	0.11104E 03	-0.34000E 03	0.30440E 03	-0.	0.	1.65
-0.71077E 02	0.97544E 02	-0.10770E 03	0.22646E 03	-0.	0.	1.80
-0.46094E 02	0.89600E 02	-0.11207E 03	0.16700E 03	-0.	0.	1.90
-0.30070E 02	0.85379E 02	-0.74624E 02	0.11691E 03	-0.	0.	2.00
-0.18239E 02	0.83926E 02	-0.30672E 02	0.82019E 02	-0.	0.	2.10
-0.11048E 02	0.93029E 02	-0.83442E 02	0.86907E 02	0.	0.	2.20
-0.40112E 01	0.96363E 02	-0.76420E 02	0.67019E 02	0.	0.	2.30
0.79364E 01	0.97221E 02	-0.77310E 02	0.50253E 02	0.	0.	2.35
0.16316E 02	0.96724E 02	-0.90500E 02	0.37577E 02	0.	0.	2.40
0.20197E 02	0.91623E 02	-0.90331E 02	0.71140E 02	0.	0.	2.45
0.29205E 02	0.84823E 02	-0.11753E 03	0.96304E 02	0.	0.	2.47
0.30806E 02	0.87224E 02	-0.11170E 03	0.94903E 02	0.	0.	2.49
0.29496E 02	0.95293E 02	-0.84900E 02	0.74959E 02	0.	0.	2.50
0.56266E 02	0.10757E 03	-0.79607E 02	0.46006E 02	0.	0.	2.55
0.65332E 02	0.10666E 03	-0.10917E 03	0.65512E 02	0.	0.	2.58
0.10612E 03	-0.13261E 02	-0.15902E 03	0.21357E 03	0.	-0.	2.60
0.17038E 03	-0.26027E 02	-0.29263E 03	0.21306E 03	0.	-0.	2.70
0.75319E 01	0.11344E 02	0.22971E 02	0.10691E 03	0.	-0.	2.80
0.51209E 01	0.47021E 02	0.37666E 02	0.10179E 03	-0.	0.	3.00
0.21522E 02	0.73905E 02	0.51011E 02	0.19245E 03	0.	0.	3.10
0.46046E 02	0.89867E 02	0.71164E 02	0.20092E 03	0.	0.	3.20
0.70777E 02	0.10414E 03	0.93273E 02	0.19993E 03	0.	0.	3.30
0.13033E 03	0.52819E 02	0.16767E 03	0.10961E 03	0.	0.	3.35
0.25790E 03	-0.19260E 03	0.29555E 03	-0.20114E 02	0.	-0.	3.40
0.14869E 03	-0.21570E 03	0.30076E 02	0.35956E 02	0.	-0.	3.50
0.10091E 03	-0.22697E 03	0.12440E 02	0.07636E 02	0.	-0.	3.55
0.50661E 02	-0.14463E 03	0.63510E 02	0.43257E 02	0.	-0.	3.60
-0.50454E 02	-0.75612E 02	0.11690E 03	-0.25020E 01	-0.	-0.	3.70
-0.57976E 02	-0.49976E 02	0.07771E 02	-0.11397E 02	-0.	-0.	3.80
-0.50930E 02	-0.93457E 02	0.66796E 02	-0.16934E 02	-0.	-0.	4.00
-0.46010E 02	-0.19634E 02	0.46906E 02	[illegible] 02	-0.	-0.	4.20
-0.43021E 02	-0.12293E 02	0.20227E 02	-0.21220E 02	-0.	-0.	4.40
-0.46140E 02	-0.71000E 01	0.14621E 02	-0.10972E 02	-0.	-0.	4.50
-0.49300E 02	0.19093E 00	0.36324E 01	0.25395E 01	-0.	0.	4.60
-0.54696E 02	0.23635E 02	-0.10607E 02	0.14795E 02	-0.	0.	4.90
-0.50699E 02	0.25904E 02	-0.02012E 01	0.10301E 02	-0.	0.	5.00
-0.17279E 02	0.12101E 02	0.30322E 02	-0.30969E 01	-0.	0.	5.25
-0.12700E 02	0.77920E 01	0.53235E 02	-0.12940E 02	-0.	0.	5.50
-0.14123E 02	0.75495E 01	0.23541E 02	-0.16341E 02	-0.	0.	[illegible]
-0.14080E 02	0.70174E 01	0.10407E 02	-0.17001E 02	-0.	0.	[illegible]
-0.13001E 02	0.63373E 01	0.14196E 02	-0.15503E 02	-0.	0.	[illegible]
-0.10566E 02	0.56913E 01	0.97900E 01	-0.14067E 02	-0.	0.	[illegible]
-0.10104E 02	0.43190E 01	0.92537E 01	-0.13975E 02	-0.	-0.	[illegible]
-0.10007E 02	0.31225E 01	0.09962E 01	-0.13037E 02	-0.	-0.	[illegible]
-0.10561E 02	0.30419E 01	0.91907E 01	-0.14407E 02	-0.	-0.	[illegible]
-0.17259E 02	0.97290E 01	0.11003E 02	-0.16902E 02	-0.	0.	[illegible]
-0.15966E 02	0.11766E 02	0.79826E 01	-0.15306E 02	-0.	-0.	[illegible]
-0.13637E 02	0.13694E 02	0.60050E 01	-0.13903E 02	-0.	0.	[illegible]
-0.96617E 01	0.14439E 02	-0.60274E 00	-0.11334E 02	-0.	0.	[illegible]
-0.61107E 01	0.14214E 02	-0.92339E 01	-0.07263E 01	-0.	0.	[illegible]
-0.73921E-01	0.12040E 02	-0.64070E 01	-0.16090E 01	-0.	0.	[illegible]
0.52006E 01	0.73400E 01	-0.60579E 01	0.19677E 01	0.	0.	[illegible]
0.91311E 01	0.	-0.62696E 01	0.	0.	0.	[illegible]

Table XV - - - Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMI SPAN: 40.06 SEGMENT NUMBER 107

INCREMENTAL SHEAR STRESS				INCREMENTAL AXIAL STRESS		
REAL	IMAGINARY			REAL	IMAGINARY	FREQUENCY CPS
-0.944936E-01	0.717872 02	0.	0.	0.106718E 01	-0.230366E 03	0.10
0.448044E 02	0.613236E 02	0.	0.	-0.154291E 03	-0.206746E 03	0.30
0.880236E 02	0.181418E 02	0.	0.	-0.209566E 03	-0.626955E 02	0.36
0.111337E 03	-0.920801E 01	0.	-0.	-0.372599E 05	0.312708E 02	0.44
0.107164E 03	-0.324636E 02	0.	-0.	-0.361239E 03	0.113095E 03	0.50
0.935401E 02	-0.447208E 02	0.	-0.	-0.517265E 03	0.159506E 03	0.66
0.895469E 02	-0.542386E 02	0.	-0.	-0.283681E 05	0.195082E 03	0.70
0.773708E 02	-0.644027E 02	0.	-0.	-0.261515E 03	0.233082E 03	0.80
0.734523E 02	-0.762925E 02	0.	-0.	-0.246586E 05	0.270849E 03	0.90
0.714095E 02	-0.110951E 03	0.	-0.	-0.235993E 03	0.476594E 03	1.00
0.704555E 02	-0.140308E 03	0.	-0.	-0.215804E 03	0.662046E 03	1.20
0.599066E 02	-0.246864E 03	0.	-0.	-0.192108E 03	0.843179E 03	1.34
0.362146E 02	-0.318078E 03	0.	-0.	-0.529971E 02	0.106467E 04	1.40
-0.188877E 02	-0.355331E 03	-0.	-0.	0.150299E 03	0.116442E 04	1.45
-0.737477E 02	-0.381425E 03	-0.	-0.	0.338116E 03	0.119992E 04	1.47
-0.155008E 03	-0.387000E 03	-0.	-0.	0.612033E 03	0.863337E 03	1.50
-0.379064E 03	-0.447042E 02	-0.	-0.	0.129951E 04	0.374022E 02	1.55
-0.437397E 03	0.960881E 02	-0.	0.	0.137997E 04	-0.378766E 03	1.60
-0.922866E 05	0.120738E 03	-0.	0.	0.960479E 03	-0.348902E 03	1.65
-0.211440E 05	0.102944E 03	-0.	0.	0.291266E 05	-0.260155E 03	1.80
-0.600888E 02	0.905279E 02	-0.	0.	0.160308E 03	-0.193666E 03	1.90
-0.435208E 02	0.832044E 02	-0.	0.	0.964435E 02	-0.143397E 03	2.00
-0.261866E 02	0.792480E 02	-0.	0.	0.637661E 02	-0.993838E 02	2.10
-0.167177E 02	0.782226E 02	-0.	0.	0.580131E 02	-0.700808E 02	2.20
-0.101935E 02	0.853236E 02	-0.	0.	0.712946E 02	-0.763748E 02	2.30
-0.313190E 01	0.881296E 02	-0.	0.	0.653026E 02	-0.572636E 02	2.35
0.750408E 01	0.884616E 02	0.	0.	0.662277E 02	-0.497746E 02	2.40
0.145718E 02	0.879908E 02	0.	0.	0.773268E 02	-0.491968E 02	2.43
0.176988E 02	0.861726E 02	0.	0.	0.840179E 02	-0.607916E 02	2.44
0.245268E 02	0.802948E 02	0.	0.	0.100446E 03	-0.822858E 02	2.47
0.257368E 02	0.844128E 02	0.	0.	0.954639E 02	-0.811568E 02	2.50
0.266708E 02	0.920778E 02	0.	0.	0.722178E 02	-0.637068E 02	2.54
0.349188E 02	0.102958E 03	0.	0.	0.680188E 02	-0.393778E 02	2.58
0.450468E 02	0.101038E 03	0.	0.	0.932768E 02	-0.388878E 02	2.65
0.104698E 03	-0.177638E 02	-0.	-0.	0.133878E 03	-0.182688E 03	2.70
0.173958E 03	-0.294938E 02	-0.	-0.	0.198618E 03	-0.183768E 03	2.80
0.473758E 01	0.662288E 01	0.	-0.	-0.192858E 02	-0.157658E 03	3.00
0.471668E 01	0.400208E 02	-0.	0.	-0.321668E 02	-0.155298E 03	3.10
0.149048E 02	0.635538E 02	0.	0.	-0.435358E 02	-0.164428E 03	3.20
0.424238E 02	0.777758E 02	0.	0.	-0.600858E 02	-0.171878E 03	3.26
0.646908E 02	0.910108E 02	0.	0.	-0.796958E 02	-0.170838E 03	3.29
0.135968E 03	0.288958E 02	0.	0.	-0.143268E 03	-0.904068E 02	3.35
0.233568E 03	-0.181908E 03	0.	-0.	-0.218338E 03	0.240218E 02	3.40
0.145258E 03	-0.210458E 03	0.	-0.	-0.532168E 02	-0.307228E 02	3.52
0.100078E 03	-0.725728E 03	0.	-0.	-0.106298E 02	-0.748798E 02	3.56
0.356258E 02	-0.140128E 03	0.	-0.	-0.571038E 02	-0.369438E 02	3.60
-0.653368E 02	-0.692188E 02	-0.	-0.	-0.999468E 02	0.220618E 01	3.70
-0.613378E 02	-0.439948E 02	-0.	-0.	-0.749958E 02	0.109528E 02	3.85
-0.521108E 02	-0.280848E 02	-0.	-0.	-0.533828E 02	0.164698E 02	4.00
-0.453958E 02	-0.149778E 02	-0.	-0.	-0.401408E 02	0.176778E 02	4.20
-0.406528E 02	-0.846638E 01	-0.	-0.	-0.241108E 02	0.181318E 02	4.39
-0.400598E 02	-0.479368E 01	-0.	-0.	-0.124938E 02	0.162118E 02	4.70
-0.408558E 02	0.738028E 01	-0.	0.	-0.465918E 01	-0.218998E 01	4.80
-0.419788E 02	0.125128E 02	-0.	0.	0.913148E 01	-0.176078E 02	4.96
-0.395238E 02	0.141258E 02	-0.	0.	0.707578E 01	-0.157068E 02	5.00
-0.270518E 02	0.823218E 01	-0.	0.	-0.760798E 02	0.264818E 01	5.15
-0.192568E 02	0.738078E 01	-0.	0.	-0.284148E 02	0.110578E 02	5.30
-0.148518E 02	0.519408E 01	-0.	0.	-0.218238E 02	0.139628E 02	5.44
-0.179518E 02	0.695758E 01	-0.	0.	-0.159898E 02	0.145768E 02	5.70
-0.168278E 02	0.916228E 01	-0.	0.	-0.121308E 02	0.133138E 02	5.85
-0.152688E 02	0.899388E 01	-0.	0.	-0.836498E 01	0.127038E 02	6.00
-0.150698E 02	0.883558E 01	-0.	-0.	-0.790678E 01	0.119608E 02	6.03
-0.149608E 02	0.863728E 01	-0.	-0.	-0.768668E 01	0.111408E 02	6.06
-0.150488E 02	0.960788E 01	-0.	-0.	-0.785288E 01	0.123108E 02	6.08
-0.164868E 02	0.122378E 02	-0.	0.	-0.101598E 02	0.144938E 02	6.20
-0.145738E 02	0.134658E 02	-0.	0.	-0.647868E 01	0.140098E 02	6.40
-0.124788E 02	0.147638E 02	-0.	0.	-0.342278E 01	0.115808E 02	6.60
-0.855338E 01	0.131108E 02	-0.	0.	0.514748E 00	0.958608E 01	7.00
-0.548058E 01	0.143308E 02	-0.	0.	0.276328E 01	0.576898E 01	7.40
0.977098E 00	0.116848E 02	-0.	0.	0.547638E 01	0.137488E 01	8.20
0.600948E 01	0.688968E 01	0.	0.	0.584258E 01	-0.168128E 01	9.00
0.953288E 01	0.	0.	0.	0.359688E 01	0.	10.00

Table XV – – – Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

BODY BALANCE STATION: 540 SEGMENT NUMBER 17

INCREMENTAL SHEAR STRESS						
REAL	IMAGINARY					FREQUENCY CPS
-0.41556E-01	-0.11891E 01	0.	-0.	0.	-0.	0.10
-0.12179E 01	-0.77898E 00	0.	-0.	0.	-0.	0.30
-0.18556E 01	0.91125E-01	0.	-0.	0.	-0.	0.36
-0.19906E 01	0.50408E 00	-0.	-0.	-0.	-0.	0.44
-0.17376E 01	0.74625E 00	-0.	-0.	-0.	-0.	0.50
-0.13591E 01	0.80593E 00	-0.	-0.	-0.	-0.	0.60
-0.11179E 01	0.87421E 00	-0.	-0.	-0.	-0.	0.70
-0.94CC7E 00	0.84129E 00	-0.	-0.	-0.	-0.	0.80
-0.90381E 00	0.87507E 00	-0.	-0.	-0.	-0.	0.90
-0.87C77E 00	0.10753E 01	-0.	-0.	-0.	-0.	1.00
-0.90624E 00	0.15150E 01	-0.	-0.	-0.	-0.	1.20
-0.56410E 00	0.19134E 01	0.	-0.	0.	-0.	1.34
-0.92164E 00	0.24331E 01	0.	-0.	0.	-0.	1.40
-0.66876E 00	0.27529E 01	-0.	-0.	-0.	-0.	1.47
-0.42273E-00	0.30482E 01	-0.	-0.	-0.	-0.	1.47
0.49574E-01	0.29039E 01	-0.	-0.	-0.	-0.	1.50
0.15715E 01	0.13965E 01	-0.	-0.	-0.	-0.	1.55
0.23137E 01	0.31194E-00	-0.	-0.	-0.	-0.	1.60
0.19053E 01	-0.14333E-00	-0.	0.	-0.	0.	1.65
0.45002E-00	-0.65090E-01	-0.	0.	-0.	0.	1.80
0.75392E-01	0.30583E-01	-0.	0.	-0.	0.	1.90
-0.17078E-00	0.12103E-00	-0.	0.	-0.	0.	2.00
-0.34177E-00	0.25075E-00	-0.	-0.	-0.	-0.	2.10
-0.53919E 00	0.45146E-00	0.	-0.	0.	-0.	2.20
-0.70218E 00	0.56544E 00	0.	-0.	0.	-0.	2.30
-0.71011E 00	0.70344E 00	0.	-0.	0.	-0.	2.35
-0.73506E 00	0.79091E 00	0.	-0.	0.	-0.	2.40
-0.66940E 00	0.81300E 00	0.	-0.	0.	-0.	2.45
-0.61489E 00	0.73339E 00	0.	-0.	0.	-0.	2.44
-0.42446E-00	0.42470E-00	0.	-0.	0.	-0.	2.47
-0.41417E-00	0.20201E-00	0.	-0.	0.	-0.	2.50
-0.78208E 00	0.23893E-00	0.	-0.	0.	-0.	2.54
-0.11547E 01	0.45288E-00	0.	-0.	0.	-0.	2.58
-0.17489E 01	0.77002E 00	0.	-0.	0.	-0.	2.65
-0.23210E 01	0.28963E 01	0.	-0.	0.	-0.	2.70
-0.31740E 01	0.46034E 01	0.	-0.	0.	-0.	2.80
-0.87678E 00	0.57247E 01	0.	-0.	0.	-0.	3.00
-0.43940E-00	0.79344E 01	0.	-0.	0.	-0.	3.10
0.77891E 00	0.10005E 02	-0.	-0.	-0.	-0.	3.20
0.27926E 01	0.11310E 02	-0.	-0.	-0.	-0.	3.26
0.49549E 01	0.12624E 02	-0.	-0.	-0.	-0.	3.29
0.12118E 02	0.39513E 01	-0.	-0.	-0.	-0.	3.35
0.20749E 02	-0.91543E 01	-0.	0.	-0.	0.	3.40
0.21439E 01	-0.42554E 01	-0.	0.	-0.	0.	3.52
-0.55491E 00	-0.10376E-00	0.	-0.	0.	-0.	3.56
0.95789E 00	-0.18467E 01	-0.	0.	-0.	0.	3.60
0.42653E 01	-0.34728E 01	-0.	0.	-0.	0.	3.70
0.31991E 01	-0.34853E 01	-0.	0.	-0.	0.	3.85
0.17666E 01	-0.25987E 01	-0.	0.	-0.	0.	4.00
0.77809E 00	-0.24161E 01	-0.	0.	-0.	0.	4.20
0.72858E-01	-0.21506E 01	-0.	0.	-0.	0.	4.30
-0.13809E-00	-0.20910E 01	-0.	0.	-0.	0.	4.70
-0.16757E-00	-0.23517E 01	-0.	0.	-0.	0.	4.80
-0.19906E-00	-0.25313E 01	-0.	0.	-0.	0.	4.96
-0.34072E-00	-0.23803E 01	-0.	0.	-0.	0.	5.00
-0.13132E 01	-0.18575E 01	0.	0.	0.	0.	5.15
-0.15916E 01	-0.15331E 01	0.	0.	0.	0.	5.30
-0.18658E 01	-0.12681E 01	0.	0.	0.	0.	5.40
-0.24655E 01	-0.87254E 00	0.	0.	0.	0.	5.70
-0.33136E 01	0.10737E 01	0.	-0.	0.	-0.	5.89
-0.51447E 01	0.19715E 01	0.	-0.	0.	-0.	6.00
-0.56273E 01	0.31694E 01	0.	-0.	0.	-0.	6.03
-0.54653E 01	0.45877E 01	0.	-0.	0.	-0.	6.06
-0.50013E 01	0.49601E 01	0.	-0.	0.	-0.	6.08
0.14277E 01	0.91852E 00	-0.	-0.	-0.	-0.	6.20
0.15643E 01	0.14374E-00	-0.	-0.	-0.	-0.	6.40
0.84113E 00	-0.12448E-00	-0.	-0.	-0.	-0.	6.60
0.29744E-00	-0.12172E-00	-0.	-0.	-0.	-0.	7.00
0.41850E-01	-0.54730E-01	-0.	-0.	-0.	-0.	7.60
-0.21216E-01	-0.37764E-01	-0.	-0.	-0.	-0.	8.20
0.12324E-03	-0.62769E-01	-0.	-0.	-0.	-0.	9.80
0.17713E-01	0.	-0.	0.	-0.	0.	10.00

Table XV – – – Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

BODY BALANCE STATION: 820 SEGMENT NUMBER 1

INCREMENTAL AXIAL STRESS

		REAL	IMAGINARY			FREQUENCY CPS
0.	0.	0.14020E 01	0.11502E 03	0.	0.	0.10
0.	0.	0.91791E 02	0.90364E 02	0.	0.	0.20
0.	0.	0.13304E 03	0.15400E 02	0.	0.	0.30
0.	-0.	0.10538E 03	-0.27779E 02	0.	-0.	0.40
0.	-0.	0.17321E 03	-0.61920E 02	0.	-0.	0.50
0.	-0.	0.146718 03	-0.77793E 02	0.	-0.	0.60
0.	-0.	0.12893E 03	-0.90059E 02	0.	-0.	0.70
0.	-0.	0.11819E 03	-0.102952 03	0.	-0.	0.80
0.	-0.	0.11194E 03	-0.11949E 03	0.	-0.	0.90
0.	-0.	0.10861E 03	-0.17704E 03	0.	-0.	1.00
0.	-0.	0.10547E 03	-0.27270E 03	0.	-0.	1.10
0.	-0.	0.88204E 02	-0.34835E 03	0.	-0.	1.20
0.	-0.	0.53972E 02	-0.43520E 03	0.	-0.	1.30
-0.	-0.	-0.21706E 02	-0.48013E 03	-0.	-0.	1.40
-0.	-0.	-0.94391E 02	-0.50846E 03	-0.	-0.	1.50
-0.	-0.	-0.20281E 03	-0.39070E 03	-0.	-0.	1.60
-0.	-0.	-0.48503E 03	-0.68810E 02	-0.	-0.	1.70
-0.	0.	-0.53849E 03	0.11326E 03	-0.	0.	1.80
-0.	0.	-0.37861E 03	0.11786E 03	-0.	0.	1.90
-0.	0.	-0.10442E 03	0.82115E 02	-0.	0.	2.00
-0.	0.	-0.46515E 02	0.52419E 02	-0.	0.	2.10
-0.	0.	-0.15921E 02	0.26898E 02	-0.	0.	2.20
0.	0.	0.16612E 01	0.86538E 00	0.	0.	2.30
0.	-0.	0.11113E 02	-0.23298E 02	0.	-0.	2.40
0.	-0.	0.41083E 01	-0.33168E 02	0.	-0.	2.50
0.	-0.	0.33616E 01	-0.51983E 02	0.	-0.	2.60
-0.	-0.	-0.34249E 01	-0.61034E 02	-0.	-0.	2.70
-0.	-0.	-0.21615E 02	-0.62007E 02	-0.	-0.	2.80
-0.	-0.	-0.31440E 02	-0.46208E 02	-0.	-0.	2.90
-0.	-0.	-0.58657E 02	-0.98328E 01	-0.	-0.	3.00
-0.	0.	-0.57843E 02	0.23182E 01	-0.	0.	3.10
-0.	-0.	-0.22121E 02	-0.13984E 02	-0.	-0.	3.20
-0.	-0.	-0.28605E 01	-0.47191E 02	-0.	-0.	3.30
-0.	-0.	-0.47438E 01	-0.63847E 02	-0.	-0.	3.40
-0.	-0.	-0.27224E 02	-0.47928E 01	-0.	-0.	3.50
-0.	-0.	-0.80642E 02	-0.46099E 02	-0.	-0.	3.60
0.	-0.	0.39611E 02	-0.12611E 03	0.	-0.	3.70
0.	-0.	0.60151E 02	-0.23312E 03	0.	-0.	3.80
0.	-0.	0.19306E 02	-0.32541E 03	0.	-0.	3.90
-0.	-0.	-0.56971E 02	-0.38009E 03	-0.	-0.	4.00
-0.	-0.	-0.14021E 03	-0.41035E 03	-0.	-0.	4.10
-0.	-0.	-0.41380E 03	-0.95400E 02	-0.	-0.	4.20
-0.	0.	-0.73783E 03	0.34171E 03	-0.	0.	4.30
0.	0.	0.18019E 02	0.11410E 03	0.	0.	4.40
0.	-0.	0.10482E 03	-0.63286E 02	0.	-0.	4.50
0.	0.	0.13287E 01	0.38239E 02	0.	0.	4.60
-0.	0.	-0.22218E 03	0.15803E 03	-0.	0.	4.70
-0.	0.	-0.12256E 03	0.13279E 03	-0.	0.	4.80
-0.	0.	-0.54074E 02	0.13011E 03	-0.	0.	4.90
-0.	0.	-0.10138E 02	0.10090E 03	-0.	0.	5.00
0.	0.	0.24813E 02	0.84378E 02	0.	0.	5.10
0.	0.	0.42422E 02	0.74936E 02	0.	0.	5.20
0.	0.	0.32274E 02	0.44714E 02	0.	0.	5.30
0.	0.	0.67968E 02	0.31256E 02	0.	0.	5.40
0.	0.	0.65695E 02	0.21498E 02	0.	0.	5.50
0.	0.	0.31126E 02	0.34112E 02	0.	0.	5.60
0.	0.	0.30621E 02	0.54783E 02	0.	0.	5.70
0.	0.	0.40272E 02	0.29496E 02	0.	0.	5.80
0.	0.	0.53314E 02	0.21124E 02	0.	0.	5.90
0.	-0.	0.68491E 02	-0.12977E 02	0.	-0.	6.00
0.	-0.	0.98498E 02	-0.27972E 02	0.	-0.	6.10
0.	-0.	0.10297E 03	-0.47796E 02	0.	-0.	6.20
0.	-0.	0.10341E 03	-0.71060E 02	0.	-0.	6.30
0.	-0.	0.95663E 02	-0.97724E 02	0.	-0.	6.40
-0.	-0.	-0.86315E 01	-0.14992E 02	-0.	-0.	6.50
-0.	-0.	-0.10725E 02	-0.31031E 01	-0.	-0.	6.60
0.	-0.	0.12145E-01	-0.47990E 01	0.	-0.	6.70
0.	-0.	0.63143E 01	-0.72225E 01	0.	-0.	7.00
0.	-0.	0.50231E 01	-0.96245E 01	0.	-0.	7.60
0.	-0.	0.43788E-00	-0.83328E 01	0.	-0.	8.20
-0.	-0.	-0.50716E 01	-0.43969E 01	-0.	-0.	9.00
-0.	0.	-0.89344E 01	0.	-0.	0.	10.00

Table XV - - - Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 15 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.55

PERCENT SEMISPAN: 27 SEGMENT NUMBER 10

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				FREQUENCY
REAL	IMAGINARY	REAL	IMAGINARY			CPS
0.84721E-01	0.55385E 02	-0.00681E 00	0.30363E 03	0.	-0.	
0.29567E 02	0.29947E 02	0.19898E 03	0.26210E 03	-0.	-0.	
0.44132E 02	0.83492E 01	0.37020E 03	0.78906E 02	-0.	-0.	
0.55139E 02	-0.51952E 01	0.47339E 03	-0.39261E 02	-0.	0.	
0.53096E 02	-0.16509E 02	0.49759E 03	-0.14192E 03	-0.	0.	
0.44196E 02	-0.22436E 02	0.40079E 03	-0.19748E 03	-0.	0.	
0.41255E 02	-0.27016E 02	0.35800E 03	-0.24096E 03	-0.	0.	
0.38231E 02	-0.31773E 02	0.32986E 03	-0.28950E 03	-0.	0.	
0.36471E 02	-0.37815E 02	0.31144E 03	-0.33952E 03	-0.	0.	
0.35926E 02	-0.42753E 02	0.29897E 03	-0.37720E 03	-0.	0.	
0.36453E 02	-0.47188E 02	0.27763E 03	-0.40276E 03	-0.	0.	
0.33495E 02	-0.12897E 03	0.20961E 03	-0.10256E 04	-0.	0.	
0.22844E 02	-0.16771E 03	0.96340E 02	-0.12780E 04	-0.	0.	
-0.42896E 01	-0.18946E 03	-0.14204E 03	-0.14050E 04	-0.	0.	
-0.32143E 02	-0.20629E 03	-0.36951E 03	-0.14780E 04	-0.	0.	
-0.57468E 02	-0.17111E 03	-0.69482E 03	-0.10976E 04	-0.	0.	
-0.19911E 03	-0.34902E 02	-0.15332E 04	-0.10[illegible]0E 03	-0.	0.	
-0.23925E 03	0.46462E 02	-0.16662E 04	0.40[illegible]0E 03	-0.	0.	
-0.18287E 03	0.70086E 02	-0.11743E 04	0.46[illegible]0E 03	-0.	0.	
-0.70840E 02	0.64637E 02	-0.36373E 03	0.30[illegible]0E 03	-0.	0.	
-0.43308E 02	0.62249E 02	-0.20130E 03	0.23180E 03	-0.	0.	
-0.30738E 02	0.63716E 02	-0.12059E 03	0.17913E 03	-0.	0.	
-0.20436E 02	0.69980E 02	-0.77275E 02	0.12795E 03	-0.	0.	
-0.96218E 01	0.74659E 02	-0.34149E 02	0.87179E 02	-0.	0.	
0.14082E 02	0.70093E 02	-0.32018E 02	0.70001E 02	-0.	0.	
0.17233E 02	0.77041E 02	-0.52813E 02	0.46193E 02	-0.	0.	
0.24472E 02	0.79877E 02	-0.65530E 02	0.38245E 02	-0.	0.	
0.34061E 02	0.79724E 02	-0.85646E 02	0.35754E 02	-0.	0.	
0.39009E 02	0.72921E 02	-0.97472E 02	0.56486E 02	-0.	0.	
0.50383E 02	0.63392E 02	-0.12910E 05	0.10052E 03	-0.	0.	
0.50381E 02	0.69316E 02	-0.12646E 03	0.11476E 03	-0.	0.	
0.43933E 02	0.84011E 02	-0.84240E 02	0.97089E 02	-0.	0.	
0.54431E 02	0.10597E 03	-0.63312E 02	0.66091E 02	-0.	0.	
0.10102E 03	0.10496E 03	-0.68845E 02	0.56672E 02	-0.	0.	
0.16764E 03	-0.10330E 03	-0.96249E 02	0.14305E 03	-0.	-0.	
0.29234E 03	-0.16149E 03	-0.14613E 03	0.14927E 03	-0.	-0.	
-0.28309E 02	-0.11812E 03	0.16332E 02	0.11591E 03	-0.	-0.	
-0.36137E 02	-0.93940E 02	0.26914E 02	0.96723E 02	-0.	-0.	
-0.71372E 02	-0.85784E 02	0.30791E 02	0.98310E 02	-0.	-0.	
-0.81034E 02	-0.83382E 02	0.33523E 02	0.87505E 02	-0.	-0.	
-0.88258E 02	-0.82513E 02	0.36221E 02	0.80885E 02	-0.	-0.	
-0.10972E 03	-0.71410E 02	0.45080E 02	0.62441E 02	-0.	-0.	
-0.15204E 03	0.89707E 02	0.53823E 02	0.45047E 02	-0.	0.	
-0.20169E 03	0.10767E 03	0.10525E 02	0.61216E 02	-0.	0.	
-0.16405E 03	0.21643E 03	0.47720E 01	0.77443E 02	-0.	0.	
-0.70035E 02	0.97869E 02	0.14582E 02	0.65131E 02	-0.	0.	
0.79812E 02	0.12316E 02	0.47708E 02	0.42118E 02	-0.	-0.	
0.47726E 02	-0.54085E 01	0.47620E 02	0.32365E 02	-0.	-0.	
0.24912E 02	-0.10415E 02	0.44216E 02	0.25349E 02	-0.	-0.	
0.14327E 02	-0.10380E 02	0.42629E 02	0.18653E 02	-0.	-0.	
0.18727E-00	-0.92066E 01	0.47527E 02	0.11968E 02	-0.	-0.	
-0.35289E 01	-0.84821E 01	0.60177E 02	0.28725E 01	-0.	-0.	
-0.44424E 01	-0.67778E 01	0.73053E 02	-0.95518E 02	-0.	0.	
-0.69816E 01	-0.61227E 01	0.95124E 02	-0.82493E 02	-0.	0.	
-0.72581E 01	-0.49439E 01	0.84297E 02	-0.85851E 02	-0.	0.	
-0.70801E 01	-0.46116E 01	-0.17812E 02	-0.36016E 02	-0.	0.	
-0.78139E 01	-0.37278E 01	-0.30270E 02	-0.15076E 02	-0.	-0.	
-0.91379E 01	-0.25388E 01	-0.22972E 02	-0.77192E 01	-0.	-0.	
-0.10833E 02	-0.11493E 01	-0.20631E 02	-0.36687E 01	-0.	-0.	
-0.13055E 02	0.38635E 01	-0.23939E 02	0.10526E 02	-0.	-0.	
-0.17386E 02	0.60393E 01	-0.35703E 02	0.16962E 02	-0.	0.	
-0.18059E 02	0.89109E 01	-0.37034E 02	0.25569E 02	-0.	0.	
-0.18167E 02	0.12910E 02	-0.37163E 02	0.35800E 02	-0.	0.	
-0.17110E 02	0.13721E 02	-0.33713E 02	0.36920E 02	-0.	0.	
-0.20813E 01	0.49234E 01	0.13413E 02	0.93671E 01	-0.	0.	
-0.14308E 01	0.36368E 01	0.15748E 02	0.91794E 01	-0.	0.	
-0.27408E 01	0.32199E 01	0.11146E 02	0.13424E-00	-0.	0.	
-0.32940E 01	0.43906E 01	0.73715E 01	-0.86774E 00	-0.	0.	
-0.28731E 01	0.51495E 01	0.38944E 01	-0.73668E 01	-0.	0.	
-0.11105E 01	0.48479E 01	0.42603E 01	-0.23299E 01	-0.	0.	
0.81682E 00	0.37366E 01	0.39497E 01	-0.28913E 01	-0.	0.	
0.26288E 01	0.19723E 01	0.22131E 01	-0.30441E 01	0.	0.	
0.36106E 01	0.23041E-00	0.12966E 01	-0.28343E 01	0.	0.	
0.37481E 01	-0.12214E 01	0.28049E-00	-0.24430E 01	-0.	-0.	
0.31242E 01	-0.21871E 01	-0.54565E 00	-0.18949E 01	-0.	-0.	
0.21401E 01	-0.25813E 01	-0.10438E 01	-0.12299E 01	-0.	-0.	
0.97849E 00	0.	-0.14243E 01	0.	0.	0.	

Table XV --- Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 15 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMI SPAN: 27 SEGMENT NUMBER 14

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				FREQUENCY
REAL	IMAGINARY	REAL	IMAGINARY			CPS
0.629639E-02	0.107099E 03	-0.732164E 00	0.279559E 03	0.	-0.	0.
0.723525E 02	0.913799E 02	0.180957E 03	0.237859E 03	-0.	-0.	0.5
0.132038E 03	0.244746E 02	0.339594E 03	0.716059E 02	-0.	-0.	1.
0.366709E 03	-0.144086E 02	0.429599E 03	-0.396249E 02	-0.	0.	1.5
0.160116E 03	-0.491099E 02	0.415259E 03	-0.128799E 03	-0.	0.	2.
0.139278E 03	-0.673139E 02	0.303659E 03	-0.179211E 03	-0.	0.	2.5
0.123988E 03	-0.811239E 02	0.924088E 03	-0.210066E 03	-0.	0.	3.
0.114169E 03	-0.991111E 02	0.299934E 03	-0.259091E 03	-0.	0.	3.5
0.108079E 03	-0.112395E 03	0.282639E 03	-0.300810E 03	-0.	0.	4.
0.104511E 03	-0.170953E 03	0.271911E 03	-0.449359E 03	-0.	0.	4.5
0.101099E 03	-0.268037E 03	0.251997E 03	-0.720499E 03	-0.	0.	5.
0.854059E 02	-0.348099E 03	0.190229E 03	-0.959699E 03	0.	0.	5.5
0.526999E 02	-0.439977E 03	0.874277E 02	-0.919979E 04	0.	-0.	6.
-0.272299E 02	-0.489954E 03	-0.128999E 03	-0.127599E 04	0.	-0.	6.5
-0.956359E 02	-0.524119E 03	-0.331699E 03	-0.134219E 04	0.	-0.	7.
-0.299129E 03	-0.415999E 03	-0.630559E 03	-0.999079E 03	0.	-0.	7.5
-0.507739E 03	-0.749679E 02	-0.139149E 04	-0.920149E 02	-0.	0.	8.
-0.5F3049E 03	0.117499E 03	-0.191209E 04	0.370539E 03	-0.	0.	8.5
-0.428349E 03	0.149589E 03	-0.106569E 04	0.370099E 03	-0.	0.	9.
-0.144049E 03	0.122619E 03	-0.539089E 03	0.279329E 03	-0.	0.	9.5
-0.980429E 02	0.105299E 03	-0.182869E 03	0.230399E 03	-0.	0.	10.
-0.599979E 02	0.955279E 02	-0.109949E 03	0.158099E 03	-0.	0.	10.5
-0.359419E 02	0.922289E 02	-0.701249E 02	0.116139E 03	-0.	0.	11.
-0.195279E 02	0.880669E 02	-0.491399E 02	0.791139E 02	-0.	0.	11.5
0.468249E 01	0.902909E 02	-0.472039E 02	0.639249E 02	0.	0.	12.
0.820119E 01	0.818129E 02	-0.477459E 02	0.419199E 02	0.	0.	12.5
0.130729E 02	0.829559E 02	-0.594679E 02	0.328919E 02	0.	0.	13.
0.178709E 02	0.816929E 02	-0.777219E 02	0.329469E 02	0.	0.	13.5
0.197919E 02	0.803799E 02	-0.884549E 02	0.312599E 02	0.	0.	14.
0.224609E 02	0.840929E 02	-0.117169E 03	0.910379E 02	0.	0.	14.5
0.222169E 02	0.972279E 02	-0.114769E 03	0.104149E 03	0.	0.	15.
0.301429E 02	0.109589E 03	-0.764469E 02	0.881029E 02	0.	0.	15.5
0.443259E 02	0.125369E 03	-0.574349E 02	0.599769E 02	0.	0.	16.
0.102829E 03	0.119609E 03	-0.624759E 02	0.514299E 02	0.	0.	16.5
0.177929E 03	-0.106609E 03	-0.873439E 02	0.134959E 03	0.	0.	17.
0.302569E 03	-0.172369E 03	-0.132639E 03	0.139029E 03	0.	0.	17.5
-0.321339E 02	-0.139279E 03	0.148399E 02	0.159379E 03	-0.	-0.	18.
-0.674339E 02	-0.119839E 03	0.244249E 02	0.877749E 02	-0.	-0.	18.5
-0.447009E 02	-0.120499E 03	0.279039E 02	0.819549E 02	-0.	-0.	19.
-0.103969E 03	-0.124189E 03	0.304219E 02	0.794099E 01	-0.	-0.	19.5
-0.120969E 03	-0.128369E 03	0.328709E 02	0.734019E 02	-0.	-0.	20.
-0.174599E 03	-0.869479E 02	0.409099E 02	0.366649E 02	-0.	-0.	20.5
-0.264319E 03	0.161939E 03	0.448839E 02	0.408809E 02	-0.	0.	21.
-0.259439E 03	0.244109E 03	0.954969E 01	0.333329E 02	-0.	0.	21.5
-0.201909E 03	0.294259E 03	0.433059E 01	0.702709E 02	-0.	0.	22.
-0.904719E 02	0.151839E 03	0.131969E 02	0.991059E 02	-0.	0.	22.5
0.854329E 02	0.454709E 02	0.432949E 02	0.382219E 02	0.	-0.	23.
0.608949E 02	0.194929E 02	0.432149E 02	0.293709E 02	0.	-0.	23.5
0.382809E 02	0.924099E 01	0.401299E 02	0.230039E 02	0.	-0.	24.
0.248639E 02	0.512209E 01	0.386859E 02	0.169279E 02	0.	-0.	24.5
0.194419E 02	0.252599E 01	0.429489E 02	0.108619E 02	-0.	-0.	25.
0.252919E 02	-0.198779E 01	0.546099E 02	0.260679E 01	-0.	-0.	25.5
0.321509E 02	-0.334879E 02	0.662949E 02	-0.485679E 02	-0.	0.	26.
0.546129E 02	-0.500929E 02	0.863229E 02	-0.748609E 02	-0.	0.	26.5
0.183769E 02	-0.516399E 02	0.764979E 02	-0.779079E 02	-0.	0.	27.
-0.212049E 02	-0.717519E 02	-0.161629E 02	-0.926849E 02	0.	0.	27.5
-0.248799E 02	-0.830469E 01	-0.274699E 02	-0.136819E 02	-0.	-0.	28.
-0.248049E 02	-0.278179E 01	-0.208469E 02	-0.700509E 01	-0.	-0.	28.5
-0.215529E 02	0.526909E 00	-0.187239E 02	-0.393299E 01	-0.	-0.	29.
-0.247929E 02	0.107959E 02	-0.217429E 02	0.955239E 01	-0.	-0.	29.5
-0.339189E 02	0.153069E 02	-0.319469E 02	0.159399E 02	-0.	0.	30.
-0.345789E 02	0.215269E 02	-0.536129E 02	0.232049E 02	-0.	0.	30.5
-0.346409E 02	0.286999E 02	-0.397249E 02	0.324879E 02	-0.	0.	31.
-0.329409E 02	0.359839E 02	-0.305969E 02	0.393199E 02	-0.	0.	31.5
0.429389E-00	0.118719E 02	0.121749E 02	0.850059E 01	-0.	0.	32.
0.511089E 01	0.797559E 01	0.142919E 02	0.287979E 01	-0.	0.	32.5
0.821009E 00	0.630269E 01	0.101739E 02	0.121829E-00	-0.	0.	33.
-0.244519E-00	0.499339E 01	0.467499E 01	-0.787459E 00	-0.	0.	33.5
-0.604169E-01	0.546499E 01	0.534919E 01	-0.139799E 01	-0.	0.	34.
0.156929E 01	0.394999E 01	0.388619E 01	-0.211439E 01	-0.	0.	34.5
0.299029E 01	0.730479E 01	0.122139E 01	-0.259299E 01	-0.	0.	35.
0.360009E 01	0.622329E 00	0.200049E 01	-6.276249E 01	0.	0.	35.5
0.399939E 01	-0.452679E-00	0.117659E 01	-0.257229E 01	0.	0.	36.
0.248089E 01	-0.961549E 00	0.236599E-00	-0.221709E 01	0.	-0.	36.5
0.222359E 01	-0.172049E 01	-0.499169E-00	-0.171969E 01	0.	-0.	37.
0.171729E 01	-0.129429E 01	-0.949029E 00	-0.111619E 01	0.	-0.	37.5
0.137969E 01	0.	-0.129259E 01	0.	0.	0.	38.

Table XV - - - Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 15 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMISPAN: 40.06 SEGMENT NUMBER 8

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				
REAL	IMAGINARY	REAL	IMAGINARY			FREQUENCY
-0.13427E-00	0.73780E 02	-0.12489E 01	0.27897E 03	0.	0.	
0.49232E 02	0.63188E 02	0.18058E 03	0.24197E 03	0.	0.	
0.90538E 02	0.14492E 02	0.33849E 03	0.72329E 02	0.	0.	
0.11480E 03	-0.9994 1E 01	0.43606E 03	-0.36597E 02	0.	-0.	
0.11057E 03	-0.33806E 02	0.42277E 03	-0.13336E 03	0.	-0.	
0.98627E 02	-0.46699E 02	0.37191E 03	-0.18676E 03	0.	-0.	
0.86442E 02	-0.56777E 02	0.33216E 03	-0.22918E 03	0.	-0.	
0.80023E 02	-0.67218E 02	0.30607E 03	-0.27272E 03	0.	-0.	
0.76207E 02	0.80304E 02	0.28059E 03	-0.32593E 03	0.	-0.	
0.74177E 02	-0.12527E 03	0.27612E 03	-0.49926E 03	0.	-0.	
0.72555E 02	-0.20155E 03	0.25167E 03	-0.77483E 03	0.	-0.	
0.60560E 02	-0.26338E 03	0.17801E 03	-0.98754E 03	0.	-0.	
0.34717E 02	-0.33621E 03	0.62019E 02	-0.12251E 04	0.	-0.	
-0.24606E 02	-0.37509E 03	-0.17589E 03	-0.13415E 04	-0.	-0.	
-0.82686E 02	-0.40182E 3	-0.39572E 03	-0.14035E 04	-0.	-0.	
-0.17040E 03	-0.31481E 03	-0.71632E 03	-0.10105E 04	-0.	-0.	
-0.48766E 03	-0.44464E 02	-0.15157E 04	-0.43774E 02	-0.	-0.	
-0.46553E 03	0.10699E 03	-0.16147E 04	0.43192E 03	-0.	0.	
-0.34223E 03	0.13051E 03	-0.11241E 04	0.40089E 03	-0.	0.	
-0.11975E 03	0.11104E 03	-0.34088E 03	0.33448E 03	-0.	0.	
-0.71077E 02	0.97544E 02	-0.18770E 03	0.27466E 03	-0.	0.	
-0.46094E 02	0.89608E 02	-0.11287E 03	0.19780E 03	-0.	0.	
-0.30070E 02	0.85379E 02	-0.74624E 02	0.11631E 03	-0.	0.	
-0.18259E 02	0.85926E 02	-0.58672E 02	0.82019E 02	-0.	0.	
-0.11848E 02	0.93029E 02	-0.83442E 02	0.86987E 02	-0.	0.	
-0.49112E 01	0.96563E 02	-0.76420E 02	0.67019E 02	-0.	0.	
0.79364E 01	0.97221E 02	-0.77510E 02	0.58233E 02	0.	0.	
0.16316E 02	0.98724E 02	-0.90500E 02	0.57577E 02	0.	0.	
0.20197E 02	0.91623E 02	-0.98951E 02	0.71140E 02	0.	0.	
0.29205E 02	0.84825E 02	-0.11755E 03	0.94304E 02	0.	0.	
0.30806E 02	0.87224E 02	-0.11170E 03	0.94983E 02	0.	0.	
0.29496E 02	0.95293E 02	-0.84988E 02	0.74559E 02	0.	0.	
0.26266E 02	0.10757E 03	-0.79607E 02	0.66086E 02	0.	0.	
0.65852E 02	0.10666E 03	-0.10917E 03	0.63512E 02	0.	0.	
0.10612E 03	-0.13261E 02	-0.15902E 03	0.21357E 03	0.	-0.	
0.17838E 03	-0.26827E 02	-0.23265E 03	0.21506E 03	0.	-0.	
0.75319E 01	0.11344E 02	0.22371E 02	0.18451E 03	0.	-0.	
0.51209E 01	0.47821E 02	0.37644E 02	0.18175E 03	-0.	-0.	
0.21322E 02	0.73985E 02	0.51011E 02	0.19243E 03	0.	-0.	
0.46 02	0.89867E 02	0.71164E 02	0.20092E 03	0.	-0.	
0.7 E 02	0.10414E 03	0.93279E 02	0.19993E 03	0.	0.	
0.15033E 03	0.32819E 02	0.16767E 03	0.10581E 03	0.	0.	
0.25794E 03	-0.19268E 03	0.25553E 03	-0.28114E 02	0.	-0.	
0.14869E 03	-0.21570E 03	0.38076E 02	0.35956E 02	0.	-0.	
0.10091E 03	-0.72697E 03	0.12440E 02	0.87636E 02	0.	-0.	
0.38861E 02	-0.14469E 03	0.43518E 02	0.43237E 02	0.	-0.	
-0.58454E 02	-0.75612E 02	0.11690E 03	-0.25820E 01	-0.	-0.	
-0.57976E 02	-0.49976E 02	0.87771E 02	-0.12397E 02	-0.	-0.	
-0.50998E 02	-0.33437E 02	0.64794E 02	-0.16934E 02	-0.	-0.	
-0.44018E 02	-0.19654E 02	0.46982E 02	-0.20689E 02	-0.	-0.	
-0.43821E 02	-0.12295E 02	0.28227E 02	-0.21220E 02	-0.	-0.	
-0.46140E 02	-0.71800E 01	0.14621E 02	-0.18972E 02	-0.	-0.	
-0.49380E 02	0.13853E 02	0.34529E 01	0.25395E 01	-0.	0.	
-0.54696E 02	0.23633E 02	-0.10607E 02	0.14755E 02	-0.	0.	
-0.50699E 02	0.25984E 02	-0.02812E 01	0.18381E 02	-0.	0.	
-0.17279E 02	0.12101E 02	0.30522E 01	-0.30969E 01	-0.	0.	
-0.12780E 02	0.77928E 01	0.93259E 02	-0.12940E 02	-0.	0.	
-0.14123E 02	0.75495E 01	0.25541E 02	-0.16341E 02	-0.	0.	
-0.14088E 02	0.78174E 01	0.18407E 02	-0.17001E 02	-0.	0.	
-0.13001E 02	0.65373E 01	0.14196E 02	-0.15583E 02	-0.	0.	
-0.10566E 02	0.56913E 01	0.57200E 01	-0.14867E 02	-0.	0.	
-0.10184E 02	0.45190E 01	0.92537E 01	-0.13975E 02	-0.	-0.	
-0.10087E 02	0.31225E 01	0.89962E 01	-0.13037E 02	-0.	-0.	
-0.10561E 02	0.38419E 01	0.91907E 01	-0.14407E 02	-0.	-0.	
-0.12239E 02	0.97290E 01	0.11885E 02	-0.16962E 02	-0.	-0.	
-0.15966E 02	0.11746E 02	0.75824E 01	-0.16396E 02	-0.	0.	
-0.13697E 02	0.13694E 02	0.40058E 01	-0.13903E 02	-0.	0.	
-0.96417E 01	0.14435E 02	-0.60244E 00	-0.11334E 02	-0.	0.	
-0.61107E 01	0.14714E 02	-0.32339E 01	-0.67283E 01	-0.	0.	
-0.73921E-01	0.12040E 02	-0.64070E 01	-0.16090E 01	-0.	0.	
0.52006E 01	0.73408F 01	-0.68379E 01	0.19677E 01	0.	0.	
0.91311E 01	0.20057E 01	-0.42096E 01	0.33020E 01	0.	0.	
0.10448E 02	-0.28879E 01	-0.11278E 01	0.22374E 01	0.	-0.	
0.94145E 01	-0.64974E 01	0.18304E 01	-0.20539E-00	0.	-0.	
0.65287E 01	-0.80264E 01	0.50311E 01	-0.28541E 01	0.	-0.	
0.25512E 01	-0.77335E 01	0.24030E 01	-0.45381E 01	0.	-0.	
-0.12972E 01	0.	0.11744E-00	0.	-0.	0.	

Table XV --- Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 15 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMISPAN 40.06 SEGMENT NUMBER 107

INCREMENTAL SHEAR STRESS				INCREMENTAL AXIAL STRESS		
REAL	IMAGINARY			REAL	IMAGINARY	FREQUENCY
-0.949038E-01	0.717076 02	0.	0.	0.106716 01	-0.238366 03	0.
0.490064 02	0.613236 02	0.	0.	-0.154299 03	-0.206746 03	0.
0.880236 02	0.181416 02	0.	0.	-0.289566 03	-0.626556 02	0.
0.121376 03	-0.929016 01	0.	-0.	-0.372596 03	0.912706 02	0.
0.107146 03	-0.324636 02	0.	-0.	-0.361236 03	0.113996 03	0.
0.949516 02	-0.447286 02	0.	-0.	-0.317266 03	0.139586 03	0.
0.835696 02	-0.542306 02	0.	-0.	-0.283216 03	0.159826 03	0.
0.[illegible] 02	-0.640276 02	0.	-0.	-0.261516 03	0.293026 03	0.
0.736236 02	-0.742976 02	0.	-0.	-0.246586 03	0.278496 03	0.
0.710936 02	-0.118516 03	0.	-0.	-0.235936 03	0.426586 03	0.
0.704596 02	-0.190386 03	0.	-0.	-0.213066 03	0.662066 03	0.
0.599066 02	-0.248886 03	0.	-0.	-0.152106 03	0.843796 03	0.
0.362146 02	-0.318076 03	0.	-0.	-0.529916 02	0.104676 04	0.
-0.188876 02	-0.355316 03	-0.	-0.	0.150796 03	0.114626 04	0.
-0.731776 02	-0.381426 03	-0.	-0.	0.338116 03	0.119926 04	0.
-0.155986 01	-0.382006 03	-0.	-0.	0.612056 03	0.863376 03	0.
-0.879966 03	-0.479426 02	-0.	-0.	0.129316 04	0.374026 02	0.
-0.437376 03	0.960816 02	-0.	0.	0.139796 04	-0.378766 03	0.
-0.322866 03	0.120736 03	-0.	0.	0.966476 03	-0.348926 03	0.
-0.111486 03	0.102946 03	-0.	0.	0.291266 03	-0.260156 03	0.
-0.680886 02	0.905296 02	-0.	0.	0.160386 03	-0.195666 03	0.
-0.435286 02	0.832046 02	-0.	0.	0.964336 02	-0.143376 03	0.
-0.281666 02	0.792466 02	-0.	0.	0.637616 02	-0.993836 02	0.
-0.167176 02	0.782226 02	-0.	0.	0.501316 02	-0.780806 02	0.
-0.101936 02	0.833236 02	-0.	0.	0.712966 02	-0.743246 02	0.
-0.513196 01	0.881296 02	0.	0.	0.653026 02	-0.572636 02	0.
0.754406 01	0.884116 02	0.	0.	0.662276 02	-0.497746 02	0.
0.143716 02	0.879906 02	0.	0.	0.773266 02	-0.491966 02	0.
0.176986 02	0.861726 02	0.	0.	0.840176 02	-0.607916 02	0.
0.245266 02	0.802946 02	0.	0.	0.100446 03	-0.822856 02	0.
0.257346 02	0.844126 02	0.	0.	0.994396 02	-0.811566 02	0.
0.266706 02	0.920776 02	0.	0.	0.726176 02	-0.657066 02	0.
0.349186 02	0.102956 03	0.	0.	0.680186 02	-0.393776 02	0.
0.650666 02	0.101036 03	0.	0.	0.932766 02	-0.388876 02	0.
0.104696 03	-0.177636 02	0.	-0.	0.135876 03	-0.182486 03	0.
0.173356 03	-0.294036 02	0.	-0.	0.198616 03	-0.183766 03	0.
0.673736 01	0.642286 01	0.	-0.	-0.392836 02	-0.137656 03	0.
0.471666 01	0.400206 02	-0.	0.	-0.321666 02	-0.153296 03	0.
0.196046 02	0.635336 02	0.	0.	-0.435856 02	-0.164426 03	0.
0.424236 02	0.777736 02	0.	0.	-0.608056 02	-0.171676 03	0.
0.646906 02	0.910106 02	0.	0.	-0.796956 02	-0.170836 03	0.
0.135966 03	0.788956 02	0.	0.	-0.143266 03	-0.904066 02	0.
0.233566 03	-0.181906 03	0.	-0.	-0.218336 03	0.246216 02	0.
0.145296 03	-0.210456 03	0.	-0.	-0.332166 02	-0.307226 02	0.
0.100076 03	-0.225726 03	0.	-0.	-0.106296 02	-0.748796 02	0.
0.356256 02	-0.140126 03	0.	-0.	-0.371036 02	-0.369436 02	0.
-0.693346 02	-0.692186 02	-0.	-0.	-0.999486 01	0.220616 01	0.
-0.613376 02	-0.439946 02	-0.	-0.	-0.749956 01	0.103926 02	0.
-0.521106 02	-0.280846 02	-0.	-0.	-0.933626 02	0.144696 02	0.
-0.493996 02	-0.149776 02	-0.	-0.	-0.401486 02	0.176776 02	0.
-0.446526 02	-0.848656 01	-0.	-0.	-0.241106 02	0.181316 02	0.
-0.400096 02	-0.473366 01	-0.	-0.	-0.126936 02	0.162116 02	0.
-0.[illegible] 02	0.738826 01	-0.	0.	-0.463916 01	-0.216996 01	0.
-0.419786 02	0.125126 02	-0.	0.	0.913106 01	-0.126076 02	0.
-0.[illegible] 02	0.141256 02	-0.	0.	0.707376 01	-0.157066 02	0.
-0.229516 02	0.823216 01	-0.	0.	-0.260796 02	0.264616 01	0.
-0.192566 02	0.730376 01	-0.	0.	-0.284146 02	0.110576 02	0.
-0.188516 02	0.819406 01	-0.	0.	-0.218236 02	0.139626 02	0.
-0.179916 02	0.895756 01	-0.	0.	-0.138986 02	0.145266 02	0.
-0.166276 02	0.916226 01	-0.	0.	-0.121306 02	0.133196 02	0.
-0.152886 02	0.899386 01	-0.	0.	-0.836496 01	0.127036 02	0.
-0.150696 02	0.873536 01	-0.	-0.	-0.790676 01	0.119406 02	0.
-0.149606 02	0.863726 01	-0.	-0.	-0.768666 01	0.111406 02	0.
-0.150496 02	0.960286 01	-0.	-0.	-0.783206 01	0.123106 02	0.
-0.146866 02	0.122376 02	-0.	0.	-0.101556 02	0.144936 02	0.
-0.145736 02	0.134456 02	-0.	0.	-0.647866 01	0.140066 02	0.
-0.127486 02	0.147636 02	-0.	0.	-0.342276 01	0.118806 02	0.
-0.855336 01	0.151106 02	-0.	0.	0.314746 00	0.968406 01	0.
-0.500576 01	0.143306 02	-0.	0.	0.276326 01	0.574896 01	0.
0.977956 00	0.116846 02	-0.	0.	0.367416 01	0.137486 01	0.
0.609646 01	0.669566 01	0.	0.	0.384256 01	-0.146126 01	0.
0.953286 01	0.136476 01	0.	0.	0.339686 01	-0.282136 01	0.
0.106646 02	-0.330346 01	0.	-0.	0.963306 00	-0.191176 01	0.
0.911006 01	-0.640796 01	0.	-0.	-0.156396 01	0.179376 00	0.
0.611526 01	-0.783806 01	0.	-0.	-0.258996 01	0.243866 01	0.
0.221786 01	-0.748866 01	0.	-0.	-0.203326 01	0.387756 01	0.
-0.140186 01	0.	-0.	0.	-0.100346 00	0.	0.

Table XV -- Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 15 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

BODY BALANCE STATION: 540 SEGMENT NUMBER 17

INCREMENTAL SHEAR STRESS						
REAL	IMAGINARY					
-0.41556E-01	-0.11891E 01	0.	-0.	0.	-0.	
-0.12179E 01	-0.77898E 00	0.	-0.	0.	-0.	
-0.18598E 01	0.91125E-01	0.	-0.	0.	-0.	
-0.19006E 01	0.50408E 00	-0.	-0.	-0.	-0.	
-0.17376E 01	0.74623E 00	-0.	-0.	-0.	-0.	
-0.13591E 01	0.80593E 00	-0.	-0.	-0.	-0.	
-0.11179E 01	0.82621E 00	-0.	-0.	-0.	-0.	
-0.98007E 00	0.84129E 00	-0.	-0.	-0.	-0.	
-0.90381E 00	0.87597E 00	-0.	-0.	-0.	-0.	
-0.87077E 00	0.10753E 01	-0.	-0.	-0.	-0.	
-0.90624E 00	0.15150E 01	-0.	-0.	-0.	-0.	
-0.96810E 00	0.19134E 01	0.	-0.	0.	-0.	
-0.92366E 00	0.24331E 01	0.	-0.	0.	-0.	
-0.69876E 00	0.27529E 01	-0.	-0.	-0.	-0.	
-0.42273E-00	0.30482E 01	-0.	-0.	-0.	-0.	
0.49574E-01	0.29039E 01	-0.	-0.	-0.	-0.	
0.15715E 01	0.13965E 01	-0.	-0.	-0.	-0.	
0.23197E 01	0.31196E-00	-0.	-0.	-0.	-0.	
0.18053E 01	-0.14333E-00	-0.	0.	-0.	0.	
0.45002E-00	-0.65090E-01	-0.	0.	-0.	0.	
0.75392E-01	0.30583E-01	-0.	0.	-0.	0.	
-0.17073E-02	0.13103E-00	-0.	0.	-0.	0.	
-0.36177E-00	0.25075E-00	-0.	-0.	-0.	-0.	
-0.53919E 00	0.49146E-00	0.	-0.	0.	-0.	
-0.70718E 00	0.56544E 00	0.	-0.	0.	-0.	
-0.73011E 00	0.70344E 00	0.	-0.	0.	-0.	
-0.73506E 00	0.79091E 00	0.	-0.	0.	-0.	
-0.66940E 00	0.81300E 00	0.	-0.	0.	-0.	
-0.61489E 00	0.73339E 00	0.	-0.	0.	-0.	
-0.52446E-00	0.42470E-00	0.	-0.	0.	-0.	
-0.41417E-00	0.20201E-00	0.	-0.	0.	-0.	
-0.76706E 00	0.23893E-00	0.	-0.	0.	-0.	
-0.11547E 01	0.45288E-00	0.	-0.	0.	-0.	
-0.17489E 01	0.77602E 00	0.	-0.	0.	-0.	
-0.23210E 01	0.28963E 01	0.	-0.	0.	-0.	
-0.31240E 01	0.46034E 01	0.	-0.	0.	-0.	
-0.87478E 00	0.57242E 01	0.	-0.	0.	-0.	
-0.43960E-00	0.79344E 01	0.	-0.	0.	-0.	
0.77891E 00	0.10065E 02	-0.	-0.	-0.	-0.	
0.27924E 01	0.11310E 02	-0.	-0.	-0.	-0.	
0.49549E 01	0.12024E 02	-0.	-0.	-0.	-0.	
0.12118E 02	0.39513E 01	-0.	-0.	-0.	-0.	
0.20749E 02	-0.91543E 01	-0.	0.	-0.	0.	
0.21839E 01	-0.42554E 01	-0.	0.	-0.	0.	
-0.59691E 00	-0.18374E-00	0.	-0.	0.	-0.	
0.95739E 00	-0.18467E 01	-0.	0.	-0.	0.	
0.52653E 01	-0.36728E 01	-0.	0.	-0.	0.	
0.31931E 01	-0.34853E 01	-0.	0.	-0.	0.	
0.17466E 01	-0.29987E 01	-0.	0.	-0.	0.	
0.77809E 00	-0.24141E 01	-0.	0.	-0.	0.	
0.72858E-01	-0.21506E 01	-0.	0.	-0.	0.	
-0.13809E-00	-0.20910E 01	-0.	0.	-0.	0.	
-0.16757E-00	-0.29517E 01	-0.	0.	-0.	0.	
-0.19904E-00	-0.25313E 01	-0.	0.	-0.	0.	
-0.34072E-00	-0.23803E 01	-0.	0.	-0.	0.	
-0.13132E 01	-0.18525E 01	0.	0.	0.	0.	
-0.15916E 01	-0.15331E 01	0.	0.	0.	0.	
-0.16658E 01	-0.12681E 01	0.	0.	0.	0.	
-0.24453E 01	-0.87254E 00	0.	0.	0.	0.	
-0.33136E 01	0.10737E 01	0.	-0.	0.	-0.	
-0.51447E 01	0.19715E 01	0.	-0.	0.	-0.	
-0.54275E 01	0.31694E 01	0.	-0.	0.	-0.	
-0.54653E 01	0.45877E 01	0.	-0.	0.	-0.	
-0.50013E 01	0.49601E 01	0.	-0.	0.	-0.	
0.14277E 01	0.91832E 00	-0.	-0.	-0.	-0.	
0.15643E 01	0.14376E-00	-0.	-0.	-0.	-0.	
0.84113E 00	-0.12448E-00	-0.	-0.	-0.	-0.	
0.25744E-00	-0.12172E-00	-0.	-0.	-0.	-0.	
0.61850E-01	-0.54738E-01	-0.	-0.	-0.	-0.	
-0.21216E-01	-0.37744E-01	-0.	-0.	-0.	-0.	
0.12324E-03	-0.62769E-01	-0.	-0.	-0.	-0.	
0.17713E-01	-0.96603E-01	-0.	-0.	-0.	-0.	
0.29369E-02	-0.10807E-00	-0.	0.	-0.	0.	
-0.39261E-01	-0.85250E-01	-0.	0.	-0.	0.	
-0.74680E-01	-0.48494E-01	-0.	-0.	-0.	-0.	
-0.98868E-01	-0.17083E-01	-0.	-0.	-0.	-0.	
-0.75923E-01	0.	-0.	0.	-0.	0.	

Table XV - - - Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 15 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

BODY BALANCE STATION: 820 SEGMENT NUMBER 1

INCREMENTAL AXIAL STRESS

		REAL	IMAGINARY			
0.	0.	0.140208E 01	0.115026E 03	0.	0.	0.0
0.	0.	0.917791E 02	0.903446E 02	0.	0.	0.0
0.	0.	0.155846E 03	0.154006E 02	0.	0.	0.0
-0.	-0.	0.185588E 03	-0.277796E 02	0.	-0.	0.0
-0.	-0.	0.173211E 03	-0.615208E 02	0.	-0.	0.0
-0.	-0.	0.146711E 03	-0.777938E 02	0.	-0.	0.0
-0.	-0.	0.128095E 03	-0.900599E 02	0.	-0.	0.0
-0.	-0.	0.118119E 03	-0.102956E 03	0.	-0.	0.0
-0.	-0.	0.111844E 03	-0.111949E 03	0.	-0.	0.0
-0.	-0.	0.108611E 03	-0.117044E 03	0.	-0.	1.0
-0.	-0.	0.105477E 03	-0.272708E 03	0.	-0.	1.0
-0.	-0.	0.882064E 02	-0.348356E 03	0.	-0.	1.0
-0.	-0.	0.539972E 02	-0.435286E 03	0.	-0.	1.0
-0.	-0.	-0.217846E 02	-0.468136E 03	-0.	-0.	1.0
-0.	-0.	-0.943911E 02	-0.508466E 03	-0.	-0.	1.0
-0.	-0.	-0.202816E 03	-0.399708E 03	-0.	-0.	1.0
-0.	-0.	-0.485056E 03	-0.608106E 02	-0.	-0.	1.0
0.	0.	-0.538496E 03	0.113266E 03	-0.	0.	1.0
0.	0.	-0.378616E 03	0.117066E 03	-0.	0.	1.0
0.	0.	-0.104426E 03	0.821196E 02	-0.	0.	1.0
0.	0.	-0.465156E 02	0.524196E 02	-0.	0.	1.0
0.	0.	-0.159216E 02	0.268906E 02	-0.	0.	1.0
0.	0.	0.166126E 01	0.865396E 00	0.	0.	2.0
0.	0.	0.111336E 0.	-0.252906E 02	0.	0.	2.0
-0.	-0.	0.410836E 01	-0.331606E 02	0.	-0.	2.0
-0.	-0.	0.336166E 01	-0.519836E 02	0.	-0.	2.0
-0.	-0.	-0.942496E 01	-0.616546E 02	-0.	-0.	2.0
-0.	-0.	-0.216156E 02	-0.620076E 02	-0.	-0.	2.0
-0.	-0.	-0.314406E 02	-0.447206E 02	-0.	-0.	2.0
-0.	-0.	-0.586576E 02	-0.983206E 01	-0.	-0.	2.0
0.	0.	-0.578636E 02	0.251026E 01	-0.	0.	2.0
-0.	-0.	-0.221236E 02	-0.139046E 02	-0.	-0.	2.0
-0.	-0.	-0.286056E 01	-0.471916E 02	-0.	-0.	2.0
-0.	-0.	-0.474386E 01	-0.638476E 02	-0.	-0.	2.0
-0.	-0.	-0.272246E 02	-0.479206E 01	-0.	-0.	2.0
-0.	-0.	-0.806426E 02	-0.466996E 02	-0.	-0.	2.0
-0.	-0.	0.596136E 02	-0.126116E 03	0.	-0.	2.0
-0.	-0.	0.601516E 02	-0.233126E 03	0.	-0.	2.0
-0.	-0.	0.193066E 02	-0.325416E 03	0.	-0.	2.0
-0.	-0.	-0.569716E 02	-0.380096E 03	-0.	-0.	2.0
-0.	-0.	-0.140216E 03	-0.410356E 03	-0.	-0.	2.0
-0.	-0.	-0.415806E 03	-0.954006E 02	-0.	-0.	2.0
0.	0.	-0.737836E 03	0.341716E 03	-0.	0.	2.0
0.	0.	0.180196E 02	0.114106E 03	0.	0.	2.0
-0.	-0.	0.104826E 03	-0.632666E 02	0.	-0.	2.0
0.	0.	0.132876E 01	0.582396E 02	0.	0.	2.0
0.	0.	-0.222186E 03	0.158656E 03	-0.	0.	2.0
0.	0.	-0.122566E 03	0.152796E 03	-0.	0.	2.0
0.	0.	-0.548766E 02	0.130116E 03	-0.	0.	2.0
0.	0.	-0.101586E 02	0.100906E 03	-0.	0.	2.0
0.	0.	0.240336E 02	0.843706E 02	0.	0.	2.0
0.	0.	0.426226E 02	0.749366E 02	0.	0.	2.0
0.	0.	0.522746E 02	0.447146E 02	0.	0.	2.0
0.	0.	0.479686E 02	0.312566E 02	0.	0.	2.0
0.	0.	0.656496E 02	0.214996E 02	0.	0.	2.0
0.	0.	0.511266E 02	0.341126E 02	0.	0.	2.0
0.	0.	0.304216E 02	0.347056E 02	0.	0.	2.0
0.	0.	0.402726E 02	0.294966E 02	0.	0.	2.0
0.	0.	0.493466E 02	0.211246E 02	0.	0.	2.0
-0.	-0.	0.684936E 02	-0.129776E 02	0.	-0.	2.0
-0.	-0.	0.984986E 02	-0.279726E 02	0.	-0.	2.0
-0.	-0.	0.102976E 03	-0.477866E 02	0.	-0.	2.0
-0.	-0.	0.103416E 03	-0.710886E 02	0.	-0.	2.0
-0.	-0.	0.956636E 02	-0.777246E 02	0.	-0.	2.0
-0.	-0.	-0.863356E 01	-0.149926E 02	-0.	-0.	2.0
-0.	-0.	-0.107256E 02	-0.510316E 01	-0.	-0.	2.0
-0.	-0.	0.121456E-01	-0.479906E 01	0.	-0.	2.0
-0.	-0.	0.631636E 01	-0.722236E 01	0.	-0.	2.0
-0.	-0.	0.902316E 01	-0.962456E 01	0.	-0.	2.0
-0.	-0.	0.457886E-00	-0.853206E 01	0.	-0.	2.0
-0.	-0.	-0.507166E 01	-0.439696E 01	-0.	-0.	2.0
-0.	-0.	-0.896446E 01	-0.123246E-00	-0.	-0.	2.0
0.	0.	-0.942856E 01	0.263506E 01	-0.	0.	2.0
0.	0.	-0.788666E 01	0.567236E 01	-0.	0.	2.0
0.	0.	-0.576886E 01	0.943886E 01	-0.	0.	2.0
0.	0.	-0.412766E 01	0.279686E 01	-0.	0.	2.0
0.	0.	-0.323406E 01	0.	-0.	0.	2.0

Table XV - - - Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 20 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMI SPAN: 27 SEGMENT NUMBER 10

INCREMENTAL SHEAR STRESS REAL	INCREMENTAL SHEAR STRESS IMAGINARY	INCREMENTAL AXIAL STRESS REAL	INCREMENTAL AXIAL STRESS IMAGINARY			FREQUENCY K CPS
0.842218-01	0.353858 02	-0.806818 C0	0.305658 05	0.	-0.	0.10
0.243478 02	0.299478 02	0.198988 C3	0.262108 05	-0.	-0.	0.20
0.441328 02	0.836528 01	0.370228 C3	0.789068 02	-0.	-0.	0.30
0.553938 02	-0.513328 01	0.473398 03	-0.592618 02	-0.	0.	0.40
0.530948 02	-0.165058 02	0.457568 C3	-0.141928 05	-0.	0.	0.50
0.461908 02	-0.224348 02	0.400738 C3	-0.197488 03	-0.	0.	0.60
0.412538 02	-0.270168 02	0.358C0E C3	-0.249968 05	-0.	0.	0.70
0.382318 02	-0.312738 02	0.329868 C3	-0.285308 03	-0.	0.	0.80
0.365218 02	-0.378158 02	0.311448 C3	-0.339528 05	-0.	0.	0.90
0.359248 02	-0.562538 02	0.296878 C3	-0.517208 05	-0.	0.	1.00
0.366538 C2	-0.671888 02	0.277838 03	-0.802768 03	-0.	0.	1.10
0.334958 02	-0.128978 05	0.209038 05	-0.102568 04	0.	0.	1.20
0.228488 02	-0.167718 03	0.965408 02	-0.127808 04	0.	-0.	1.30
-0.428968 01	-0.189468 03	-0.142048 03	-0.140508 04	0.	-0.	1.40
-0.323438 02	-0.229258 03	-0.365518 03	-0.147898 04	0.	-0.	1.50
-0.754958 02	-0.171118 03	-0.694828 03	-0.109768 04	0.	-0.	1.60
-0.399118 03	-0.359C28 02	-0.153328 04	-0.301468 03	-0.	-0.	1.70
-0.239258 03	0.464628 02	-0.166628 04	0.408308 03	-0.	0.	1.80
-0.182878 03	C.700848 02	-0.117638 04	0.408708 03	-0.	0.	1.90
-0.708408 02	0.644378 02	-0.963738 03	0.307298 03	-0.	0.	2.00
-0.453088 02	0.622498 02	-0.201508 03	0.251808 03	-0.	0.	2.10
-0.302188 02	0.637148 02	-0.120598 C3	0.175138 03	-0.	0.	2.20
-0.206368 02	0.659808 C2	-0.772738 02	0.127958 03	-0.	0.	2.30
-0.562188 01	0.744998 02	-0.561498 02	0.871798 02	-0.	0.	2.40
0.340828 02	0.700938 02	-0.520188 02	0.700018 02	0.	0.	2.50
0.172338 02	0.270418 02	-0.524138 C2	0.461938 02	0.	0.	2.60
0.244728 C2	0.798228 02	-0.655308 02	0.562458 02	0.	0.	2.70
0.340618 02	0.797248 02	-0.856468 02	0.357548 02	0.	0.	2.80
0.390098 02	0.729218 02	-0.974728 C2	0.564868 02	0.	0.	2.90
0.505338 02	0.693528 02	-0.129108 03	0.100528 03	0.	0.	3.00
0.503818 02	0.693148 02	-0.120448C 05	0.114768 03	0.	0.	3.10
0.455358 02	0.840118 02	-0.842468 02	0.970858 02	0.	0.	3.20
0.546318 C2	0.105928 05	-0.633128 02	0.660918 02	0.	0.	3.30
0.101028 03	0.104568 03	-0.488458 02	0.566728 02	0.	0.	3.40
0.147668 03	-0.105308 03	-0.982468 C2	0.148058 03	0.	-0.	3.50
0.292348 03	-0.363498 03	-0.144158 03	0.143278 03	0.	-0.	3.60
-0.283098 02	-0.118128 03	0.163528 C2	0.113918 03	-0.	-0.	3.70
-0.561328 02	-0.939408 02	0.269148 02	0.967258 02	-0.	-0.	3.80
-0.233228 02	-0.852848 02	0.307918 02	0.903108 02	-0.	-0.	3.90
-0.810368 02	-0.833828 02	0.335238 02	0.875058 02	-0.	-0.	4.00
-0.882398 02	-0.825158 02	0.362218 02	0.808858 02	-0.	-0.	4.10
-0.109728 03	-0.714108 02	0.450808 02	0.624418 02	-0.	-0.	4.20
-0.152048 03	0.897C78 02	0.538238 02	0.450478 02	-0.	0.	4.30
-0.201698 03	0.162428 03	0.105238 02	0.612168 02	-0.	0.	4.40
-0.164658 05	0.216438 03	0.472208 01	0.774438 02	-0.	0.	4.50
-0.100038 02	0.678638 02	0.145428 02	0.651318 02	-0.	0.	4.60
0.758128 02	0.123148 02	0.417088 02	0.421108 02	0.	-0.	4.70
0.477248 02	-0.540858 01	0.476228 02	0.323458 02	0.	-0.	4.80
0.249128 02	-0.304158 02	0.442148 02	0.253498 02	0.	-0.	4.90
0.303278 02	-0.103708 02	0.426258 02	0.198538 02	0.	-0.	5.00
0.387078-00	-0.920668 01	0.473278 02	0.119688 02	-0.	-0.	5.10
-0.352868 01	-0.848218 01	0.601778 02	0.287238 01	-0.	-0.	5.20
-0.498248 01	-0.627798 01	0.730538 02	-0.535188 02	-0.	0.	5.30
-0.698168 01	-0.617278 01	0.951248 02	-0.824938 02	-0.	0.	5.40
-0.725818 01	-0.67[illegible]98E 01	0.942978 02	-0.858518 02	-0.	0.	5.50
-0.708018 01	-0.67[illegible]E 01	-0.128108 02	-0.360168 02	0.	0.	5.60
-0.781598 01	-0.[illegible]01	-0.302208 02	-0.150788 02	0.	-0.	5.70
-0.913298 01	-0.[illegible]01	-0.229728 02	-0.771928 01	-0.	-0.	5.80
-0.108938 02	-0.[illegible]E 01	-0.206318 02	-0.366878 01	-0.	-0.	5.90
-0.130558 02	0.586358 01	-0.239598 02	0.105268 02	-0.	-0.	6.00
-0.173868 02	0.603538 01	-0.352038 02	0.169628 02	-0.	0.	6.00
-0.180598 02	0.891058 01	-0.370398 02	0.255698 02	-0.	0.	6.00
-0.181678 02	0.123108 02	-0.373638 02	0.358008 02	-0.	0.	6.00
-0.171108 02	0.137218 02	-0.337158 02	0.508208 02	-0.	0.	6.00
-0.208138 01	0.492368 01	0.134158 02	0.936718 01	-0.	0.	6.20
-0.143088 01	0.363688 01	0.157488 02	0.317548 01	-0.	0.	6.40
-0.276088 01	0.381998 01	0.111468 02	0.13424E-00	-0.	0.	6.60
-0.329408 01	0.439C48 01	0.732158 01	-0.867748 00	-0.	0.	7.00
-0.287318 01	0.514558 01	0.589448 01	-0.173668 01	-0.	0.	7.40
-0.111058 01	0.484798 01	0.426038 01	-0.252998 01	-0.	0.	8.00
0.816878 C0	0.377668 01	0.356928 01	-0.285758 01	-0.	0.	9.00
0.242898 C1	0.157238 01	0.221318 01	-0.304418 01	0.	0.	10.00
0.361088 01	0.23C418-00	0.179648 01	-0.283458 01	0.	0.	11.00
0.374818 01	-0.122148 01	0.260498-00	-0.244308 01	0.	-0.	12.00
0.312428 01	-0.218718 01	-0.545658 00	-0.189498 01	0.	-0.	13.00
0.214018 01	-0.258138 01	-0.104588 01	-0.122998 01	0.	-0.	14.00
0.978498 00	-0.253968 01	-0.142438 01	-0.668898 00	0.	-0.	15.00
-0.336608-00	-0.207568 01	-0.358278 01	-0.196478-01	-0.	-0.	16.00
-0.100998 01	-0.139808 01	-0.142008 01	0.629068 00	-0.	-0.	17.00
-0.360598 01	-0.643918 00	-0.356148 01	0.128338 01	-0.	0.	18.00
-0.182388 01	0.772868-01	-0.129498 01	0.394898 01	-0.	0.	19.00
-0.125918 01	0.	-0.786918 00	0.	-0.	0.	20.00

Table XV - - - Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 20 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMISPAN: 27 SEGMENT NUMBER 14

INCREMENTAL SHEAR STRESS REAL	INCREMENTAL SHEAR STRESS IMAGINARY	INCREMENTAL AXIAL STRESS REAL	INCREMENTAL AXIAL STRESS IMAGINARY			FREQUENCY CPS
0.629663E-02	0.107609E 03	0.732166E 00	0.275555E 03	0.	-0.	0.10
0.721529E 02	0.513299E 02	0.180571E 03	0.237185E 03	-0.	-0.	0.30
0.137019E 03	0.266476E 02	0.335946E 03	0.716059E 32	-0.	-0.	0.50
0.166670E 03	-0.144496E 02	0.429596E 03	-0.356629E 02	-0.	0.	0.70
0.160108E 03	-0.491998E 02	0.415258E 03	-0.128799E 03	-0.	0.	0.90
0.139227E 03	-0.673113E 02	0.363658E 03	-0.179211E 03	-0.	0.	1.10
0.123966E 03	-0.811121E 02	0.324888E 03	-0.211866E 03	-0.	0.	1.30
0.114116E 03	-0.951111E 02	0.299346E 03	-0.258911E 03	-0.	0.	1.50
0.108007E 03	-0.112355E 03	0.282638E 03	-0.300810E 03	-0.	0.	1.70
0.104521E 03	-0.129053E 03	0.271331E 03	-0.469955E 33	-0.	0.	1.90
0.101098E 03	-0.269007E 03	0.251652E 03	-0.728699E 03	-0.	0.	2.10
0.854094E 02	-0.144899E 03	0.199222E 03	-0.930699E 03	0.	0.	2.30
0.576698E 02	-0.439177E 03	0.874279E 02	-0.115978E 04	0.	-0.	2.50
-0.222229E 02	-0.488954E 03	-0.128900E 03	-0.127508E 04	0.	-0.	2.70
-0.936395E 02	-0.524111 03	-0.331699E 03	-0.134218E 04	0.	-0.	2.90
-0.207172E 01	-0.415900E 03	-0.630538E 03	-0.998607E 03	0.	-0.	3.10
-0.502773E 03	-0.745671 02	-0.139146E 04	-0.920168E 02	-0.	-0.	3.30
-0.583046E 03	0.117498E 03	-0.151208E 04	0.370538E 03	-0.	0.	3.50
-0.428346E 03	0.147588E 03	-0.106568E 04	0.370899E 03	-0.	0.	3.70
-0.148046E 03	0.122616E 03	0.730088E 03	0.279826E 03	-0.	0.	3.90
-0.880629E 02	0.105299E 03	-0.182886E 03	0.210355E 03	-0.	0.	4.10
-0.559799E 02	0.955527E 02	-0.109446E 03	0.153893E 03	-0.	0.	4.30
-0.359801E 02	0.922228E 02	-0.701246E 02	0.116116E 03	-0.	0.	4.50
-0.185522E 02	0.880646E 02	-0.491398E 02	0.791136E 02	-0.	0.	4.70
0.498246E 01	0.860 90E 02	-0.472059E 02	0.683524E 02	0.	0.	4.90
0.820116E 01	0.818329E 02	-0.477451 02	0.619199E 02	0.	0.	5.10
0.136772E 02	0.820953E 02	-0.594677 02	0.328691E 02	0.	0.	5.30
0.178794E 02	0.816492E 02	-0.777211E 02	0.324466E 02	0.	0.	5.50
0.197961E 02	0.803799E 02	-0.886956E 02	0.512599E 02	0.	0.	5.70
0.224609E 02	0.860092E 02	-0.117166E 03	0.910037E 02	0.	0.	5.90
0.222154E 02	0.972227E 02	-0.114768E 03	0.104146E 03	0.	0.	6.10
0.301429E 02	0.109558E 03	-0.784468E 02	0.881102E 02	0.	0.	6.30
0.493256E 02	0.123 6E 03	-0.574956E 02	0.599761 02	0.	0.	6.50
0.102826E 03	0.119652E 03	-0.624756E 02	0.514296E 02	0.	0.	6.70
0.173952E 03	-0.106660E 03	-0.873436E 02	0.134356E 03	0.	-0.	6.90
0.302566E 03	-0.172366E 03	-0.132636E 03	0.130026E 03	0.	-0.	7.10
-0.321336E 02	-0.134276E 03	0.148396E 02	0.100336E 03	-0.	-0.	7.30
-0.628836E 02	-0.119836E 03	0.244746E 02	2.877746E 02	-0.	-0.	7.50
-0.847026E 02	-0.120696E 03	0.279436E 02	0.819546E 02	-0.	-0.	7.70
-0.103946E 03	-0.124186E 03	0.304216E 02	0.794096E 02	-0.	-0.	7.90
-0.120966E 03	-0.128366E 03	0.328706E 02	0.734016E 02	-0.	-0.	8.10
-0.174596E 03	-0.869476E 02	0.409096E 02	0.566646E 02	-0.	-0.	8.30
-0.260316E 03	0.161936E 03	0.488436E 02	0.408606E 02	-0.	0.	8.50
-0.259636E 03	0.244106E 03	0.954986E 01	0.555526E 02	-0.	0.	8.70
-0.203901 03	0.294256E 03	0.433056E 01	0.702786E 02	-0.	0.	8.90
-0.606716E 02	0.151836E 03	0.131966E 02	0.591056E 02	-0.	0.	9.10
0.854326E 02	0.454706E 02	0.432946E 02	0.382216E 02	0.	-0.	9.30
0.608346E 02	0.154926E 02	0.432146E 02	0.293706E 02	0.	-0.	9.50
0.182806E 02	0.924606E 01	0.401256E 02	0.230036E 02	0.	-0.	9.70
0.248616E 02	0.512206E 01	0.386856E 02	0.169276E 02	0.	-0.	9.90
0.199416E 02	0.252596E 01	0.429486E 02	0.108616E 02	-0.	-0.	10.10
0.252516E 02	-0.159776E 01	0.546096E 02	0.260676E 01	-0.	-0.	10.30
0.321306E 02	-0.334876E 02	0.662946E 02	-0.485676E 02	-0.	0.	10.50
0.446126E 02	-0.500526E 02	0.863226E 02	-0.748606E 02	-0.	0.	10.70
0.383746E 02	-0.516396E 02	0.766976E 02	-0.779076E 02	-0.	0.	10.90
-0.212096E 02	-0.217536E 02	-0.161626E 02	-0.326846E 02	0.	0.	11.10
-0.288786E 02	-0.830466E 01	-0.274696E 02	-0.136816E 02	0.	-0.	11.30
-0.248046E 02	-0.278176E 01	-0.208466E 02	-0.700506E 01	-0.	-0.	11.50
-0.235326E 02	0.526906E 00	-0.187236E 02	-0.332936E 01	-0.	-0.	11.70
-0.257526E 02	0.107956E 02	-0.217426E 02	0.955236E 01	-0.	-0.	11.90
-0.333186E 02	0.151066E 02	-0.319466E 02	0.153936E 02	-0.	0.	12.10
-0.345776E 02	0.213266E 02	-0.336126E 02	0.232046E 02	-0.	0.	12.30
-0.346806E 02	0.286496E 02	-0.337246E 02	0.324876E 02	-0.	0.	12.50
-0.323406E 02	0.315836E 02	-0.305966E 02	0.353196E 02	-0.	0.	12.70
0.429336E-00	0.118716E 02	0.121746E 02	0.850056E 01	-0.	0.	12.90
0.311086E 01	0.797566E 01	0.142916E 02	0.267976E 01	-0.	0.	13.10
0.821006E 00	0.630266E 01	0.101156E 02	0.121826E-06	-0.	0.	13.30
+0.295516E-00	0.593336E 01	0.668956E 01	-0.787456E 00	-0.	0.	13.50
-0.608166E-01	0.546696E 01	0.534916E 01	-0.157596E 01	-0.	0.	13.70
0.196826E 01	0.394996E 01	0.386616E 01	-0.211436E 01	-0.	0.	13.90
0.299026E 01	0.230476 01	0.322136E 01	-0.259296E 01	-0.	0.	14.10
0.360006E 01	0.622326E 00	0.200846E 01	-0.276246E 01	0.	0.	14.30
0.355536E 01	-0.452676E-00	0.117656E 01	-0.257226E 01	0.	0.	14.50
0.298686 01	-0.961546E 00	0.236386E-00	-0.221706E 01	0.	-0.	14.70
0.222396E 01	-0.122066E 01	-0.495166E-00	-0.171966E 01	0.	-0.	14.90
0.171726E 01	-0.125426 01	-0.949026E 00	-0.111616E 01	0.	-0.	15.10
0.137566E 01	-0.149716E 01	-0.129256E 01	-0.600656E 00	0.	-0.	15.30
0.113506E 01	-0.172836E 01	-0.140636E 01	-0.178296E-01	-0.	-0.	15.50
0.966466E 00	-0.203856E 01	-0.147026E 01	0.570866E 00	-0.	-0.	15.70
0.374496E-00	-0.222276 01	-0.141696E 01	0.116266E 01	-0.	0.	15.90
-0.266506E-00	-0.209716E 01	-0.117506E 01	0.176866E 01	-0.	0.	16.10
-0.114846 01	0.	-0.719106E 00	0.	-0.	0.	16.30

Table XV- - - Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 20 CPS
ALTITUDE: 24 000 FT
MACH NUMBER: 0.85

PERCENT SEMISPAN: 40.06 SEGMENT NUMBER 8

INCREMENTAL SHEAR STRESS REAL	INCREMENTAL SHEAR STRESS IMAGINARY	INCREMENTAL AXIAL STRESS REAL	INCREMENTAL AXIAL STRESS IMAGINARY			FREQUENCY CPS
-0.134278-00	0.73780E 02	-0.12489E 01	0.27897E 03	0.	0.	0.00
0.49232E 02	0.63168E 02	0.18058E 03	0.24197E 03	0.	0.	0.20
0.90530E 02	0.18692E 02	0.33889E 03	0.73329E 02	0.	0.	0.35
0.11480E 03	-0.95961E 01	0.43606E 03	-0.36597E 02	0.	-0.	0.44
0.11057E 03	-0.33906E 02	0.42277E 03	-0.13336E 03	0.	-0.	0.50
0.96627E 02	-0.46659E 02	0.37331E 03	-0.18678E 03	0.	-0.	0.60
0.86442E 02	-0.56777E 02	0.33216E 03	-0.22938E 03	0.	-0.	0.70
0.80023E 02	-0.67218E 02	0.30607E 03	-0.27272E 03	0.	-0.	0.80
0.76276E 02	-0.80304E 02	0.28859E 03	-0.32593E 03	0.	-0.	0.90
0.74177E 02	-0.12527E 03	0.27612E 03	-0.49926E 03	0.	-0.	1.00
0.72554E 02	-0.20125E 03	0.25167E 03	-0.77483E 03	0.	-0.	1.20
0.60560E 02	-0.26338E 03	0.17801E 03	-0.98754E 03	0.	-0.	1.30
0.36717E 02	-0.33621E 03	0.62019E 02	-0.12251E 04	0.	-0.	1.40
-0.24660E 02	-0.37509E 03	-0.17589E 03	-0.13415E 04	-0.	-0.	1.45
-0.87688E 02	-0.40102E 03	-0.39572E 03	-0.14035E 04	-0.	-0.	1.47
-0.17080E 03	-0.31481E 03	-0.71632E 03	-0.10105E 04	-0.	-0.	1.39
-0.40766E 03	-0.44464E 02	-0.15157E 04	-0.63774E 02	-0.	-0.	1.25
-0.46553E 03	0.12459E 03	-0.16147E 04	0.43392E 03	-0.	0.	1.00
-0.34223E 03	0.13052E 03	-0.11241E 04	0.40837E 03	-0.	0.	1.05
-0.11575E 03	0.11104E 03	-0.34088E 03	0.30.40E 03	-0.	0.	1.00
-0.71877E 02	0.67544E 02	-0.18770E 03	0.22646E 03	-0.	0.	1.10
-0.46054E 02	0.85608E 02	-0.11287E 03	0.16780E 03	-0.	0.	2.00
-0.30070E 02	0.85379E 02	-0.74624E 02	0.13631E 03	-0.	0.	2.10
-0.18259E 02	0.85926E 02	-0.58672E 02	0.12019E 02	-0.	0.	2.20
-0.11848E 02	0.93029E 02	-0.83442E 02	0.86987E 02	0.	0.	2.30
-0.40112E 01	0.56563E 02	-0.76428E 02	0.67019E 02	0.	0.	2.35
0.79344E 01	0.97221E 02	-0.77510E 02	0.58253E 02	0.	0.	2.40
0.16314E 02	0.96724E-02	-0.70500E 02	0.57577E 02	0.	0.	2.43
0.20157E 02	0.91623E 02	-0.98331E 02	0.71148E 02	0.	0.	2.44
0.29270E 02	0.84825E 02	-0.11755E 03	0.91304E 02	0.	0.	2.47
0.30806E 02	0.87224E 02	-0.11170E 03	0.94983E 02	0.	0.	2.50
0.29456E 02	0.95293E 02	-0.84988E 02	0.74559E 02	0.	0.	2.54
0.36266E 02	0.10757E 03	-0.79607E 02	0.46086E 02	0.	0.	2.58
0.65852E 02	0.10666E 03	-0.10917E 03	0.45512E 02	0.	0.	2.65
0.10612E 03	-0.13761E 02	-0.15902E 03	0.21357E 03	0.	-0.	2.70
0.17839E 03	-0.26827E 02	-0.23245E 03	0.21506E 03	0.	-0.	2.80
0.75315E 01	0.11344E 02	0.22571E 02	0.38451E 03	0.	-0.	3.00
0.51209E 01	0.47821E 02	0.37644E 02	0.18175E 03	-0.	0.	3.10
0.21322E 02	0.73985E 02	0.51011E 02	0.19243E 03	0.	0.	3.20
0.45044E 02	0.89867E 02	0.71164E 02	0.20092E 03	0.	0.	3.26
0.70777E 02	0.10414E 03	0.93273E 02	0.19993E 03	0.	0.	3.29
0.15039E 03	0.32819E 02	0.16767E 03	0.10581E 03	0.	0	3.35
0.25759E 03	-0.19268E 03	0.25553E 03	-0.28114E 02	0.	-0.	3.40
0.14869E 03	-0.21570E 03	0.38876E 02	0.359956E 02	0.	-0.	3.52
0.16051E 03	-0.22697E 03	0.12440E 02	0.87636E 02	0.	-0.	3.56
0.38661E 02	-0.14463E 03	0.43518E 02	0.43237E 02	0.	-0.	3.60
-0.58454E 02	-0.79612E 02	0.11698E 03	-0.29820E 01	-0.	-0.	3.70
-0.57976E 02	-0.46976E 02	0.87771E 02	-0.32397E 02	-0.	-0.	3.89
-0.50958E 02	-0.33437E 02	0.64794E 02	-0.16934E 02	-0.	-0.	4.00
-0.46018E 02	-0.19654E 02	0.46988E 02	-0.20489E 02	-0.	-0.	4.20
-0.43821E 02	-0.12295E 02	0.28227E 02	-0.21220E 02	-0.	-0.	4.30
-0.46140E 02	-0.72400E 01	0.14621E 02	-0.18972E 02	-0.	-0.	4.70
-0.49780E 02	0.13853E 02	0.54529E 01	0.25395E 01	-0.	0.	4.80
-0.54656E 02	0.23633E 02	-0.10687E 02	0.14755E 02	-0.	0.	4.96
-0.50699E 02	0.25984E 02	-0.82822E 01	0.18381E 02	-0.	0.	5.00
-0.17279E 02	0.12101E 02	0.30522E 02	-0.30969E 01	-0.	0.	5.15
-0.12780E 02	0.77925E 01	0.33255E 02	-0.12940E 02	-0.	0.	5.20
-0.14123E 02	0.75495E 01	0.25541E 02	-0.16341E 02	-0.	0.	5.50
-0.14089E 02	0.78174E 01	0.18607E 02	-0.17001E 02	-0.	0.	5.70
-0.13001E 02	0.65373E 01	0.14156E 02	-0.15583E 02	-0.	0.	5.89
-0.10566E 02	0.56913E 01	0.97900E 01	-0.14867E 02	-0.	0.	6.00
-0.10184E 02	0.45190E 01	0.92537E 01	-0.13975E 02	-0.	-0.	6.09
-0.10087E 02	0.31225E 01	0.89962E 01	-0.13037E 02	-0.	-0.	6.66
-0.10561E 02	0.38419E 01	0.91907E 01	-0.14407E 02	-0.	-0.	6.68
-0.17239E 02	0.97298E 01	0.11885E 02	-0.16962E 02	-0.	0.	6.80
-0.15966E 02	0.11746E 02	0.75824E 01	-0.16396E 02	-0.	0.	7.40
-0.13637E 02	0.13696E 02	0.40058E 01	-0.13903E 02	-0.	0.	.60
-0.96417E 01	0.14435E 02	-0.60244E 00	-0.11334E 02	-0.	0.	.00
-0.61107E 01	0.14214E 02	-0.32339E 01	-0.67263E 01	-0.	0.	7.40
-0.75521E-01	0.12040E 02	-0.64070E 01	-0.16090E 01	-0.	0.	8.20
0.52006E 01	0.73408E 01	-0.68379E 01	0.19677E 01	0.	0.	9.00
0.91311E 01	0.20057E 01	-0.47096E 01	0.39020E 01	0.	0.	10.00
0.10648E 02	-0.28879E 01	-0.11278E 01	0.22374E 01	0.	-0.	11.00
0.94345E 01	-0.64674E 01	0.18304E 01	-0.20993E-00	0.	-0.	12.00
0.65287E 01	-0.80264E 01	0.30311E 01	0.28541E 01	0.	-0.	13.00
0.25512E 01	-0.77335E 01	0.24030E 01	-0.45381E 01	0.	-0.	14.00
-0.12972E 01	-0.57597E 01	0.11744E-00	-0.44539E 01	-0.	-0.	15.00
-0.42634E 01	-0.30551E 01	-0.29933E 01	-0.25030F 01	-0.	-0.	16.00
-0.59672E 01	-0.51029E-01	-0.55505E 01	0.86736E 00	-0.	-0.	17.00
-0.61324E 01	0.24047E 01	-0.68224E 01	0.45982E 01	-0.	0.	18.00
-0.51799E 01	0.40225E 01	-0.59469E 01	0.75800E 01	-0.	0.	19.00
-0.32513E 01	0.	-0.30834E 01	0.	-0.	0.	20.00

Table XV - - - Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY 20 CPS
ALTITUDE: 24,900 FT
MACH NUMBER: 0.85

PERCENT SEMISPAN: 40.06 SEGMENT NUMBER 10

INCREMENTAL SHEAR STRESS REAL	INCREMENTAL SHEAR STRESS IMAGINARY			INCREMENTAL AXIAL STRESS REAL	INCREMENTAL AXIAL STRESS IMAGINARY	FREQUENCY CPS
-0.949C3E-01	0.717C7E 02	0.	0.	0.1C821E 01	-0.23836E 03	0.10
0.690C4E 02	0.61323E 02	0.	0.	-0.1342?F 03	-0.20674E 03	0.30
0.88C23E 02	0.18141E 02	0.	0.	-0.2?95?E 03	-0.62655E 02	0.36
0.11137E 33	-0.9201E 01	0.	-0.	-0.5?2?9E 03	0.31270E 02	0.44
0.10714E 03	-0.52463E 02	0.	-0.	-0.3613?E 03	0.11395E 03	0.50
0.93501E 02	-0.44728E 02	0.	-0.	-0.3?1?6E 03	0.15958E 03	0.60
0.835C9E 02	-0.54230E 02	0.	-0.	-0.2?89?E 03	0.19582E 03	0.70
0.27320E 02	-0.64027E 02	0.	-0.	-0.1?151E 03	0.23302E 03	0.80
0.23625E 02	-0.76292E 02	0.	-0.	-0.246?8E 03	0.27849E 03	0.90
0.71693E C2	-0.11851E 03	0.	-0.	-0.33593E 03	0.42658E 03	1.00
0.70455E C3	-0.19038E 03	0.	-0.	-0.21504E 03	0.66204E 03	1.20
0.5?9C6E 02	-0.24886E 03	0.	-0.	-0.1?210E 03	0.84379E 03	1.34
0.36214E 32	-0.31802E 03	0.	-0.	-0.52?9?E 02	0.10467E 04	1.40
-0.18887E 02	-0.35531E 03	-0.	-0.	0.15529E 03	0.11462E 04	1.45
-0.73127E 02	-0.38142E 03	-0.	-0.	0.33911E 03	0.11992E 04	1.47
-0.1558BE C3	-0.30203E 03	-0.	-0.	0.612?5E 03	0.96332E 03	1.90
-0.32694E 03	-0.47942E 02	-0.	-0.	0.12951E 04	0.37402E 02	1.25
-0.61273E 03	0.96081E 02	-0.	0.	0.13?97E 04	-0.37076E 03	1.60
-0.32248E 03	0.12073E 03	-0.	0.	0.96047E 03	-0.34892E 03	1.65
-0.11364E 03	0.10294E 03	-0.	0.	0.29126E 03	-0.26015E 03	1.80
-0.68C88E 02	0.90529E 02	-0.	0.	0.16038E 03	-0.19366E 03	1.90
-0.4352PE 02	0.43204E 02	-0.	0.	0.9?4?5E 02	-0.14332E 03	2.00
-0.28166E C2	0.29240E 02	-0.	0.	0.637?1E 02	-0.99383F 02	2.10
-0.1671?E 02	0.29222E 32	-0.	0.	0.5C131E 02	-0.70080E 02	2.20
-0.10193E 02	0.853?3E '2	0.	0.	0.712?0C 02	-0.?4324E 02	2.30
-0.313?9E 01	0.881?9E	0.	0.	0.653?2E 02	-0.522?3E 02	2.35
0.75040E 01	0.88461E	0.	0.	0.662?2E 02	-0.49?74E 02	2.40
0.1457?E 02	0.829?0E 0_	0.	0.	0.773?6E 02	-0.4919?E 02	2.43
0.17699E 02	0.84172E 02	0.	0.	0.?4012E 02	-0.60791E 02	2.46
0.24526E 02	0.80?94E 02	0.	0.	0.10044E 03	-0.82285E 02	2.47
0.25736E 02	0.844?2E 02	0.	0.	0.954?9E 02	-0.811?6E 02	2.50
0.26670E 02	0.92072E 02	0.	0.	0.726?7E 02	-0.63706E 02	2.54
0.3451?E 02	0.10295E 03	0.	0.	0.6401?F 02	-0.39?7?E 02	2.58
0.65C66E 02	0.13103E 03	0.	0.	0.932?6E 02	-0.38887E 02	2.65
0.10469E 03	-0.12763E 02	0.	-0.	0.13587E 03	-0.1?248E 03	2.70
0.17355E 03	-0.29493E 02	0.	-0.	0.17?61E 03	-0.18376E 03	2.80
0.67325E 01	0.66228E 01	0.	-0.	-0.19285E 02	-0.15765E 03	3.00
0.4716?E C1	0.40070E 02	-0.	0.	-0.?21?6E 02	-0.15529E 03	3.10
0.19904E 02	0.63533E 02	0.	0.	-0.?3585E 02	-0.16442E 03	3.20
0.42623E 02	0.?27?3E 02	0.	0.	-0.?1805E 02	-0.17167E 03	3.26
0.64690E 02	0.91010E 02	0.	0.	-0.296495E 02	-0.12063E 03	3.29
0.13596E 03	0.28895E 02	0.	0.	-0.143?6E 03	-0.90406E 02	3.35
0.23356E 03	-0.18150E 03	0.	-0.	-0.?1833E 03	0.24021E 02	3.40
0.14525E 03	-0.21045E 03	0.	-0.	-0.33?14E 02	-0.30?22E 02	3.52
0.10007E 03	-0.?2522E 03	0.	-0.	-0.?0629E 02	-0.74879E 02	3.56
0.35625E 02	-0.14012E 03	0.	-0.	-0.37183E 02	-0.36943E 02	3.60
-0.65334E 02	-0.69?18E 02	-0.	-0.	-0.?9945E 02	0.22061E 01	3.70
-0.61333E 02	-0.43954E 02	-0.	-0.	-0.?4995E 02	0.10592E 02	3.85
-0.52110E 02	-0.28084E 02	-0.	-0.	-0.553?2E 02	0.14469E 02	4.00
-0.453951 02	-0.14977E 02	-0.	-0.	-0.40148E 02	0.17672E 02	4.20
-0.40C521 02	-0.84863E 01	-0.	-0.	-0.?41?8E 02	0.18131E 02	4.50
-0.40C5?E 02	-0.42?36E 01	-0.	-0.	-0.12493E 02	0.16211E 02	4.70
-0.40B55E 02	0.73882E 01	-0.	0.	-0.46591E 01	-0.21699E 01	4.80
-0.41978E 02	0.12512E 02	-0.	0.	0.913?6E 01	-0.12607E 02	4.96
-0.39523E 02	0.14125E 02	-0.	0.	0.70?57E 01	-0.15706E 02	5.00
-0.2?05?E 02	0.82321E 01	-0.	0.	-0.26079E 02	0.?6461E 01	5.15
-0.19?5BE 02	0.73037E 01	-0.	0.	-0.28414E 02	0.11057E 02	5.30
-0.14951E 02	0.81940E 01	-0.	0.	-0.?1823E 02	0.13963E 02	5.50
-0.17951E 02	0.89525E 01	-0.	0.	-0.15898E 02	0.14526E 02	5.70
-0.16827E 02	0.91627E 01	-0.	0.	-0.12130E 02	0.13315E 02	5.85
-0.15?8PE 02	0.89938E 01	-0.	0.	-0.83649E 01	0.12703E 02	6.00
-0.15045E 02	0.82355E 01	-0.	-0.	-0.?9067?E 01	0.11940E 02	6.65
-0.14960E 02	0.84372E 01	-0.	-0.	-0.?6866E 01	0.11140E 02	6.06
-0.15049E 02	0.96078E 01	-0.	-0.	-0.?8528E 01	0.12310E 02	6.08
-0.16698E 02	0.12232E 02	-0.	0.	-0.101559E 02	0.14493E 02	6.20
-0.145731 02	0.13445E 02	-0.	0.	-0.66?86E 01	0.14009E 02	6.40
-0.12478E 02	0.14763E 02	-0.	0.	-0.34227E 01	0.11880S 02	6.60
-0.855?9E 01	0.15110E 02	-0.	0.	0.51474E 00	0.96840E 01	7.00
-0.50057E 01	0.14330E 02	-0.	0.	0.?2?42E 01	0.57489E 01	7.40
0.97795E 00	0.11684E 02	-0.	0.	0.54?63E 01	0.13748E 01	8.20
0.60?69E 01	0.66956E 01	0.	0.	0.58?25E 01	-0.16812E 01	9.00
0.95328E 01	0.13667E 01	0.	0.	0.55?69E 01	-0.28213E 01	10.00
0.106651 02	-0.33034E 01	0.	-0.	0.96?56E 00	-0.19112E 01	11.00
0.91100E C1	-0.66079E 01	0.	-0.	-0.15639E 01	0.17937E-00	12.00
0.61152E 01	-0.78380E 01	0.	-0.	-0.25?79E 01	0.24586E 01	13.00
0.72129E 01	-0.73866E 01	0.	-0.	-0.?0532E 01	0.38775E 01	14.00
-0.14059E 01	-0.54632E 01	-0.	-0.	-0.10034E-00	0.38055E 01	15.00
-0.40910E 01	-0.28838E 01	-0.	-0.	0.?5576E 01	0.21586E 01	16.00
-0.56070I 01	-0.17401E-00	-0.	-0.	0.47423E 01	-0.74110E 00	17.00
-0.57021E 01	0.20822E 01	-0.	0.	0.58?93E 01	-0.39?89E 01	18.00
-0.48792E 01	0.35629E 02	-0.	0.	0.50812E 01	-0.64766E 01	19.00
-0.32850E 01	0.	-0.	0.	0.?6362E 01	0.	20.00

Table XV – – – Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 20 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

BODY BALANCE STATION: 540 SEGMENT NUMBER 17

INCREMENTAL SHEAR STRESS REAL	IMAGINARY					
-0.41556E-01	-0.11891E 01	0.	-0.	0.	-0.	
-0.12179E 01	-0.77898E 00	0.	-0.	0.	-0.	
-0.18598E 01	0.91125E-01	0.	-0.	0.	-0.	
-0.19906E 01	0.50408E 00	-0.	-0.	-0.	-0.	
-0.17376E 01	0.74625E 00	-0.	-0.	-0.	-0.	
-0.13591E 01	0.80593E 00	-0.	-0.	-0.	-0.	
-0.11179E 01	0.82421E 00	-0.	-0.	-0.	-0.	
-0.98007E 00	0.84129E 00	-0.	-0.	-0.	-0.	
-0.90381E 00	0.87597E 00	-0.	-0.	-0.	-0.	
-0.97077E 00	0.10753E 01	-0.	-0.	-0.	-0.	
-0.90624E 00	0.15150E 01	-0.	-0.	-0.	-0.	
-0.56810E 00	0.19134E 01	0.	-0.	0.	-0.	
-0.92368E 00	0.24331E 01	0.	-0.	0.	-0.	
-0.69876E 00	0.27529E 01	-0.	-0.	-0.	-0.	
-0.42273E-00	0.30482E 01	-0.	-0.	-0.	-0.	
0.49574E-01	0.29039E 01	-0.	-0.	-0.	-0.	
0.15715E 01	0.13965E 01	-0.	-0.	-0.	-0.	
0.23187E 01	0.31194E-00	-0.	-0.	-0.	-0.	
0.18653E 01	-0.14333E-00	-0.	0.	-0.	0.	
0.45002E-00	-0.65059E-01	-0.	0.	-0.	0.	
0.75392E-01	0.30583E-01	-0.	0.	-0.	0.	
-0.17C7AE-00	0.13103E-00	-0.	0.	-0.	0.	
-0.36177E-00	0.25075E-00	-0.	-0.	-0.	-0.	
-0.53919E 00	0.45146E-00	0.	-0.	0.	-0.	
-0.70218E 00	0.56544E 00	0.	-0.	0.	-0.	
-0.73011E 00	0.70344E 00	0.	-0.	0.	-0.	
-0.73506E 00	0.79091E 00	0.	-0.	0.	-0.	
-0.66940E 00	0.81309E 00	0.	-0.	0.	-0.	
-0.61489E 00	0.73339E 00	0.	-0.	0.	-0.	
-0.42446E-00	0.42470E-00	0.	-0.	0.	-0.	
-0.41417E-00	0.20201E-00	0.	-0.	0.	-0.	
-0.78708E 00	0.23893E-00	0.	-0.	0.	-0.	
-0.11547E 01	0.45288E-00	0.	-0.	0.	-0.	
-0.17459E 01	0.77002E 00	0.	-0.	0.	-0.	
-0.23213E 01	0.28963E 01	0.	-0.	0.	-0.	
-0.31240E 01	0.46034E 03	0.	-0.	0.	-0.	
-0.87678E 00	0.57242E 01	0.	-0.	0.	-0.	
-0.43960E-00	0.79344E 01	0.	-0.	0.	-0.	
0.77891E 00	0.10005E 02	-0.	-0.	-0.	-0.	
0.27924E 01	0.11310E 02	-0.	-0.	-0.	-0.	
0.49545E 01	0.12024E 02	-0.	-0.	-0.	-0.	
0.12118E 02	0.39513E 01	-0.	-0.	-0.	0.	
0.20749E 02	-0.91543E 01	-0.	0.	-0.	0.	
0.21839E 01	-0.42554E 01	-0.	0.	-0.	0.	
-0.556911 00	-0.18374E-00	0.	-0.	0.	-0.	
0.95789E 00	-0.18467E 01	-0.	0.	-0.	0.	
0.52659E 01	-0.36728E 01	-0.	0.	-0.	0.	
0.31931E 01	-0.34853E 01	-0.	0.	-0.	0.	
0.17466E 01	-0.25987E 01	-0.	0.	-0.	0.	
0.77809E 00	-0.24141E 01	-0.	0.	-0.	0.	
0.72854E-01	-0.21506E 01	-0.	0.	-0.	0.	
-0.13809E-00	-0.20910E 01	-0.	0.	-0.	0.	
-0.16757E-00	-0.23517E 01	-0.	0.	-0.	0.	
-0.19904E-00	-0.25313E 01	-0.	0.	-0.	0.	
-0.34072E-00	-0.23803E 01	-0.	0.	-0.	0.	
-0.13132E 01	-0.18525E 01	0.	0.	0.	0.	
-0.15916E 01	-0.15331E 01	0.	0.	0.	0.	
-0.18658E 01	-0.12681E 01	0.	0.	0.	0.	
-0.24453E 01	-0.87254E 00	0.	0.	0.	0.	
-0.33136E 01	0.10737E 01	0.	-0.	0.	-0.	
-0.51447E 01	0.19715E 01	0.	-0.	0.	-0.	
-0.54273E 01	0.31694E 01	0.	-0.	0.	-0.	
0.54659E 01	0.45877E 01	0.	-0.	0.	-0.	
-0.50013E 01	0.49861E 01	0.	-0.	0.	-0.	
0.14277E 01	0.91832E 00	-0.	-0.	-0.	-0.	
0.13643E 01	0.14376E-00	-0.	-0.	-0.	-0.	
0.84113E 00	-0.1[illegible]E-00	-0.	-0.	-0.	-0.	
0.25734E-00	-0.12172E-00	-0.	-0.	-0.	-0.	
0.61850E-01	-0.54738E-01	-0.	-0.	-0.	-0.	
-0.21216E-01	-0.37764E-01	-0.	-0.	-0.	-0.	
0.12324E-03	-0.62769E-01	-0.	-0.	-0.	-0.	
0.17713E-01	-0.96605E-01	-0.	-0.	-0.	-0.	
0.29369E-02	-0.10807E-00	-0.	0.	-0.	0.	
-0.39261E-01	-0.85250E-01	-0.	0.	-0.	0.	
-0.74680E-01	-0.48464E-01	-0.	-0.	-0.	-0.	
-0.88684E-01	-0.17083E-01	-0.	-0.	-0.	-0.	
-0.75929E-01	-0.72081E-02	-0.	-0.	-0.	-0.	
-0.50305E-01	-0.19938E-01	-0.	0.	-0.	0.	
-0.34450E-03	-0.43249E-01	-0.	0.	-0.	0.	
-0.38823E-01	-0.54482E-01	-0.	0.	-0.	0.	
-0.47129E-01	-0.41010E-01	-0.	0.	-0.	0.	
-0.10530E-00	0.	-0.	0.	-0.	0.	

Table XV --- Concluded

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 20 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

BODY BALANCE STATION: 820 SEGMENT NUMBER 1

		INCREMENTAL AXIAL STRESS REAL	INCREMENTAL AXIAL STRESS IMAGINARY			FREQUENCY CPS
0.	0.	0.140728E 01	0.115029E 03	0.	0.	0.10
0.	0.	0.917918E 02	0.953644E 02	0.	0.	0.20
0.	0.	0.155884E 03	0.134000E 02	0.	0.	0.30
0.	-0.	0.185588E 03	-0.277799E 02	0.	-0.	0.40
0.	-0.	0.179321E 03	-0.615206E 02	0.	-0.	0.50
0.	-0.	0.146771E 03	-0.779938E 02	0.	-0.	0.60
0.	-0.	0.128955E 03	-0.900599E 02	0.	-0.	0.70
0.	-0.	0.118119E 03	-0.102955E 03	0.	-0.	0.80
0.	-0.	0.111944E 03	-0.113949E 03	0.	-0.	0.90
0.	-0.	0.108818E 03	-0.117804E 03	0.	-0.	1.00
0.	-0.	0.105547E 03	-0.272735E 03	0.	-0.	1.10
0.	-0.	0.882046E 02	-0.348355E 03	0.	-0.	1.20
0.	-0.	0.539972E 02	-0.495260E 03	0.	-0.	1.30
-0.	-0.	-0.217846E 02	-0.460136E 03	-0.	-0.	1.40
-0.	-0.	-0.943916E 02	-0.508466E 03	-0.	-0.	1.50
-0.	-0.	-0.202816E 03	-0.390705E 03	-0.	-0.	1.60
-0.	-0.	-0.485056E 03	-0.608106E 02	-0.	-0.	1.70
-0.	0.	-0.538496E 03	0.113266E 03	-0.	0.	1.80
-0.	0.	-0.578616E 03	0.117886E 03	-0.	0.	1.90
-0.	0.	-0.104426E 03	0.821156E 02	-0.	0.	2.00
-0.	0.	-0.465156E 02	0.524196E 02	-0.	0.	2.10
-0.	0.	-0.159216E 02	0.268986E 02	-0.	0.	2.20
0.	0.	0.366126E 01	0.865386E 00	0.	0.	2.30
0.	-0.	0.111336E 02	-0.252986E 02	0.	-0.	2.40
0.	-0.	0.410836E 01	-0.331686E 02	0.	-0.	2.50
0.	-0.	0.336166E 01	-0.519836E 02	0.	-0.	2.60
-0.	-0.	-0.542496E 01	-0.610546E 02	-0.	-0.	2.70
-0.	-0.	-0.216156E 02	-0.620076E 02	-0.	-0.	2.80
-0.	-0.	-0.314406E 02	-0.462086E 02	-0.	-0.	2.90
-0.	-0.	-0.586576E 02	-0.983286E 01	-0.	-0.	3.00
-0.	0.	-0.578636E 02	0.251826E 01	-0.	0.	3.10
-0.	-0.	-0.221236E 02	-0.139846E 02	-0.	-0.	3.20
-0.	-0.	-0.286056E 01	-0.471916E 02	-0.	-0.	3.30
-0.	-0.	-0.474386E 01	-0.638476E 02	-0.	-0.	3.40
-0.	-0.	-0.272246E 02	-0.479296E 01	-0.	-0.	3.50
-0.	-0.	-0.806426E 02	-0.460996E 02	-0.	-0.	3.60
0.	-0.	0.598136E 02	-0.126116E 03	0.	-0.	3.70
0.	-0.	0.601516E 02	-0.235126E 03	0.	-0.	3.80
0.	-0.	0.193066E 02	-0.325616E 03	0.	-0.	3.90
-0.	-0.	-0.569716E 02	-0.380096E 03	-0.	-0.	4.00
-0.	-0.	-0.140216E 03	-0.430356E 03	-0.	-0.	4.10
-0.	-0.	-0.415806E 03	-0.954086E 02	-0.	-0.	4.20
-0.	0.	-0.737836E 03	0.341716E 03	-0.	0.	4.30
0.	0.	0.180196E 02	0.136106E 03	0.	0.	4.40
0.	-0.	0.104626E 03	-0.632866E 02	0.	-0.	4.50
0.	0.	0.133876E 01	0.582396E 02	0.	0.	4.60
-0.	0.	-0.222186E 03	0.154356E 03	-0.	0.	4.70
-0.	0.	-0.122366E 03	0.132796E 03	-0.	0.	4.80
-0	0.	-0.568746E 02	0.130116E 03	-0.	0.	4.90
-0.	0.	-0.101586E 02	0.100906E 03	-0.	0.	5.00
0.	0.	0.248336E 02	0.843786E 02	0.	0.	5.10
0.	0.	0.424326E 02	0.749366E 02	0.	0.	5.20
0.	0.	0.572746E 02	0.447146E 02	0.	0.	5.30
0.	0.	0.679686E 02	0.312466E 02	0.	0.	5.40
0.	0.	0.656456E 02	0.218986E 02	0.	0.	5.50
0.	0.	0.311266E 02	0.341126E 02	0.	0.	5.60
0.	0.	0.304216E 02	0.347856E 02	0.	0.	5.70
0.	0.	0.402726E 02	0.294966E 02	0.	0.	5.80
0.	0.	0.531466E 02	0.211246E 02	0.	0.	5.90
0.	-0.	0.684936E 02	-0.129776E 02	0.	-0.	6.00
0.	-0.	0.984986E 02	-0.279726E 02	0.	-0.	6.10
0.	-0.	0.102976E 03	-0.477866E 02	0.	-0.	6.20
0.	-0.	0.103416E 03	-0.710806E 02	0.	-0.	6.30
0.	-0.	0.956636E 02	-0.777246E 02	0.	-0.	6.40
-0.	-0.	-0.863356E 01	-0.149926E 02	-0.	-0.	6.50
-0.	-0.	-0.107256E 02	-0.510516E 01	-0.	-0.	6.60
0.	-0.	0.121456E-01	-0.479906E 01	0.	-0.	6.70
0.	-0.	0.431636E 01	-0.722236E 01	0.	-0.	6.80
0.	-0.	0.582316E 01	-0.962456E 01	0.	-0.	6.90
0.	-0.	0.457886E-00	-0.853786E 01	0.	-0.	7.00
-0.	-0.	-0.507166E 01	-0.439696E 01	-0.	-0.	7.10
-0.	-0.	-0.898446E 01	-0.123246E-00	-0.	-0.	7.20
-0.	0.	-0.942856E 01	0.263586E 01	-0.	0.	7.30
-0.	0.	-0.748666E 01	0.567236E 01	-0.	0.	7.40
-0.	0.	-0.576886E 01	0.863886E 01	-0.	0.	7.50
-0.	0.	-0.412766E 01	0.279606E 01	-0.	0.	7.60
-0.	0.	-0.323406E 01	0.219576E 01	-0.	0.	7.70
-0.	0.	-0.283656E 01	0.179496E 01	-0.	0.	7.80
-0.	0.	-0.253746E 01	0.130266E 01	-0.	0.	7.90
-0.	0.	-0.210316E 01	0.355636E-00	-0.	0.	8.00
-0.	-0.	-0.177206E 01	-0.107696E 01	-0.	-0.	8.10
-0.	0.	-0.188336E 01	0.	-0.	0.	8.20

Table XVI Stress Frequency Response Functions (Analysis Condition 2)

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 268,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMISPAN 27 SEGMENT NUMBER 10

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				
REAL	IMAGINARY	REAL	IMAGINARY			FREQUENCY CPS
1.306477-00	0.33327E 02	0.610316 00	0.298296 03	0.	-0.	
0.339941E 02	0.21879E 02	0.289466 03	0.190226 03	-0.	-0.	
0.495826 02	0.23387E 01	0.428916 03	0.250256 02	-0.	-0.	
0.53714F 02	-0.78171E 01	0.467046 03	-0.650186 02	-0.	0.	
0.506256 02	-0.16911E 02	0.438996 03	-0.145786 03	-0.	0.	
0.450206 02	-0.22383E 02	0.386346 03	-0.192336 03	-0.	0.	
0.411376 02	-0.26967E 02	0.344866 03	-0.228296 03	-0.	0.	
0.386906 02	-0.31709E 02	0.314856 03	-0.262026 03	-0.	0.	
0.371716 02	-0.37361E 02	0.291376 03	-0.298456 03	-0.	0.	
0.362896 02	-0.53894E 02	0.271326 03	-0.390106 03	-0.	0.	
0.355536 02	-0.74831E 02	0.234336 03	-0.493846 03	0.	-0.	
0.342116 02	-0.88353E 02	0.198406 03	-0.555626 03	0.	-0.	
0.323146 02	-0.10306E 03	0.174196 03	-0.620296 03	0.	-0.	
0.291386 02	-0.11197E 03	0.144776 03	-0.658436 03	0.	-0.	
0.266026 02	-0.12219E 03	0.124956 03	-0.701306 03	0.	-0.	
0.230946 02	-0.14740E 03	0.100126 03	-0.803396 03	0.	-0.	
0.113846 02	-0.18019E 03	0.274346 02	-0.920446 03	0.	-0.	
-0.119646 02	-0.21854E 03	-0.991136 02	-0.105896 04	-0.	-0.	
-0.595436 02	-0.33323E 03	-0.330156 03	-0.110396 03	-0.	-0.	
-0.339276 03	0.13073E 03	-0.137196 04	0.450376 03	-0.	0.	
-0.200676 03	0.13384E 03	-0.693916 03	0.373786 03	-0.	0.	
-0.102786 03	0.11989E 03	-0.306306 03	0.262716 03	-0.	0.	
-0.578296 02	0.10923E 03	-0.152376 03	0.174266 03	-0.	0.	
-0.321226 02	0.99165E 02	-0.841266 02	0.106376 03	-0.	0.	
-0.106036 02	0.90912E 02	-0.644086 02	0.811736 02	-0.	0.	
-0.685246 01	0.88016E 02	-0.388296 02	0.580426 02	0.	0.	
-0.456826 01	0.86493E 02	-0.619916 02	0.533746 02	0.	0.	
-0.346586 01	0.83913E 02	-0.748496 02	0.287176 02	0.	0.	
-0.335336 01	0.854E3E 02	-0.834816 02	0.296836 02	0.	0.	
-0.429736 01	0.88673E 02	-0.112556 03	0.594336 02	0.	0.	
-0.562436 01	0.93866E 02	-0.131996 03	0.977086 02	0.	0.	
-0.161946 01	0.99622E 02	-0.106006 03	0.956986 02	0.	0.	
3.593936 01	0.102326 03	-0.706766 02	0.477476 02	0.	0.	
0.179106 02	0.10426E 03	-0.437916 02	0.488976 02	0.	0.	
0.261146 02	0.10972E 03	-0.382646 02	0.202736 02	0.	0.	
0.436076 02	0.12833E 03	-0.402366 02	-0.185276 02	0.	0.	
0.102826 03	0.13734E 03	-0.711036 02	-0.291136 02	0.	0.	
0.164326 03	0.11662E 03	-0.103476 03	-0.194376 02	0.	0.	
0.288276 03	0.22209E 02	-0.161716 03	0.275546 02	0.	0.	
0.409816 03	-0.10634E 03	-0.212676 03	0.883336 02	0.	-0.	
0.439256 03	-0.36059E 03	-0.228186 03	0.199666 03	0.	-0.	
9.304536-03	-0.30336E 03	-0.137266 03	0.156906 03	0.	-0.	
0.990366 02	-0.31219E 03	-0.198726 02	0.278086 02	0.	-0.	
0.325916 02	-0.29060E 03	-0.291316 02	0.154026 02	0.	-0.	
-0.436596 02	-0.24686E 03	-0.456906 02	0.701466 01	-0.	-0.	
-0.894936 02	-0.15219E 03	-0.612866 02	-0.184276 01	-0.	-0.	
-0.177346 03	-0.69139E 02	-0.106166 03	0.226266 02	-0.	-0.	
-0.131896 03	0.70290E 00	-0.183416 03	0.149406 03	-0.	-0.	
-0.120686 03	0.53387E 02	-0.273806 03	0.444826 03	-0.	-0.	
-0.317576 02	-0.82668E 01	-0.491966 02	0.157926 03	-0.	-0.	
-0.922926 01	-0.17621E 02	0.208346 03	0.632756 02	-0.	-0.	
-0.156726 02	-0.11747E 02	0.179106 03	0.367036 02	-0.	-0.	
-0.187056 02	-0.90481E 01	0.163986 03	0.721926 01	-0.	-0.	
-0.222156 02	-0.82109E 01	0.143426 03	0.112316 01	-0.	-0.	
-0.279006 02	-0.50006E 01	0.138776 03	-0.172316 02	-0.	-0.	
-0.248496 02	-0.11934E 01	0.124346 03	-0.336[illegible] 02	-0.	0.	
-0.264476 02	0.31097E 01	0.111776 03	-0.346956 02	-0.	0.	
-0.283506 02	0.16766E 02	0.978176 02	-0.842536 02	-0.	0.	
-0.296726 02	0.34278E 02	0.814376 02	-0.117316 03	-0.	0.	
-0.224016 02	0.31057E 02	0.506206 02	-0.999446 02	-0.	0.	
0.143086 02	0.24143E 02	-0.233616 02	-0.880076 02	0.	0.	
0.176106 02	0.17432E 02	-0.266336 02	-0.781436 02	0.	0.	
0.180556 02	0.12222E 02	-0.261556 02	-0.711596 02	0.	0.	
0.169036 02	0.84016E 00	-0.216636 02	-0.660446 02	0.	0.	
0.697386 01	-0.11186E-00	-0.145976 02	-0.798766 02	0.	0.	
-0.319616 01	0.33690E 01	-0.477866 02	-0.221486 01	0.	-0.	
-0.628156 01	0.30833E 01	-0.103776 03	0.321766 02	0.	-0.	
-0.548206 01	0.63166E 01	-0.323476 01	0.118666 02	-0.	-0.	
-0.686086 01	0.77709E 01	0.868616 01	-0.106896 01	-0.	0.	
-0.706786 01	0.744886 01	0.827086 01	-0.391696 01	-0.	0.	
0.989846 00	0.369396 01	0.483376 01	-0.378806 01	-0.	0.	
0.387716 01	0.	0.166096 01	0.	0.	0.	

Table XVI – – – Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 268,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.95

PERCENT SEMISPAN: 27 SEGMENT NUMBER 14

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				FREQUENCY
REAL	IMAGINARY	REAL	IMAGINARY			CPS
0.596266E 00	0.305816E 03	0.354822E 00	0.270696E 03	0.	-0.	0.10
0.104988E 03	0.695608E 02	0.262478E 03	0.179888E 03	-0.	-0.	0.20
0.154078 03	0.836508E 01	0.389222E 03	0.234368E 02	-0.	-0.	0.30
0.146838 03	-0.235038E 02	0.423828E 03	-0.590888E 02	-0.	0.	0.40
0.136638 03	-0.515748E 02	0.398378E 03	-0.132298E 03	-0.	0.	0.50
0.137798 03	-0.677348E 02	0.349698E 03	-0.174548E 03	-0.	0.	0.60
0.124078 03	-0.804218E 02	0.312958E 03	-0.207178E 03	-0.	0.	0.70
0.114388 03	-0.926868E 02	0.285728E 03	-0.237788E 03	-0.	0.	0.80
0.107328E 03	-0.106438E 03	0.266628E 03	-0.270848E 03	-0.	0.	0.90
0.101828E 03	-0.143788E 03	0.246218E 03	-0.354868E 03	-0.	0.	1.00
0.930198E 02	-0.198 58E 03	0.222698E 03	-0.448148E 03	0.	-0.	1.10
0.842618E 02	-0.215018E 03	0.180058E 03	-0.584218E 03	0.	-0.	1.20
0.779948E 02	-0.244348E 03	0.158078E 03	-0.562908E 03	0.	-0.	1.30
0.681368E 02	-0.261938E 03	0.131388E 03	-0.597338E 03	0.	-0.	1.40
0.614708E 02	-0.281898E 03	0.113398E 03	-0.636418E 03	0.	-0.	1.50
0.527348E 02	-0.330468E 03	0.988568E 02	-0.729058E 03	0.	-0.	1.60
0.256318E 02	-0.392208E 03	0.248958E 02	-0.842368E 03	0.	-0.	1.70
-0.249588E 02	-0.446168E 03	-0.899448E 02	-0.980958E 03	-0.	-0.	1.80
-0.123068E 03	-0.732328E 02	-0.299608E 03	-0.100178E 03	-0.	-0.	1.90
-0.443388E 03	0.221678 03	-0.125508E 04	0.408708E 03	-0.	0.	2.00
-0.357818E 03	0.210.8E 03	-0.629718E 03	0.339198E 03	-0.	0.	2.10
-0.177838 03	0.172968 03	-0.277968E 03	0.238408E 03	-0.	0.	2.20
-0.925108E 02	0.142318E 03	-0.138448E 03	0.158148E 03	-0.	0.	2.30
-0.508648E 02	0.115718E 03	-0.763428E 02	0.947108E 02	-0.	0.	2.40
-0.262988E 02	0.103428E 03	-0.381588E 02	0.736638E 02	-0.	0.	2.50
-0.214468E 02	0.927118E 02	-0.323868E 02	0.656128E 02	0.	0.	2.60
-0.198838E 02	0.868058E 02	-0.342568E 02	0.304688E 02	0.	0.	2.70
-0.227338E 02	0.849808E 02	-0.680158E 02	0.260668E 02	0.	0.	2.80
-0.242928E 02	0.854278E 02	-0.757578E 02	0.269398E 02	0.	0.	2.90
-0.355058E 02	0.989488E 02	-0.102148E 03	0.339368E 02	0.	0.	2.97
-0.432838E 02	0.119858E 03	-0.119788E 03	0.888688E 02	0.	0.	3.00
-0.311388E 02	0.124448E 03	-0.961948E 02	0.868448E 02	0.	0.	3.10
-0.118478E 02	0.123188E 03	-0.441378E 02	0.614798E 02	0.	0.	3.20
0.999988E 01	0.117278E 03	-0.397418E 02	0.446738E 02	0.	0.	3.30
0.211788E 02	0.115378E 03	-0.367238E 02	0.383978E 02	0.	0.	3.40
0.410738E 02	0.122248E 03	-0.365138E 02	0.368138E 02	0.	0.	3.50
0.018868 03	0.124938 03	-0.645248E 02	0.264198E 02	0.	0.	3.60
0.165318 03	0.968518E 02	-0.938978E 02	0.176388E 02	0.	0.	3.70
0.294678 03	-0.127298E 02	-0.146748E 03	0.258858E 02	0.	0.	3.80
0.422268 03	-0.158378E 03	-0.192998E 03	0.881628E 02	0.	-0.	3.86
0.471808E 03	-0.446848E 03	-0.207078E 03	0.181198 03	0.	-0.	3.90
0.286108E 03	-0.386008E 03	-0.124368E 03	0.142388 03	0.	-0.	3.96
0.326868E 02	-0.314848E 03	-0.180348E 02	0.252338E 02	0.	-0.	3.99
-0.967528E 02	-0.284918E 03	-0.264368E 02	0.139778E 02	0.	-0.	4.00
-0.117598E 03	-0.243328E 03	-0.414638E 02	0.436568E 01	-0.	-0.	4.04
-0.156868E 03	-0.150948E 03	-0.556168E 02	-0.167228E 01	-0.	-0.	4.10
-0.195508E 03	-0.449748E 02	-0.945088E 02	0.205338E 02	-0.	-0.	4.20
-0.229908E 03	0.627218E 02	-0.166448E 03	0.135588E 03	-0.	-0.	4.30
-0.258898E 03	0.230358E 03	-0.248678E 03	0.403468E 03	-0.	-0.	4.40
-0.577538E 02	0.576548E 02	-0.446648E 02	0.163318E 03	-0.	-0.	4.50
0.717508E 02	0.158378E 02	0.189248E 03	0.597628E 02	-0.	-0.	4.60
0.953428E 02	0.579638E 01	0.162538E 03	0.333828E 02	-0.	-0.	4.70
0.477738E 02	-0.440068E 01	0.148818E 03	0.633138E 01	-0.	-0.	4.80
0.186498E 02	-0.440148E 01	0.130158E 03	0.102108E 01	-0.	-0.	4.90
0.367848E 02	-0.123478E 02	0.125938E 03	-0.136558E 02	-0.	-0.	5.00
0.313338E 02	-0.178468E 02	0.112848E 03	-0.303178E 02	-0.	0.	5.10
0.270368E 02	-0.257418E 02	0.101438E 03	-0.496338E 02	-0.	0.	5.20
0.224878E 02	-0.381368E 02	0.887678E 02	-0.764598E 02	-0.	0.	5.30
0.161888E 02	-0.519768E 02	0.739028E 02	-0.106638E 03	-0.	0.	5.40
0.376208E 01	-0.628728E 02	0.449368E 02	-0.906978E 02	-0	0.	5.50
-0.271118E 01	-0.381428E 02	-0.212008E 01	-0.798648E 02	0.	0.	5.60
-0.278318E 02	-0.345528E 02	-0.261698E 02	-0.709138E 02	0.	0.	5.70
-0.271068E 02	-0.323588E 02	-0.237358E 02	-0.663738E 02	0.	0.	5.80
-0.267308E 02	-0.344078E 02	-0.217648E 02	-0.599338E 02	0.	0.	5.90
-0.279518E 02	-0.459498E 02	-0.132448E 02	-0.724868E 02	0.	0.	6.00
-0.497138E 02	0.120478E 02	-0.433648E 02	-0.200988E 01	0.	-0.	6.10
-0.925918E 02	0.411228E 02	-0.941718E 02	0.291998E 02	0.	-0.	6.20
-0.136508E 02	0.259018E 02	-0.295348E 01	0.107688E 02	-0.	-0.	6.30
0.614398E 00	0.139238E 02	0.878998E 01	-0.970008E 00	-0.	0.	7.00
0.487158E 01	0.744018E 01	0.750558E 01	-0.353458E 01	-0.	0.	8.00
0.818728E 01	0.270628E 01	0.438658E 01	-0.363828E 01	-0.	0.	9.00
0.790278E 01	0.	0.198728E 01	0.	0.	0.	10.00

Table XVI --- Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 268,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.8

PERCENT SEMISPAN: 40.06 SEGMENT NUMBER 8

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				
REAL	IMAGINARY	REAL	IMAGINARY			
0.25514E-00	0.66628E 02	-0.24416E-01	0.27159E 03	0.	0.	
0.67833E 02	0.45532E 02	0.26127E 03	0.10101E 03	0.	0.	
0.99953E 02	0.58171E 01	0.38903E 03	0.23330E 02	0.	0.	
0.10877E 03	-0.15047E 02	0.42488E 03	-0.68332E 02	0.	-0.	
0.10256E 03	-0.33733E 02	0.39921E 03	-0.13492E 03	0.	-0.	
0.90993E 02	-0.44660E 02	0.35073E 03	-0.17844E 03	0.	-0.	
0.92594E 02	-0.53954E 02	0.31326E 03	-0.21214E 03	0.	-0.	
0.76193E 02	-0.63673E 02	0.28500E 03	-0.24344E 03	0.	-0.	
0.72918E 02	-0.73601E 02	0.26243E 03	-0.27747E 03	0.	-0.	
0.69965E 02	-0.10300E 03	0.24258E 03	-0.36223E 03	0.	-0.	
0.65407E 02	-0.13863E 03	0.20463E 03	-0.45503E 03	0.	-0.	
0.59459E 02	-0.16104E 03	0.16740E 03	-0.51033E 03	0.	-0.	
0.54861E 02	-0.18510E 03	0.14203E 03	-0.56791E 03	0.	-0.	
0.47754E 02	-0.19955E 03	0.11356E 03	-0.60174E 03	0.	-0.	
0.42506E 02	-0.21598E 03	0.94103E 02	-0.63960E 03	0.	-0.	
0.35561E 02	-0.25600E 03	0.69973E 02	-0.72923E 03	0.	-0.	
0.13627E 02	-0.30693E 03	0.39709E-00	-0.83756E 03	0.	-0.	
-0.27767E 02	-0.36420E 03	-0.31847E 03	-0.94701E 03	-0.	-0.	
-0.10856E 03	-0.41617E 02	-0.33154E 03	-0.37372E 02	-0.	-0.	
-0.53774E 03	0.20257E 03	-0.12366E 04	0.42220E 03	-0.	0.	
-0.29973E 03	0.19305E 03	-0.60791E 03	0.32870E 03	-0.	0.	
-0.14539E 03	0.16062E 03	-0.26348E 03	0.23199E 03	-0.	0.	
-0.78111E 02	0.13232E 03	-0.13106E 03	0.14432E 03	-0.	0.	
-0.44430E 02	0.11204E 03	-0.76822E 02	0.87647E 02	-0.	0.	
-0.39047E 02	0.11852E 03	-0.86203E 02	0.92763E 02	-0.	0.	
-0.30166E 02	0.11201E 03	-0.75352E 02	0.69486E 02	-0.	0.	
-0.18179E 02	0.10699E 03	-0.63436E 02	0.53440E 02	-0.	0.	
-0.15431E 02	0.10509E 03	-0.67709E 02	0.50974E 02	-0.	0.	
-0.15197E 02	0.10248E 03	-0.71829E 02	0.47999E 02	0.	0.	
-0.16899E 02	0.10560E 03	-0.87142E 02	0.62213E 02	0.	0.	
-0.18488E 02	0.11238E 03	-0.96842E 02	0.79548E 02	0.	0.	
-0.12326E 02	0.11298E 03	-0.80160E 02	0.73594E 02	0.	0.	
-0.26409E 01	0.10892E 03	-0.59034E 02	0.51141E 02	0.	0.	
0.62304E 01	0.10609E 03	-0.46233E 02	0.36934E 02	0.	0.	
0.15461E 02	0.10258E 03	-0.46202E 02	0.16323E 02	0.	0.	
0.25469E 02	0.10247E 03	-0.33964E 02	-0.49968E 01	0.	0.	
0.45097E 02	0.10616E 03	-0.92988E 02	-0.22626E 01	0.	0.	
0.56654E 02	0.11452E 03	-0.13006E 03	0.32477E 02	0.	0.	
0.69941E 02	0.12727E 03	-0.19510E 03	0.11381E 03	0.	0.	
0.78267E 02	0.14287E 03	-0.24786E 03	0.20577E 03	0.	0.	
0.85546E 02	0.16599E 03	-0.23412E 03	0.36971E 03	0.	0.	
0.13359E 03	0.18429E 03	-0.90160E 02	0.30049E 03	0.	0.	
0.23602E 03	-0.88743E 02	0.12732E 03	-0.59766E 02	0.	-0.	
0.26845E 03	-0.10154E 03	0.13236E 03	-0.63403E 02	0.	-0.	
0.19899E 03	-0.67747E 02	0.34535E 02	-0.83552E 02	0.	-0.	
0.16050E 03	-0.53533E 02	0.70814E 00	-0.39541E 02	0.	-0.	
0.14089E 03	-0.61555E 02	-0.78477E 02	-0.86823E 01	0.	-0.	
0.17677E 03	-0.15939E 03	-0.15973E 03	0.11728E 03	0.	0.	
0.22665E 03	-0.36710E 03	-0.22214E 03	0.34063E 03	0.	0.	
0.21434E 02	-0.12274E 03	-0.16088E 02	0.87302E 02	0.	-0.	
-0.16377E 03	-0.51119E 02	0.14932E 03	0.22172E 02	-0.	-0.	
-0.13721E 03	-0.31644E 02	0.10722E 03	0.22489E 01	-0.	-0.	
-0.12490E 03	-0.10388E 02	0.88297E 02	-0.52309E 01	-0.	-0.	
-0.10870E 03	-0.60998E 01	0.62197E 02	-0.68999E 01	-0.	-0.	
-0.10511E 03	0.65244E 01	0.56401E 02	-0.89379E 01	-0.	0.	
-0.94080E 02	0.12218E 02	0.52199E 02	-0.34680E 01	-0.	0.	
-0.84688E 02	0.29945E 02	0.19536E 02	0.86046E 01	-0.	0.	
-0.74715E 02	0.46288E 02	-0.24234E 00	0.43012E 02	-0.	0.	
-0.64591E 02	0.64364E 02	-0.13830E 02	0.10220E 03	-0.	0.	
-0.44629E 02	0.58020E 02	0.41215E 01	0.86317E 02	-0.	0.	
-0.93065E 01	0.52013E 02	0.11946E 03	0.66528E 02	-0.	0.	
-0.70227E 01	0.46886E 02	0.12642E 03	0.46786E 02	-0.	0.	
-0.67294E 01	0.43109E 02	0.12598E 03	0.31176E 02	-0.	0.	
-0.75866E 01	0.39121E 02	0.12082E 03	0.63733E 01	-0.	0.	
-0.11821E 02	0.44924E 02	0.89145E 02	0.21189E 02	-0.	0.	
0.60610E 00	0.12556E 02	0.91883E 02	-0.64859E 02	0.	0.	
0.27794E 02	0.68152E 01	0.14063E 03	-0.85430E 02	0.	0.	
-0.99091E 01	0.14962E 02	0.23288E 02	-0.58602E 02	-0.	0.	
-0.10278E 02	0.19010E 02	-0.66289E 01	-0.28218E 02	-0.	0.	
-0.19616E 01	0.16923E 02	-0.23609E 02	-0.79133E 01	-0.	0.	
0.60764E 01	0.10529E 02	-0.26913E 02	0.63897E 01	0.	0.	
0.12184E 02	0.	-0.17164E 02	0.	0.	0.	

Table XVI --- Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 260,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMI SPAN: 40.06 SEGMENT NUMBER 107

INCREMENTAL SHEAR STRESS				INCREMENTAL AXIAL STRESS		
REAL	IMAGINARY			REAL	IMAGINARY	FREQUENCY CPS
0.290111E-00	0.675035E 02	0.	0.	0.290620E 01	-0.232802E 03	0.00
0.666546E 02	0.446235E 02	0.	0.	-0.223226E 03	-0.154666E 03	0.20
0.990047E 02	0.576011E 01	0.	0.	-0.532460E 03	-0.208105E 02	0.36
0.106559E 03	-0.145089E 02	0.	-0.	-0.363030E 03	0.512994E 02	0.44
0.100460E 03	-0.327259E 02	0.	-0.	-0.561535E 03	0.115208E 03	0.50
0.889409E 02	-0.434469E 02	0.	-0.	-0.299868E 03	0.152466E 03	0.60
0.807644E 02	-0.521644E 02	0.	-0.	-0.267644E 03	0.181268E 03	0.70
0.751066E 02	-0.608000E 02	0.	-0.	-0.249352E 03	0.208199E 03	0.80
0.713117E 02	-0.709932E 02	0.	-0.	-0.224218E 03	0.237107E 03	0.90
0.684993E 02	-0.998010E 02	0.	-0.	-0.207278E 03	0.309952E 03	1.00
0.642118E 02	-0.133888E 03	0.	-0.	-0.174884E 03	0.388779E 03	1.20
0.591158E 02	-0.156451E 03	0.	-0.	-0.143038E 03	0.436804E 03	1.34
0.544882E 02	-0.177536E 03	0.	-0.	-0.122046E 03	0.489524E 03	1.40
0.478851E 02	-0.191137E 03	0.	-0.	-0.970827E 02	0.514158E 03	1.49
0.429366E 02	-0.207106E 03	0.	-0.	-0.800404E 02	0.546649E 03	1.47
0.364111E 02	-0.245466E 03	0.	-0.	-0.597078E 02	0.623807E 03	1.50
0.157330E 02	-0.294137E 03	0.	-0.	-0.339928E-00	0.715466E 03	1.59
-0.234688E 02	-0.349957E 03	-0.	-0.	0.101238E 03	0.809195E 03	1.60
-0.100188E 03	-0.445532E 02	-0.	-0.	0.283208E 03	0.490208E 02	1.65
-0.511858E 03	0.189992E 03	-0.	0.	0.105466E 04	-0.360746E 03	1.80
-0.286218E 03	0.181646E 03	-0.	0.	0.919426E 03	-0.289396E 03	1.90
-0.139818E 03	0.150886E 03	-0.	0.	0.225126E 03	-0.198222E 03	2.00
-0.743826E 02	0.123756E 03	-0.	0.	0.111986E 03	-0.125196E 03	2.10
-0.427644E 02	0.103796E 03	-0.	0.	0.656396E 02	-0.748086E 02	2.20
-0.347456E 02	0.109286E 03	-0.	0.	0.736546E 02	-0.792596E 02	2.30
-0.286506E 02	0.102486E 03	-0.	0.	0.643876E 02	-0.593716E 02	2.35
-0.179936E 02	0.973506E 02	-0.	0.	0.542026E 02	-0.473696E 02	2.40
-0.161906E 02	0.955206E 02	-0.	0.	0.570536E 02	-0.435946E 02	2.45
-0.164416E 02	0.935006E 02	-0.	0.	0.613736E 02	-0.410116E 02	2.44
-0.196156E 02	0.980216E 02	-0.	0.	0.744576E 02	-0.551576E 02	2.47
-0.224166E 02	0.107236E 03	-0.	0.	0.827446E 02	-0.679686E 02	2.50
-0.152366E 02	0.108256E 03	-0.	0.	0.684916E 02	-0.620616E 02	2.54
-0.428796E 01	0.103756E 03	-0.	0.	0.511416E 02	-0.456976E 02	2.58
0.848416E 01	0.100566E 03	-0.	0.	0.389476E 02	-0.515586E 02	2.65
0.148656E 02	0.983936E 02	-0.	0.	0.394766E 02	-0.139476E 02	2.70
0.247666E 02	0.945706E 02	-0.	0.	0.461086E 02	0.426946E 01	2.80
0.438826E 02	0.960876E 02	-0.	0.	0.794526E 02	0.109306E 01	3.00
0.538496E 02	0.103256E 03	-0.	0.	0.111136E 03	-0.277496E 02	3.10
0.650156E 02	0.114496E 03	-0.	0.	0.166706E 03	-0.965586E 02	3.20
0.709766E 02	0.129126E 03	-0.	0.	0.211706E 03	-0.175826E 03	3.26
0.781926E 02	0.171716E 03	-0.	0.	0.217136E 03	-0.315096E 03	3.29
0.119406E 03	0.171096E 03	-0.	0.	0.770366E 02	-0.260546E 03	3.35
0.214556E 03	-0.749916E 02	-0.	-0.	-0.108036E 03	0.510656E 02	3.40
0.245926E 03	-0.866326E 02	-0.	-0.	-0.113096E 03	0.729716E 02	3.52
0.186706E 03	-0.747716E 02	-0.	-0.	-0.466146E 02	0.713096E 02	3.56
0.151196E 03	-0.477356E 02	-0.	-0.	-0.603066E 00	0.508746E 02	3.60
0.135866E 03	-0.570726E 02	-0.	-0.	0.670536E 02	0.741866E 01	3.72
0.170616E 03	-0.352746E 03	-0.	-0.	0.136406E 02	-0.100216E 03	3.85
0.215986E 03	-0.347416E 03	-0.	-0.	0.194076E 03	-0.291056E 03	4.00
0.168036E 02	-0.112636E 03	-0.	-0.	0.137466E 02	-0.745936E 02	4.20
-0.154126E 03	-0.458296E 02	-0.	-0.	-0.127596E 03	-0.189456E 02	4.50
-0.127046E 03	-0.280046E 02	-0.	-0.	-0.916156E 02	-0.619376E 01	4.70
-0.116726E 03	-0.895116E 01	-0.	-0.	-0.754436E 02	0.446946E 01	4.80
-0.985136E 02	-0.519696E 01	-0.	-0.	-0.533146E 02	0.589556E 01	4.96
-0.944056E 02	0.557116E 01	0.	0.	-0.481916E 02	0.763686E 01	5.00
-0.817966E 02	0.161666E 02	0.	0.	-0.317646E 02	0.467216E 01	5.15
-0.742636E 02	0.234036E 02	-0.	0.	-0.166926E 02	-0.735206E 01	5.30
-0.660946E 02	0.335056E 02	-0.	0.	0.634236E 00	-0.384606E 02	5.47
-0.564956E 02	0.412566E 02	-0.	0.	0.135256E 02	-0.873956E 02	5.70
-0.435416E 02	0.460466E 02	-0.	0.	-0.351166E 01	-0.754616E 02	5.89
-0.217406E 02	0.371426E 02	-0.	0.	-0.102076E 03	-0.568446E 02	6.00
-0.203706E 02	0.347206E 02	-0.	0.	-0.108016E 03	-0.999766E 02	6.03
-0.199756E 02	0.329946E 02	-0.	0.	-0.107646E 03	-0.266376E 02	6.06
-0.201276E 02	0.318416E 02	-0.	0.	-0.103236E 03	-0.564576E 01	6.08
-0.207036E 02	0.344106E 02	-0.	0.	-0.761686E 02	-0.101056E 02	6.20
-0.118666E 02	0.208856E 02	-0.	0.	-0.765086E 02	0.383296E 02	6.40
0.669206E 00	0.168076E 02	0.	0.	-0.120146E 03	0.729946E 02	6.60
-0.121016E 02	0.706236E 02	-0.	0.	-0.198986E 02	0.500716E 02	7.00
-0.879336E 01	0.209006E 02	-0.	0.	0.570676E 01	0.241116E 02	7.40
0.514276E 00	0.170716E 02	-0.	0.	0.201726E 02	0.676316E 01	8.20
0.918716E 01	0.977596E 01	0.	0.	0.212086E 02	-0.539056E 01	9.00
0.133276E 02	0.	0.	0.	0.146656E 02	0.	10.00

Table XVI --- Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 268,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

BODY BALANCE STATION: 540 SEGMENT NUMBER 17

INCREMENTAL SHEAR STRESS REAL	INCREMENTAL SHEAR STRESS IMAGINARY					FREQUENCY CPS
-0.499023E-01	-0.[illegible]E 01	0.	-0.	0.	-0.	
-0.172756 01	-0.66[illegible]E 00	0.	-0.	0.	-0.	
-0.228437E 01	0.[illegible]195E-00	0.	-0.	0.	-0.	
-0.225148E 01	0.551716 00	0.	-0.	0.	-0.	
-0.700588E 01	0.812406 00	0.	-0.	0.	-0.	
-0.146467E 01	0.921396 00	0.	-0.	0.	-0.	
-0.146596 01	0.990046 00	0.	-0.	0.	-0.	
-0.130686 01	0.105426 01	0.	-0.	0.	-0.	
-0.121926 01	0.113216 01	0.	-0.	0.	-0.	
-0.114636 01	0.117856 01	0.	-0.	0.	-0.	
-0.113126 01	0.170556 01	0.	-0.	0.	-0.	
-0.112996 01	0.191746 01	0.	-0.	0.	-0.	
-0.111936 01	0.214776 01	0.	-0.	0.	-0.	
-0.109256 01	0.228726 01	0.	-0.	0.	-0.	
-0.106756 01	0.244696 01	0.	-0.	0.	-0.	
-0.103016 01	0.284126 01	0.	-0.	0.	-0.	
-0.893396 00	0.335766 01	0.	-0.	0.	-0.	
-0.598136 00	0.397906 01	-0.	-0.	-0.	-0.	
0.378736-01	0.189846 01	-0.	-0.	-0.	-0.	
0.416816 01	-0.668336 00	-0.	0.	-0.	0.	
0.730396 01	-0.665736 00	-0.	0.	-0.	0.	
0.482776 00	-0.330286-00	-0.	0.	-0.	0.	
0.705866-00	0.485036-01	-0.	0.	-0.	0.	
-0.166776-00	0.472886-00	-0.	0.	-0.	0.	
-0.278066-00	0.606526 00	-0.	0.	-0.	0.	
-0.305566-00	0.859976 00	-0.	0.	-0.	0.	
-0.292956-00	0.101676 01	-0.	0.	-0.	0.	
-0.175046-00	0.106546 01	-0.	0.	-0.	0.	
-0.918346-01	0.105376 01	-0.	0.	-0.	0.	
0.297466-00	0.743176 00	-0.	0.	-0.	0.	
0.422416-00	0.306146-00	-0.	0.	-0.	0.	
0.136486-00	0.316686-00	-0.	0.	-0.	0.	
-0.793766-00	0.876776 00	-0.	0.	-0.	0.	
-0.701516 00	0.975656 00	0.	-0.	0.	-0.	
-0.856766 00	0.159056 01	0.	-0.	0.	-0.	
-0.102206 01	0.931996 01	0.	-0.	0.	-0.	
-0.107036 01	0.474666 01	0.	-0.	0.	-0.	
-0.889596 00	0.719726 01	0.	-0.	0.	-0.	
-0.386196-00	0.100336 02	-0.	-0.	-0.	-0.	
0.477386-00	0.126186 02	-0.	-0.	-0.	-0.	
0.183626 01	0.174336 02	-0.	-0.	-0.	-0.	
0.913566 01	0.157306 02	-0.	-0.	-0.	-0.	
0.213506 02	-0.202886 02	-0.	0.	-0.	0.	
0.217506 02	-0.217966 02	-0.	0.	-0.	0.	
0.110866 02	-0.195596 02	-0.	0.	-0.	0.	
0.438366 01	-0.133346 02	-0.	0.	-0.	0.	
-0.273746 01	-0.765976 01	0.	0.	0.	0.	
-0.641506 01	-0.197426 01	0.	0.	0.	0.	
-0.852016 01	0.599066 01	0.	-0.	0.	-0.	
-0.246096 01	0.167956-01	0.	-0.	0.	-0.	
0.749866 01	-0.138466 01	-0.	0.	-0.	0.	
0.143296 01	-0.164896 01	-0.	0.	-0.	0.	
0.945026 00	-0.181276 01	-0.	0.	-0.	0.	
0.259936-00	-0.182126 01	-0.	0.	-0.	0.	
0.953856-01	-0.176746 01	-0.	0.	-0.	0.	
-0.446746-00	-0.157606 01	-0.	0.	-0.	0.	
-0.105026 01	-0.974636 00	0.	0.	0.	0.	
-0.190826 01	0.805946 00	0.	-0.	0.	-0.	
-0.288206 01	0.429056 01	0.	-0.	0.	-0.	
-0.709266 01	0.384556 01	0.	-0.	0.	-0.	
0.573276 01	0.225946 01	-0.	-0.	-0.	-0.	
0.661816 01	0.899496 00	-0.	-0.	-0.	-0.	
0.656756 01	-0.861356 00	-0.	0.	-0.	0.	
0.491506 01	-0.408206 01	-0.	0.	-0.	0.	
0.361676 01	-0.537176 01	-0.	0.	-0.	0.	
-0.139546 01	-0.491066-00	0.	0.	0.	0.	
-0.520766 01	0.136816 01	0.	-0.	0.	-0.	
-0.194956-00	0.463976-00	-0.	-0.	-0.	-0.	
0.248976-00	0.117156-01	-0.	-0.	-0.	-0.	
0.172976-00	-0.853476-01	-0.	-0.	-0.	-0.	
0.962206-01	-0.119906-00	-0.	-0.	-0.	-0.	
0.874726-01	0.	-0.	0.	-0.	0.	

Table XVI ---Concluded

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 268,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

BODY BALANCE STATION 820 SEGMENT NUMBER 1

		INCREMENTAL AXIAL STRESS				FREQUENCY
		REAL	IMAGINARY			CPS
0.	0.	0.198618 01	0.122028 03	0.	0.	0.10
0.	0.	0.155708 05	0.744338 02	0.	0.	0.20
0.	0.	0.191198 05	0.125758-00	0.	0.	0.30
0.	-0.	0.199998 03	-0.365058 02	0.	-0.	0.40
0.	-0.	0.184268 05	-0.466178 02	0.	-0.	0.50
0.	-0.	0.158748 03	-0.024778 02	0.	-0.	0.60
0.	-0.	0.140908 05	-0.944708 02	0.	-0.	0.70
0.	-0.	0.128548 05	-0.105798 03	0.	-0.	0.80
0.	-0.	0.119628 03	-0.118338 03	0.	-0.	0.90
0.	-0.	0.111718 03	-0.131508 03	0.	-0.	1.00
0.	-0.	0.101768 03	-0.189528 03	0.	-0.	1.20
0.	-0.	0.917578 02	-0.212478 03	0.	-0.	1.30
0.	-0.	0.846508 02	-0.236528 03	0.	-0.	1.40
0.	-0.	[illegible]532E 02	-0.259718 03	0.	-0.	1.50
0.	-0.	[illegible].79E 02	-0.284668 03	0.	-0.	1.60
0.	-0.	0.614058 02	-0.304718 03	0.	-0.	1.70
0.	-0.	0.374668 02	-0.351628 03	0.	-0.	1.80
-0.	-0.	-0.534218 01	-0.401678 03	-0.	-0.	1.90
-0.	-0.	-0.051728 02	-0.407838 02	-0.	-0.	1.95
-0.	0.	-0.441698 03	0.128208 03	-0.	0.	1.80
-0.	0.	-0.224748 05	0.906148 02	-0.	0.	1.90
-0.	0.	-0.844718 02	0.446768 02	-0.	0.	2.00
-0.	0.	-0.277088 02	0.254948 01	-0.	0.	2.10
-0.	-0.	-0.256558 01	-0.349048 02	-0.	-0.	2.20
-0.	-0.	-0.485408 01	-0.432568 02	-0.	-0.	2.30
-0.	-0.	-0.584078 01	-0.638658 02	-0.	-0.	2.35
-0.	-0.	-0.680588 01	-0.757358 02	-0.	-0.	2.40
-0.	-0.	-0.175998 02	-0.792368 02	-0.	-0.	2.45
-0.	-0.	-0.245948 02	-0.778008 02	-0.	-0.	2.44
-0.	-0.	-0.482288 02	-0.940008 02	-0.	-0.	2.47
-0.	-0.	-0.641058 02	-0.242238 02	-0.	-0.	2.50
-0.	-0.	-0.457548 02	-0.273808 02	-0.	-0.	2.54
-0.	-0.	-0.158118 02	-0.544658 02	-0.	-0.	2.58
0.	-0.	0.527878 01	-0.753168 02	0.	-0.	2.65
0.	-0.	0.952548 01	-0.116498 03	0.	-0.	2.77
0.	-0.	0.594998 01	-0.209228 03	0.	-0.	2.80
-0.	-0.	-0.356648 02	-0.275148 03	-0.	-0.	3.00
-0.	-0.	-0.878058 02	-0.358468 03	-0.	-0.	3.10
-0.	-0.	-0.194458 05	-0.468548 03	-0.	-0.	3.20
-0.	-0.	-0.518648 03	-0.419058 03	-0.	-0.	3.26
-0.	-0.	-0.395978 03	-0.438688 03	-0.	-0.	3.29
-0.	-0.	-0.573648 05	-0.413308 03	-0.	-0.	3.30
-0.	0.	-0.910308 03	0.965838 03	-0.	0.	3.40
-0.	0.	-0.888108 03	0.100348 04	-0.	0.	3.50
-0.	0.	-0.455108 03	0.880948 03	-0.	0.	3.56
-0.	0.	-0.155348 03	0.588648 03	-0.	0.	3.60
0.	0.	0.120508 03	0.334508 03	0.	0.	3.70
0.	0.	0.222168 03	0.142108 03	0.	0.	3.80
0.	-0.	0.244928 03	-0.246098 02	0.	-0.	4.00
0.	0.	0.800818 02	0.834638 02	0.	0.	4.20
0.	0.	0.235528 02	0.843148 02	0.	0.	4.30
0.	0.	0.542398 02	0.777818 02	0.	0.	4.40
0.	0.	0.658698 02	0.638418 02	0.	0.	4.50
0.	0.	0.[illegible]000E 02	0.597918 02	0.	0.	4.56
0.	0.	0.845538 02	0.439718 02	0.	0.	5.00
0.	0.	0.[illegible]579E 02	0.243608 02	0.	0.	5.15
0.	-0.	0.106938 01	-0.109868 02	0.	-0.	5.30
0.	-0.	0.1[illegible]75E 03	-0.027698 02	0.	-0.	[illegible]
0.	-0.	0.11[illegible]19E 05	-0.195808 03	0.	-0.	[illegible]
0.	-0.	0.927458 02	-0.173318 03	0.	-0.	[illegible]
-0.	-0.	-0.149648 03	-0.127458 03	-0.	-0.	6.00
-0.	-0.	-0.167868 03	-0.842408 02	-0.	-0.	6.05
-0.	-0.	-0.170078 03	-0.482878 02	-0.	-0.	6.08
-0.	0.	-0.161928 03	0.274338 02	-0.	0.	6.08
-0.	0.	-0.938568 02	0.337728 02	-0.	0.	6.20
-0.	0.	-0.250558 02	0.155258 02	-0.	0.	6.40
-0.	0.	-0.990058 01	0.162318 02	-0.	0.	6.60
0.	0.	0.220138 01	0.798788 01	0.	0.	7.00
0.	-0.	0.956128 01	-0.388498 01	0.	-0.	7.40
0.	-0.	0.889148 01	-0.887798 01	0.	-0.	8.00
0.	-0.	0.256798 01	-0.844228 01	0.	-0.	9.00
-0.	0.	-0.467708 01	0.	-0.	0.	10.00

Table XVII Stress Frequency Response Functions (Analysis Condition 3)

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT. 390,590 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMISPAN: 27 SEGMENT NUMBER 10

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				
REAL	IMAGINARY	REAL	IMAGINARY			
0.144A8E 01	0.16311E 02	0.19029E 02	0.19340E 03	-0.	-0.	
0.23312E 02	0.10499E 02	0.26795E 03	0.12602E 03	-0.	-0.	
0.29478E 02	0.18436E 01	0.33885E 03	0.24623E 02	-0.	-0.	
0.32310E 02	-0.35651E 01	0.36973E 03	-0.38487E 02	-0.	0.	
0.31996E 02	-0.96094E 01	0.34179E 03	-0.10708E 03	-0.	0.	
0.30627E 02	-0.13961E 02	0.33581E 03	-0.15287E 03	-0.	0.	
0.29086E 02	-0.17861E 02	0.31032E 03	-0.18951E 03	-0.	0.	
0.28241E 02	-0.21951E 02	0.28852E 03	-0.22319E 03	-0.	0.	
0.27851E 02	-0.26813E 02	0.26987E 03	-0.25[illegible]3E 03	-0.	0.	
0.27835E 02	-0.41892E 02	0.25298E 03	-0.36250E 03	-0.	0.	
0.28668E 02	-0.58514E 02	0.22065E 03	-0.43191E 03	-0.	0.	
0.28343E 02	-0.69752E 02	0.19955E 03	-0.48371E 03	-0.	-0.	
0.27376E 02	-0.81903E 02	0.17022E 03	-0.53764E 03	0.	-0.	
0.25354E 02	-0.89239E 02	0.14689E 03	-0.56922E 03	0.	-0.	
0.23650E 02	-0.97617E 02	0.13161E 03	-0.60452E 03	0.	-0.	
0.21347E 02	-0.11825E 03	0.11270E 03	-0.68844E 03	0.	-0.	
0.19389E 02	-0.14534E 03	0.58705E 02	-0.79270E 03	0.	-0.	
-0.25248E 01	-0.17904E 03	-0.32451E 02	-0.91156E 03	-0.	-0.	
-0.34974E 02	-0.85746E 02	-0.19561E 03	-0.35480E 03	-0.	-0.	
-0.30621E 03	0.11509E 03	-0.12468E 04	0.37398E 03	-0.	-0.	
-0.21299E 03	0.13190E 03	-0.73854E 03	0.34806E 03	-0.	0.	
-0.10779E 03	0.11983E 03	-0.32130E 33	0.26510E 03	-0.	0.	
-0.59644E 02	0.10928E 03	-0.15685E 03	0.16000E 03	-0.	0.	
-0.32394E 02	0.98963E 02	-0.85435E 02	0.92564E 02	-0.	0.	
-0.10713E 02	0.90871E 02	-0.64132E 02	0.70562E 02	-0.	0.	
-0.66259E 01	0.87532E 02	-0.58481E 02	0.60768E 02	0.	0.	
-0.40946E 01	0.85662E 02	-0.60136E 02	0.26295E 02	0.	0.	
-0.30239E 01	0.84923E 02	-0.71197E 02	0.18922E 02	0.	0.	
-0.29662E 01	0.84024E 02	-0.78696E 02	0.15855E 02	0.	0.	
-0.42278E 01	0.87021E 02	-0.10559E 03	0.39935E 02	0.	0.	
-0.64551E 01	0.95449E 02	-0.12971E 03	0.82225E 02	0.	0.	
-0.31523E 01	0.99937E 02	-0.11241E 03	0.85780E 02	0.	0.	
0.52718E 01	0.10202E 03	-0.76893E 02	0.60623E 02	0.	0.	
0.18405E 02	0.10311E 03	-0.47973E 02	0.42636E 02	0.	0.	
0.26948E 02	0.10649E 03	-0.41788E 02	0.35434E 02	0.	0.	
0.44515E 02	0.11789E 03	-0.43386E 02	-0.20305E 02	0.	0.	
0.10112E 03	0.12020E 03	-0.74153E 02	-0.28794E 02	0.	0.	
0.14853E 03	0.87071E 02	-0.10682E 03	-0.14418E 02	0.	0.	
0.27243E 03	-0.23708E 07	-0.16623E 03	0.41240E 02	0.	-0.	
0.37741E 03	-0.14321E 03	-0.21576E 03	0.10878E 03	0.	-0.	
0.40213E 03	-0.38437E 03	-0.22334E 03	0.20511E 03	0.	-0.	
0.14671E 03	-0.29507E 03	-0.11249E 03	0.15194E 03	0.	-0.	
-0.36681E 02	-0.92738E 02	-0.10562E 02	0.35139E 02	-0.	-0.	
-0.58021E 02	-0.17649E 02	-0.94073E 01	0.18592E 02	-0.	0.	
-0.24044E 02	0.35874E-00	-0.22697E 02	0.70359E 01	0.	0.	
0.18882E 02	-0.77998E 02	-0.36277E 02	-0.11750E 02	0.	-0.	
0.13456E 03	-0.19200E 03	-0.73584E 02	0.23942E-00	0.	-0.	
-0.56694E 02	-0.67322E 02	-0.15221E 03	0.87806E 02	-0.	-0.	
-0.11929E 03	0.28333E 02	-0.23117E 03	0.35327E 03	-0.	-0.	
-0.60219E 02	-0.12288E 02	-0.14905E 03	0.18742E 03	-0.	-0.	
-0.78982E 01	-0.16731E 02	0.18127E 03	0.77461E 02	-0.	-0.	
-0.17995E 02	-0.15118E 02	0.16537E 03	0.67579E 02	-0.	-0.	
-0.20643E 02	-0.11236E 02	0.15063E 03	0.16191E 02	-0.	-0.	
-0.23440E 02	-0.10142E 02	0.12865E 03	0.10138E 02	-0.	-0.	
-0.23860E 02	-0.62945E 01	0.12346E 03	-0.67784E 01	-0.	-0.	
-0.24455E 02	-0.24302E 01	0.10700E 03	-0.19493E 02	-0.	0.	
-0.24601E 02	0.22692E 01	0.92136E 02	-0.31396E 02	-0.	0.	
-0.23706E 02	0.69024E 01	0.75443E 02	-0.40357E 02	-0.	0.	
-0.22012E 02	0.10229E 02	0.60075E 02	-0.45416E 02	-0.	0.	
-0.20303E 02	0.13951E 02	0.49704E 02	-0.49940E 02	-0.	0.	
-0.17861E 02	0.14630E 02	0.38804E 02	-0.50655E 02	-0.	0.	
-0.17343E 02	0.15325E 02	0.30888E 02	-0.51393E 02	-0.	0.	
-0.16784E 02	0.16036E 02	0.34947E 02	-0.52037E 02	-0.	0.	
-0.16185E 02	0.19460E 02	0.32976E 02	-0.54905E 02	-0.	0.	
-0.12723E 02	0.25307E 02	0.23487E 02	-0.57259E 02	-0.	0.	
-0.94206E 00	0.89019E 01	0.25455E 01	-0.34020E 02	0.	0.	
0.24026E 02	-0.38088E 01	-0.23228E 02	-0.34045E 02	0.	-0.	
-0.94514E 01	0.56895E 01	-0.68373E 01	-0.27879E 02	-0.	0.	
-0.77424E 01	0.42638E 01	-0.52461E 02	0.19606E 02	0.	-0.	
-0.66885E 01	0.89025E 01	0.23464E 02	-0.45361E 01	-0.	0.	
-0.19673E 01	0.78713E 01	0.12694E 02	-0.63699E 01	-0.	0.	
0.28407E 01	0.	0.33263E 01	0.	0.	0.	

Table XVII --- Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 190,590 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMISPAN 27 SEGMENT NUMBER 14

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				FREQUENCY
REAL	IMAGINARY	REAL	IMAGINARY			CPS
0.540706E 01	0.449129E 02	0.136396E 02	0.175908E 03	-0.	-0.	0.10
0.987844E 02	0.419499E 02	0.241356E 03	0.116367E 03	-0.	-0.	0.20
0.119066E 01	0.790387E 01	0.307357E 03	0.223659E 02	-0.	-0.	0.30
0.124788E 01	-0.130667E 02	0.334611E 03	-0.349268E 02	-0.	0.	0.40
0.122978E 03	-0.355737E 02	0.328311E 03	-0.971699E 02	-0.	0.	0.50
0.113866E 03	-0.909920E 02	0.304746E 03	-0.138722E 03	-0.	0.	0.60
0.105833E 03	-0.633227E 02	0.281611E 03	-0.181997E 03	-0.	0.	0.70
0.991155E 02	-0.748557E 02	0.261038E 03	-0.202754E 03	-0.	0.	0.80
0.941689E 02	-0.874145E 02	0.244490E 03	-0.234344E 03	-0.	0.	0.90
0.899113E 02	-0.119699E 03	0.237957E 03	-0.310811E 03	-0.	0.	1.00
0.828336E 02	-0.134629E 03	0.259624E 03	-0.391590E 03	-0.	0.	1.10
0.760331E 02	-0.178887E 03	0.172427E 03	-0.638895E 03	-0.	-0.	1.20
0.708888E 02	-0.207659E 03	0.154667E 03	-0.681689E 03	0.	-0.	1.30
0.640900E 02	-0.216780E 03	0.133333E 03	-0.715559E 03	0.	-0.	1.40
0.592699E 02	-0.232808E 03	0.119943E 03	-0.748598E 03	0.	-0.	1.47
0.540331E 02	-0.271664E 03	0.102227E 03	-0.826746E 03	0.	-0.	1.57
0.539960E 02	-0.321555E 03	0.332746E 02	-0.719355E 03	0.	-0.	1.67
-0.839179E 00	-0.381688E 03	-0.294688E 02	-0.827222E 03	-0.	-0.	1.77
-0.674118E 02	-0.417028E 03	-0.177515E 03	-0.321908E 03	-0.	-0.	1.87
-0.567218E 03	0.183028E 03	-0.113146E 04	0.339038E 03	-0.	0.	1.97
-0.371099E 03	0.197428E 03	-0.670218E 03	0.315095E 03	-0.	0.	2.07
-0.177156E 03	0.166599E 03	-0.291578E 03	0.222628E 03	-0.	0.	2.17
-0.979132E 02	0.116098E 01	-0.142366E 03	0.165198E 03	-0.	0.	2.27
-0.582072E 02	0.111068E 03	-0.775338E 02	0.840008E 02	-0.	0.	2.37
-0.252638E 02	0.995446E 02	-0.521908E 02	0.640366E 02	-0.	0.	2.47
-0.200338E 02	0.895018E 02	-0.535738E 02	0.369968E 02	0.	0.	2.57
-0.176518E 02	0.834608E 02	-0.545728E 02	0.220478E 02	0.	0.	2.67
-0.195928E 02	0.816678E 02	-0.646938E 02	0.171718E 02	0.	0.	2.77
-0.216218E 02	0.804768E 02	-0.714138E 02	0.143888E 02	0.	0.	2.87
-0.307028E 02	0.910968E 02	-0.960948E 02	0.362408E 02	0.	0.	2.97
-0.399928E 02	0.113138E 03	-0.117718E 03	0.766178E 02	0.	0.	3.07
-0.318358E 02	0.120168E 03	-0.102518E 03	0.778638E 02	0.	0.	3.17
-0.127418E 02	0.117078E 03	-0.697768E 02	0.350148E 02	0.	0.	3.27
0.101608E 02	0.114298E 03	-0.434718E 02	0.386918E 02	0.	0.	3.37
0.217458E 02	0.112128E 03	-0.379228E 02	0.140068E 02	0.	0.	3.47
0.421178E 02	0.116928E 03	-0.393728E 02	-0.186268E 02	0.	0.	3.57
0.102978E 03	0.116478E 03	-0.672928E 02	-0.261388E 02	0.	0.	3.67
0.163438E 03	0.737278E 02	-0.969398E 02	-0.138068E 02	0.	0.	3.77
0.292198E 03	-0.532108E 02	-0.150838E 03	0.376268E 02	0.	-0.	3.87
0.410648E 03	-0.214658E 03	-0.199838E 03	0.987168E 02	0.	-0.	3.97
0.417268E 03	-0.672338E 03	-0.202688E 03	0.186138E 03	0.	-0.	4.07
0.185828E 03	-0.372138E 03	-0.102938E 03	0.137088E 03	0.	-0.	4.17
-0.749678E 02	-0.956328E 02	-0.958868E 01	0.318888E 02	-0.	-0.	4.27
-0.119598E 03	-0.367598E 02	-0.853698E 01	0.168728E 02	-0.	0.	4.37
-0.888498E 02	-0.307268E 02	-0.205978E 02	0.638498E 01	0.	0.	4.47
-0.499398E 02	-0.401118E 02	-0.329218E 02	-0.106638E 02	0.	-0.	4.57
0.554278E 02	-0.184268E 01	-0.667768E 02	0.217278E-00	0.	-0.	4.67
-0.112068E 03	-0.359698E 02	-0.118138E 03	0.706808E 02	-0.	-0.	4.77
-0.211338E 03	0.144958E 03	-0.209758E 03	0.320598E 03	-0.	-0.	4.87
-0.119918E 03	0.496658E 02	-0.133278E 03	0.170038E 03	-0.	-0.	4.97
0.441738E 02	0.904358E 01	0.166508E 03	0.702948E 02	-0.	-0.	5.07
0.392848E 02	0.863738E 00	0.150078E 03	0.431738E 02	-0.	-0.	5.17
0.229178E 02	-0.370638E 01	0.136678E 03	0.146938E 02	-0.	-0.	5.27
0.137678E 02	-0.465718E 01	0.118678E 03	0.920008E 01	-0.	-0.	5.37
0.118358E 02	-0.866468E 01	0.112368E 03	-0.613128E 01	-0.	-0.	5.47
0.630328E 01	-0.964438E 01	0.971308E 02	-0.176898E 02	-0.	0.	5.57
0.208738E 01	-0.967718E 01	0.838118E 02	-0.286898E 02	-0.	0.	5.67
-0.211448E 01	-0.891528E 01	0.686638E 02	-0.346238E 02	-0.	0.	5.77
-0.511958E 01	-0.827318E 01	0.515178E 02	-0.412168E 02	-0.	0.	5.87
-0.726608E 01	-0.739688E 01	0.451058E 02	-0.453198E 02	-0.	0.	5.97
-0.801078E 01	-0.722288E 01	0.352168E 02	-0.439688E 02	-0.	0.	6.07
-0.929438E 01	-0.706088E 01	0.314738E 02	-0.466028E 02	-0.	0.	6.17
-0.954728E 01	-0.680008E 01	0.317168E 02	-0.472228E 02	-0.	0.	6.27
-0.986518E 01	-0.388198E 01	0.209238E 02	-0.498458E 02	-0.	0.	6.37
-0.109998E 02	-0.329448E 01	0.213138E 02	-0.519618E 02	-0.	0.	6.47
-0.122378E 02	-0.120378E 01	0.231338E 01	-0.308728E 02	0.	0.	6.57
-0.377998E 01	-0.876688E 01	-0.210798E 02	-0.308938E 02	0.	-0.	6.67
-0.167818E 02	-0.955918E 00	-0.620468E 01	-0.253008E 02	-0.	0.	6.77
-0.137458E 02	0.250288E 02	-0.478078E 02	0.187928E 02	0.	-0.	6.87
0.861698E 01	0.103408E 02	0.217038E 02	-0.611648E 01	-0.	0.	6.97
0.888868E 01	0.941998E 01	0.133208E 02	-0.958068E 01	-0.	0.	7.07
0.782058E 01	0.	0.301858E 01	0.	0.	0.	7.17

Table XVII - - - Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 190,590 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMISPAN: 40.06 SEGMENT NUMBER 8

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				FREQUENCY
REAL	IMAGINARY	REAL	IMAGINARY			CPS
0.326466E 01	0.412206E 02	0.125316E 02	0.169236E 03	0.	0.	0.00
0.570011E 02	0.269366E 02	0.231436E 03	0.110446E 03	0.	0.	0.20
0.726666E 02	0.548186E 01	0.296076E 03	0.211336E 02	0.	0.	0.40
0.793656E 02	-0.791286E 01	0.323346E 03	-0.349496E 02	0.	-0.	0.60
0.785046E 02	-0.226876E 02	0.317936E 03	-0.906176E 02	0.	-0.	0.80
0.737086E 02	-0.329346E 02	0.295336E 03	-0.138466E 03	0.	-0.	1.00
0.696266E 02	-0.417086E 02	0.273736E 03	-0.172436E 03	0.	-0.	1.20
0.661316E 02	-0.503976E 02	0.256576E 03	-0.206406E 03	0.	-0.	1.40
0.637136E 02	-0.601946E 02	0.237036E 03	-0.237036E 03	0.	-0.	1.60
0.619106E 02	-0.866956E 02	0.222656E 03	-0.316566E 03	0.	-0.	1.80
0.598106E 02	-0.117796E 03	0.191586E 03	-0.440176E 03	0.	-0.	2.00
0.553296E 02	-0.137046E 03	0.161026E 03	-0.448946E 03	0.	-0.	2.20
0.517346E 02	-0.157416E 03	0.141166E 03	-0.499146E 03	0.	-0.	2.40
0.466556E 02	-0.169736E 03	0.117086E 03	-0.528446E 03	0.	-0.	2.60
0.427226E 02	-0.183376E 03	0.102616E 03	-0.561126E 03	0.	-0.	2.80
0.376496E 02	-0.217216E 03	0.838756E 02	-0.638426E 03	0.	-0.	3.00
0.217886E 02	-0.240496E 03	0.508136E 02	-0.733576E 03	0.	-0.	3.20
-0.775696E 01	-0.312706E 03	-0.577106E 02	-0.840096E 03	-0.	-0.	3.40
-0.449206E 02	-0.134966E 03	-0.214126E 03	-0.287086E 03	-0.	-0.	3.60
-0.497106E 03	0.177366E 03	-0.117986E 04	0.577206E 03	-0.	0.	3.80
-0.325346E 03	0.188896E 03	-0.681056E 03	0.337766E 03	-0.	0.	4.00
-0.195676E 03	0.158596E 03	-0.281796E 03	0.233466E 03	-0.	0.	4.20
-0.817516E 02	0.130906E 03	-0.142176E 03	0.146306E 03	-0.	0.	4.40
-0.654636E 02	0.108616E 03	-0.813036E 02	0.844096E 02	-0.	0.	4.60
-0.392746E 02	0.114516E 03	-0.883216E 02	0.881616E 02	-0.	0.	4.80
-0.305666E 02	0.107326E 03	-0.776406E 02	0.633336E 02	-0.	0.	5.00
-0.187696E 02	0.101706E 03	-0.637616E 02	0.478636E 02	-0.	0.	5.20
-0.163796E 02	0.995836E 02	-0.703436E 02	0.426246E 02	-0.	0.	5.40
-0.163076E 02	0.962216E 02	-0.747676E 02	0.371896E 02	-0.	0.	5.60
-0.190116E 02	0.994116E 02	-0.922146E 02	0.310416E 02	0.	0.	5.80
-0.227726E 02	0.108886E 03	-0.107376E 03	0.757426E 02	0.	0.	6.00
-0.175596E 02	0.110856E 03	-0.938696E 02	0.733736E 02	0.	0.	6.20
-0.636466E 01	0.105966E 03	-0.694786E 02	0.492306E 02	0.	0.	6.40
0.720376E 01	0.102006E 03	-0.522936E 02	0.320336E 02	0.	0.	6.60
0.137136E 02	0.959166E 02	-0.507416E 02	0.797196E 01	0.	0.	6.80
0.290866E 02	0.879536E 02	-0.593586E 02	-0.236856E 02	0.	0.	7.00
0.363026E 02	0.856246E 02	-0.107466E 03	-0.271876E 02	0.	0.	7.20
0.385496E 02	0.892106E 02	-0.135376E 03	0.625136E 01	0.	0.	7.40
0.299076E 02	0.109486E 03	-0.246696E 03	0.103366E 03	0.	0.	7.60
0.139766E 02	0.139766E 03	-0.321446E 03	0.226726E 03	0.	0.	7.80
0.893756E 01	0.203396E 03	-0.328936E 03	0.375726E 03	0.	0.	8.00
0.591126E 02	0.200756E 03	-0.138366E 03	0.289316E 03	0.	0.	8.20
0.131936E 03	0.152406E 03	0.338976E 02	0.104426E 03	0.	0.	8.40
0.722226E 03	0.137196E 03	0.562386E 02	0.787566E 02	0.	0.	8.60
0.254336E 03	0.114346E 03	0.422326E 02	0.396736E 02	0.	0.	8.80
0.293696E 03	-0.446286E 02	0.320926E 02	0.727266E 01	0.	-0.	9.00
0.385056E 03	-0.191716E 03	0.859736E 01	-0.164086E 02	0.	-0.	9.20
0.170736E 03	-0.165566E 03	-0.121236E 03	0.930946E 02	0.	-0.	9.40
0.161476E 03	-0.313606E 03	-0.216246E 03	0.546126E 03	0.	-0.	9.60
0.826916E 02	-0.155296E 03	-0.116396E 03	0.174066E 03	0.	-0.	9.80
-0.154286E 03	-0.679416E 02	0.202916E 03	0.637426E 02	-0.	-0.	10.00
-0.139086E 03	-0.441736E 02	0.173386E 03	0.378486E 02	-0.	-0.	10.20
-0.127046E 03	-0.139036E 02	0.155896E 03	0.101506E 02	-0.	-0.	10.40
-0.109766E 03	-0.139806E 02	0.130636E 03	0.512896E 01	-0.	-0.	10.60
-0.105766E 03	-0.897926E-01	0.124596E 03	-0.793656E 01	-0.	0.	10.80
-0.931626E 02	0.105276E 02	0.103716E 03	-0.162646E 02	-0.	0.	11.00
-0.819386E 02	0.207096E 02	0.893346E 02	-0.219306E 02	-0.	0.	11.20
-0.695756E 02	0.287236E 02	0.722326E 02	-0.237116E 02	-0.	0.	11.40
-0.586766E 02	0.335446E 02	0.586336E 02	-0.230166E 02	-0.	0.	11.60
-0.509946E 02	0.382036E 02	0.504786E 02	-0.206096E 02	-0.	0.	11.80
-0.431966E 02	0.389836E 02	0.445276E 02	-0.220146E 02	-0.	0.	12.00
-0.418176E 02	0.397616E 02	0.437196E 02	-0.193626E 02	-0.	0.	12.20
-0.406176E 02	0.405386E 02	0.429986E 02	-0.186526E 02	-0.	0.	12.40
-0.388906E 02	0.446036E 02	0.423706E 02	-0.167076E 02	-0.	0.	12.60
-0.320116E 02	0.484146E 02	0.410536E 02	-0.673816E 01	-0.	0.	12.80
-0.155686E 02	0.322656E 02	0.694166E 02	-0.320346E 02	-0.	0.	13.00
0.930376E 01	0.271556E 02	0.796976E 02	-0.489026E 02	0.	0.	13.20
-0.932286E 01	0.291406E 02	0.133396E 02	-0.321936E 02	-0.		13.40
0.149416E 02	0.786016E 01	0.174676E 02	-0.405336E 02	0.		13.60
-0.123396E 02	0.176906E 02	-0.202146E 02	-0.133836E 02	-0.		13.80
-0.557306E 00	0.135396E 02	-0.249266E 02	-0.508096E 00	-0.	0.	14.00
0.966446E 01	0.	-0.180326E 02	0.	0.	0.	14.20

Table XVII - - - Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 190,590 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMI SPAN: 40.06 SEGMENT NUMBER 107

INCREMENTAL SHEAR STRESS				INCREMENTAL AXIAL STRESS		
REAL	IMAGINARY			REAL	IMAGINARY	FREQUENCY CPS
0.329746E 01	0.411896E 02	0.	0.	-0.107076E 02	-0.144660E 03	0.10
0.573618E 02	0.269086E 02	0.	0.	-0.197788E 02	-0.943668E 02	0.30
0.729468E 02	0.994798E 01	0.	0.	-0.252978E 03	-0.180564E 02	0.50
0.790888E 02	-0.772788E 01	0.	0.	-0.276429E 03	0.298628E 02	0.70
0.779199E 02	-0.222718E 02	0.	0.	-0.271678E 03	0.825593E 02	0.90
0.731928E 02	-0.322768E 02	0.	0.	-0.252778E 03	0.111831E 03	1.10
0.690058E 02	-0.407178E 02	0.	0.	-0.239388E 03	0.147338E 03	1.30
0.654268E 02	-0.490308E 02	0.	0.	-0.217518E 03	0.174308E 03	1.50
0.629938E 02	-0.583958E 02	0.	0.	-0.203278E 03	0.208758E 03	1.70
0.610708E 02	-0.684278E 02	0.	0.	-0.190078E 03	0.237048E 03	1.90
0.582648E 02	-0.112918E 03	0.	0.	-0.163698E 03	0.341928E 03	2.10
0.564918E 02	-0.131148E 03	0.	0.	-0.137588E 03	0.383598E 03	2.30
0.513648E 02	-0.150538E 03	0.	0.	-0.120618E 03	0.426408E 03	2.50
0.469218E 02	-0.162118E 03	0.	0.	-0.100728E 03	0.451528E 03	2.70
0.429498E 02	-0.175238E 03	0.	0.	-0.876768E 02	0.479448E 03	2.90
0.382238E 02	-0.207148E 03	0.	0.	-0.718468E 02	0.545488E 03	3.10
0.233788E 02	-0.268258E 03	0.	0.	-0.263298E 02	0.426788E 03	3.30
-0.413618E 01	-0.297968E 03	0.	0.	0.493098E 02	0.717808E 03	3.50
-0.481028E 02	-0.132548E 03	0.	0.	0.182958E 03	0.243298E 03	3.70
-0.447938E 03	0.163758E 03	0.	0.	0.100818E 04	-0.322358E 03	3.90
-0.307458E 03	0.175628E 03	0.	0.	0.381868E 03	-0.288578E 03	4.10
-0.147138E 03	0.147538E 03	0.	0.	0.249318E 03	-0.199488E 03	4.30
-0.770938E 02	0.120378E 03	0.	0.	0.121478E 03	-0.129008E 03	4.50
-0.427198E 02	0.997918E 02	0.	0.	0.696308E 02	-0.721908E 02	4.70
-0.365938E 02	0.104898E 03	0.	0.	0.754648E 02	-0.753278E 02	4.90
-0.286548E 02	0.976988E 02	0.	0.	0.663388E 02	-0.541148E 02	5.10
-0.180488E 02	0.921498E 02	0.	0.	0.561888E 02	-0.408958E 02	5.30
-0.143918E 02	0.900748E 02	0.	0.	0.601038E 02	-0.364198E 02	5.50
-0.166788E 02	0.972688E 02	0.	0.	0.638838E 02	-0.317758E 02	5.70
-0.206138E 02	0.919138E 02	0.	0.	0.787918E 02	-0.436118E 02	5.90
-0.250718E 02	0.132728E 03	0.	0.	0.917408E 02	-0.647168E 02	6.10
-0.195448E 02	0.109768E 03	0.	0.	0.802048E 02	-0.626938E 02	6.30
-0.747128E 01	0.100378E 03	0.	0.	0.593468E 02	-0.420638E 02	6.50
0.668898E 01	0.963638E 02	0.	0.	0.445118E 02	-0.280728E 02	6.70
0.133158E 02	0.901978E 02	0.	0.	0.433728E 02	-0.681148E 01	6.90
0.226978E 02	0.819468E 02	0.	0.	0.507178E 02	0.202378E 02	7.10
0.358758E 02	0.792068E 02	0.	0.	0.913218E 02	0.232298E 02	7.30
0.363648E 02	0.816078E 02	0.	0.	0.133618E 03	-0.934138E 01	7.50
0.305208E 02	0.997618E 02	0.	0.	0.210788E 03	-0.883138E 02	7.70
0.114868E 02	0.127878E 03	0.	0.	0.274698E 03	-0.105178E 03	7.90
0.910798E 01	0.148798E 03	0.	0.	0.261898E 03	-0.321038E 03	8.10
0.353658E 02	0.187668E 03	0.	0.	0.118228E 01	-0.267198E 03	8.30
0.124068E 01	0.142178E 03	0.	0.	-0.289638E 02	-0.894228E 02	8.50
0.210688E 01	0.127248E 03	0.	0.	-0.463598E 02	-0.672928E 02	8.70
0.241118E 01	0.109518E 03	0.	0.	-0.360508E 02	-0.509888E 02	8.90
0.277988E 01	-0.438608E 02	0.	0.	-0.274128E 02	-0.671398E 01	9.10
0.363228E 01	-0.181908E 03	0.	0.	-0.734598E 01	0.110198E 02	9.30
0.170818E 01	-0.160798E 03	0.	0.	0.103368E 03	-0.802268E 02	9.50
0.156528E 01	-0.305528E 03	0.	0.	0.184768E 03	-0.312828E 03	9.70
0.770048E 02	-0.149068E 03	0.	0.	0.991898E 02	-0.140728E 03	9.90
-0.193238E 01	-0.644838E 02	0.	0.	-0.173378E 01	-0.961728E 02	10.10
-0.136098E 01	-0.614068E 02	0.	0.	-0.149858E 03	-0.323388E 02	10.30
-0.123978E 01	-0.175148E 02	0.	0.	-0.113408E 03	-0.867218E 01	10.50
-0.106728E 01	-0.128548E 02	0.	0.	-0.111628E 03	-0.438238E 01	10.70
-0.102748E 01	0.191878E-00	0.	0.	-0.106438E 03	0.678128E 01	10.90
-0.907338E 02	0.100138E 02	0.	0.	-0.903218E 02	0.158948E 02	11.10
-0.792068E 02	0.192348E 02	0.	0.	-0.763478E 02	0.187378E 02	11.30
-0.671768E 02	0.262738E 02	0.	0.	-0.617148E 02	0.202398E 02	11.50
-0.565278E 02	0.303718E 02	0.	0.	-0.499278E 02	0.196658E 02	11.70
-0.499948E 02	0.342148E 02	0.	0.	-0.433018E 02	0.176098E 02	11.90
-0.429178E 02	0.348658E 02	0.	0.	-0.380458E 02	0.171008E 02	12.10
-0.412928E 02	0.354708E 02	0.	0.	-0.373348E 02	0.163438E 02	12.30
-0.400058E 02	0.360918E 02	0.	0.	-0.367378E 02	0.159368E 02	12.50
-0.388068E 02	0.388618E 02	0.	0.	-0.360208E 02	0.123668E 02	12.70
-0.528658E 02	0.429498E 02	0.	0.	-0.330778E 02	0.377448E 01	12.90
-0.193008E 02	0.311718E 02	0.	0.	-0.422228E 02	0.273718E 02	13.10
-0.831718E 00	0.276628E 02	0.	0.	-0.680968E 02	0.417838E 02	13.30
-0.113368E 02	0.287198E 02	0.	0.	-0.130818E 02	0.273068E 02	13.50
0.748928E 01	0.134638E 02	0.	0.	-0.152668E 02	0.346318E 02	13.70
-0.749358E 01	0.183738E 02	0.	0.	0.172898E 02	0.131448E 02	13.90
0.285138E 01	0.128178E 02	0.	0.	0.203298E 02	0.434138-00	14.10
0.114378E 02	0.	0.	0.	0.160918E 02	0.	14.30

Table XVII---Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 190,590 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

BODY BALANCE STATION: 540 SEGMENT NUMBER 17

INCREMENTAL SHEAR STRESS						
REAL	IMAGINARY					FREQUENCY CPS
-0.334296E 01	-0.27740E 02	0.	0.	0.	0.	0.10
-0.44444E 02	-0.16055E 02	0.	0.	0.	-0.	0.20
-0.53946E 02	-0.43280E 00	0.	-0.	0.	-0.	0.30
-0.55910E 02	0.81572E 01	0.	-0.	0.	-0.	0.40
-0.53027E 02	0.16442E 02	0.	-0.	0.	-0.	0.50
-0.47271E 02	0.21007E 02	0.	-0.	0.	-0.	0.60
-0.42415E 02	0.24020E 02	0.	-0.	0.	-0.	0.70
-0.38831E 02	0.26390E 02	0.	-0.	0.	-0.	0.80
-0.35713E 02	0.28630E 02	0.	-0.	0.	-0.	0.90
-0.33619E 02	0.33825E 02	0.	-0.	0.	-0.	1.00
-0.30272E 02	0.39486E 02	0.	-0.	0.	-0.	1.10
-0.28593E 02	0.42912E 02	0.	-0.	0.	-0.	1.20
-0.27780E 02	0.46530E 02	0.	-0.	0.	-0.	1.30
-0.26871E 02	0.48684E 02	0.	-0.	0.	-0.	1.40
-0.26269E 02	0.51125E 02	0.	-0.	0.	-0.	1.50
-0.25905E 02	0.53078E 02	0.	-0.	0.	-0.	1.60
-0.23189E 02	0.64841E 02	0.	-0.	0.	-0.	1.70
-0.18588E 02	0.74597E 02	0.	-0.	0.	-0.	1.80
-0.10397E 02	0.79150E 02	0.	-0.	0.	-0.	1.90
0.62920E 02	0.29499E 01	-0.	0.	-0.	0.	1.90
0.41647E 02	-0.91740E 00	-0.	0.	-0.	0.	1.90
0.15135E 02	0.38670E 01	-0.	-0.	-0.	-0.	2.00
0.30926E 01	0.93878E 01	-0.	-0.	-0.	-0.	2.10
-0.30149E 01	0.15383E 02	-0.	-0.	-0.	-0.	2.20
-0.47936E 01	0.16946E 02	-0.	-0.	-0.	-0.	2.30
-0.50727E 01	0.20127E 02	-0.	-0.	-0.	-0.	2.40
-0.51403E 01	0.22244E 02	-0.	-0.	-0.	-0.	2.50
-0.37822E 01	0.22987E 02	-0.	-0.	-0.	-0.	2.60
-0.27694E 01	0.23472E 02	-0.	-0.	-0.	-0.	2.70
0.12123E 01	0.19804E 02	-0.	-0.	-0.	-0.	2.80
0.91168E 01	0.12524E 02	-0.	-0.	-0.	-0.	2.90
0.28327E 01	0.11013E 02	-0.	-0.	-0.	-0.	2.90
-0.31547E 01	0.14212E 02	-0.	-0.	-0.	-0.	2.90
-0.84759E 01	0.17070E 02	0.	-0.	0.	-0.	2.90
-0.12062E 02	0.22418E 02	0.	-0.	0.	-0.	2.90
-0.15786E 02	0.34825E 02	0.	-0.	0.	-0.	2.90
-0.29105E 02	0.44944E 02	0.	-0.	0.	-0.	3.00
-0.39952E 02	0.70125E 02	0.	-0.	0.	-0.	3.10
-0.41196E 02	0.11789E 03	0.	-0.	0.	-0.	3.20
-0.84901E 02	0.17108E 03	0.	-0.	0.	-0.	3.30
-0.83635E 02	0.29455E 03	0.	-0.	0.	-0.	3.40
0.84498E 01	0.23261E 03	-0.	-0.	-0.	-0.	3.50
0.10491E 03	0.17010E 03	-0.	-0.	-0.	-0.	3.60
0.19766E 03	0.15581E 03	-0.	-0.	-0.	-0.	3.70
0.23654E 03	0.13112E 03	-0.	-0.	-0.	-0.	3.80
0.28879E 03	-0.98627E 02	-0.	0.	-0.	0.	3.80
0.42353E 03	-0.32151E 03	-0.	0.	-0.	0.	3.70
0.20886E 02	-0.13205E 03	-0.	0.	-0.	0.	3.60
-0.11585E 03	0.27851E 02	0.	0.	0.	-0.	3.50
-0.73891E 02	-0.33063E 01	0.	0.	0.	0.	3.40
0.21205E 03	-0.18675E 02	-0.	0.	-0.	0.	3.30
0.12121E 02	-0.20259E 02	-0.	0.	-0.	0.	3.20
0.76143E 01	-0.19495E 02	-0.	0.	-0.	0.	3.10
0.15380E 01	-0.19216E 02	-0.	0.	-0.	0.	3.00
0.31168E-00	-0.16967E 02	-0.	0.	-0.	0.	3.00
-0.32136E 01	-0.14060E 02	-0.	0.	-0.	0.	3.00
-0.58646E 01	-0.97526E 01	0.	0.	0.	0.	3.00
-0.81363E 01	-0.65393E 01	0.	0.	0.	0.	3.00
-0.92912E 01	-0.47969E-01	0.	0.	0.	0.	3.00
-0.92211E 01	0.57970E 01	0.	0.	0.	-0.	3.00
0.78216E 01	0.89666E 01	0.	-0.	0.	-0.	3.00
-0.73685E 01	0.81997E 01	0.	-0.	0.	-0.	3.00
-0.68797E 01	0.94769E 01	0.	-0.	0.	-0.	3.00
-0.61916E 01	0.16150E 02	0.	-0.	0.	-0.	3.00
-0.15726E 01	0.29093E 02	-0.	-0.	-0.	-0.	3.00
0.20643E 02	-0.98080E 01	-0.	0.	-0.	0.	3.00
0.78496E 02	-0.42938E 02	-0.	0.	-0.	0.	3.00
-0.18047E 02	-0.22341E 02	0.	0.	0.	0.	3.00
-0.49864E 02	0.13620E 02	0.	-0.	0.	-0.	3.00
0.95504E 01	0.11442E 01	-0.	-0.	-0.	-0.	3.00
0.36034E 01	-0.13286E 01	-0.	-0.	-0.	-0.	3.00
0.17133E 01	0.	-0.	0.	-0.	0.	10.00

Table XVII – – – Concluded

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 190,590 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

BODY BALANCE STATION: 820 SEGMENT NUMBER 1

		INCREMENTAL AXIAL STRESS REAL	INCREMENTAL AXIAL STRESS IMAGINARY			FREQUENCY CPS
0.	0.	0.10820E 02	0.10349E 03	0.	0.	0.10
0.	0.	0.15919E 03	0.64263E 02	0.	0.	0.20
0.	0.	0.19796E 03	0.66361E 01	0.	0.	0.30
0.	-0.	0.20835E 03	-0.27207E 02	0.	-0.	0.40
0.	-0.	0.20098E 03	-0.61645E 02	0.	-0.	0.50
0.	-0.	0.18263E 03	-0.82745E 02	0.	-0.	0.60
0.	-0.	0.16635E 03	-0.98404E 02	0.	-0.	0.70
0.	-0.	0.15325E 03	-0.11204E 03	0.	-0.	0.80
0.	-0.	0.14269E 03	-0.12577E 03	0.	-0.	0.90
0.	-0.	0.13383E 03	-0.13878E 03	0.	-0.	1.00
0.	-0.	0.11933E 03	-0.19178E 03	0.	-0.	1.20
0.	-0.	0.10725E 03	-0.21139E 03	0.	-0.	1.30
0.	-0.	0.10022E 03	-0.23156E 03	0.	-0.	1.40
0.	-0.	0.92133E 02	-0.24334E 03	0.	-0.	1.45
0.	-0.	0.86847E 02	-0.25648E 03	0.	-0.	1.47
0.	-0.	0.80352E 02	-0.28768E 03	0.	-0.	1.50
0.	-0.	0.41926E 02	-0.32649E 03	0.	-0.	1.55
0.	-0.	0.30643E 02	-0.37122E 03	0.	-0.	1.60
-0.	-0.	-0.26123E 02	-0.18998E 03	-0.	-0.	1.65
-0.	0.	-0.40201E 03	0.67341E 02	-0.	0.	1.80
-0.	0.	-0.23532E 03	0.47185E 02	-0.	0.	1.90
-0.	0.	-0.83442E 02	0.16329E 02	-0.	0.	2.00
-0.	-0.	-0.25459E 02	-0.21511E 02	-0.	-0.	2.10
-0.	-0.	-0.12175E 01	-0.54631E 02	-0.	-0.	2.20
-0.	-0.	-0.20741E 01	-0.61124E 02	-0.	-0.	2.30
-0.	-0.	-0.21805E 01	-0.78169E 02	-0.	-0.	2.35
-0.	-0.	-0.30228E 01	-0.88525E 02	-0.	-0.	2.40
-0.	-0.	-0.11997E 02	-0.91937E 02	-0.	-0.	2.43
-0.	-0.	-0.17435E 02	-0.93544E 02	-0.	-0.	2.44
-0.	-0.	-0.35945E 02	-0.76598E 02	-0.	-0.	2.47
-0.	-0.	-0.56263E 02	-0.44895E 02	-0.	-0.	2.50
-0.	-0.	-0.43224E 02	-0.44653E 02	-0.	-0.	2.54
-0.	-0.	-0.19055E 02	-0.63860E 02	-0.	-0.	2.58
0.	-0.	0.82100E 00	-0.78791E 02	0.	-0.	2.65
0.	-0.	0.51077E 01	-0.10512E 03	0.	-0.	2.70
0.	-0.	0.44563E 01	-0.15824E 03	0.	-0.	2.80
-0.	-0.	-0.13093E 02	-0.18990E 03	-0.	-0.	2.90
-0.	-0.	-0.27896E 02	-0.23365E 03	-0.	-0.	3.00
-0.	-0.	-0.43217E 02	-0.27969E 03	-0.	-0.	3.20
-0.	-0.	-0.58446E 02	-0.320 E 03	-0.	-0.	3.26
-0.	-0.	-0.76737E 02	-0.38766E 03	-0.	-0.	3.49
-0.	-0.	-0.16296E 03	-0.39898E 03	-0.	-0.	3.55
-0.	-0.	-0.26033E 03	-0.40773E 03	-0.	-0.	3.60
-0.	-0.	-0.50035E 03	-0.39481E 03	-0.	-0.	3.55
-0.	-0.	-0.62089E 03	-0.34068E 03	-0.	-0.	3.54
-0.	0.	-0.79791E 03	0.31623E 03	-0.	0.	3.60
-0.	0.	-0.12327E 04	0.97089E 03	-0.	0.	3.70
-0.	0.	-0.70839E 02	0.42332E 03	-0.	0.	3.85
0.	0.	0.29261E 03	0.56792E 02	0.	0.	4.00
0.	0.	0.17317E 03	0.93933E 02	0.	0.	4.20
0.	0.	0.26537E 02	0.91176E 02	0.	0.	4.50
0.	0.	0.51053E 02	0.81306E 02	0.	0.	4.70
0.	0.	0.59479E 02	0.63799E 02	0.	0.	4.80
0.	0.	0.67793E 02	0.59135E 02	0.	0.	4.96
0.	0.	0.69024E 02	0.43090E 02	0.	0.	5.00
0.	0.	0.71725E 02	0.27133E 02	0.	0.	5.15
0.	0.	0.72029E 02	0.73240E 01	0.	0.	5.30
0.	-0.	0.69562E 02	-0.12331E 02	0.	-0.	5.55
0.	-0.	0.63986E 02	-0.27050E 02	0.	-0.	5.70
0.	-0.	0.57747E 02	-0.44053E 02	0.	-0.	5.85
0.	-0.	0.47970E 02	-0.47223E 02	0.	-0.	6.00
0.	-0.	0.45792E 02	-0.50481E 02	0.	-0.	6.05
0.	-0.	0.43617E 02	-0.53339E 02	0.	-0.	6.08
0.	-0.	0.40814E 02	-0.76352E 02	0.	-0.	6.08
0.	-0.	0.25167E 02	-0.98879E 02	0.	-0.	6.20
-0.	-0.	-0.32324E 02	-0.11754E 02	-0.	-0.	6.40
-0.	0.	-0.15911E 03	0.57432E 02	-0.	0.	6.60
0.	0.	0.24374E 02	0.77446E 01	0.	0.	7.00
0.	0.	0.23203E 02	0.30191E 01	0.	0.	7.40
0.	-0.	0.71905E 02	-0.11644E 02	0.	-0.	8.20
0.	-0.	0.11196E 02	-0.12938E 02	0.	-0.	9.00
-0.	0.	-0.15885E 01	0.	-0.	0.	10.00

Table XVIII Stress Frequency Response Functions (Analysis Condition 4)

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 107,260 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMI SPAN: 27 SEGMENT NUMBER 10

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				
REAL	IMAGINARY	REAL	IMAGINARY			FREQUENCY CPS
-0.154009E 01	-0.632918E 01	0.208236E 02	0.922776E 02	-0.	-0.	0.10
-0.652639E 01	-0.525355E 01	0.133788E 03	0.767876E 02	-0.	-0.	0.30
-0.113948E 02	-0.303447E 01	0.164866E 03	0.462356E 02	-0.	-0.	0.56
-0.129598E 02	-0.123546E 01	0.194146E 03	0.881086E 02	-0.	-0.	0.66
-0.133166E 02	0.126746E 01	0.208166E 03	-0.238576E 02	-0.	0.	0.90
-0.129706E 02	0.297366E 01	0.214106E 03	-0.634956E 02	-0.	0.	0.96
-0.118466E 02	0.396706E 01	0.212806E 03	-0.952326E 02	-0.	0.	0.70
-0.103736E 02	0.476566E 01	0.204116E 03	-0.122656E 03	-0.	0.	0.80
-0.878366E 01	0.391366E 01	0.193296E 03	-0.148096E 03	-0.	0.	0.90
-0.709686E 01	0.985256E 00	0.181696E 03	-0.169806E 03	-0.	0.	1.00
-0.539176E 01	-0.388576E 01	0.158676E 03	-0.263296E 03	-0.	0.	1.20
-0.342726E 01	-0.715646E 01	0.140716E 03	-0.266996E 03	-0.	0.	1.36
-0.499656E 00	-0.107166E 02	0.131486E 03	-0.290226E 03	-0.	0.	1.46
-0.600196E 00	-0.124626E 02	0.122226E 03	-0.303376E 03	-0.	0.	1.46
-0.417986E-00	-0.153056E 02	0.116776E 03	-0.317766E 03	-0.	0.	1.46
-0.450366E-00	-0.212916E 02	0.110566E 03	-0.351086E 03	-0.	0.	1.50
-0.103256E 01	-0.292016E 02	0.969196E 02	-0.392836E 03	-0.	0.	1.56
-0.279526E 01	-0.397506E 02	0.726416E 02	-0.443316E 03	-0.	0.	1.66
-0.479366E 01	-0.869526E 02	0.377286E 02	-0.627856E 03	-0.	-0.	1.66
-0.705206E 01	-0.121266E 02	-0.911126E 03	-0.224856E 03	-0.	0.	1.80
-0.179306E 03	0.989556E 02	-0.758026E 03	0.210886E 03	-0.	0.	1.90
-0.121336E 03	0.108496E 03	-0.629916E 03	0.182396E 03	-0.	0.	2.00
-0.610416E 02	0.103336E 03	-0.183736E 03	0.185296E 03	-0.	0.	2.10
-0.315336E 02	0.971126E 02	-0.882246E 02	0.489876E 02	-0.	0.	2.20
-0.109736E 02	0.917466E 02	-0.604436E 02	0.387856E 02	-0.	0.	2.30
-0.616936E 01	0.903346E 02	-0.539066E 02	0.642686E 01	0.	0.	2.35
-0.279066E 01	0.896036E 02	-0.512166E 02	-0.903996E 01	0.	0.	2.40
-0.817016E 00	0.892666E 02	-0.577936E 02	-0.848556E 02	0.	0.	2.45
-0.156296E-00	0.885776E 02	-0.628666E 02	-0.824626E 02	0.	0.	2.46
0.774176E 00	0.893576E 02	-0.836216E 02	-0.145706E 02	0.	0.	2.47
0.273006E-00	0.947046E 02	-0.110706E 03	0.273746E 02	0.	0.	2.50
0.110026E 01	0.100066E 03	-0.116416E 03	0.465266E 02	0.	0.	2.54
0.459766E 01	0.104736E 03	-0.857366E 02	0.311856E 02	0.	0.	2.58
0.177486E 02	0.107596E 03	-0.509656E 02	0.156856E 02	0.	0.	2.65
0.256886E 02	0.114296E 03	-0.422086E 02	-0.944376E 01	0.	0.	2.70
0.414966E 02	0.136286E 03	-0.405906E 02	-0.456486E 02	0.	0.	2.80
0.912276E 02	0.152406E 03	-0.634716E 02	-0.396276E 02	0.	0.	3.00
0.137766E 03	0.168256E 03	-0.872376E 02	-0.700486E 02	0.	0.	3.10
0.223556E 03	0.165556E 03	-0.127446E 03	-0.693366E 02	0.	0.	3.20
0.318666E 03	0.146926E 03	-0.167626E 03	-0.614556E 02	0.	0.	3.26
0.397476E 03	0.109246E 02	-0.190876E 03	-0.107306E 02	0.	0.	3.29
0.487196E 03	-0.355876E 03	-0.206936E 03	0.123766E 03	0.	-0.	3.35
0.602696E 03	-0.695856E 03	-0.294046E 03	0.140696E 03	0.	-0.	3.40
-0.111726E 03	-0.359816E 03	-0.256566E 02	0.894186E 02	-0.	-0.	3.52
-0.170356E 03	-0.263916E 03	-0.199296E 02	0.552066E 02	-0.	-0.	3.56
-0.181636E 03	-0.125476E 03	-0.300936E 02	0.140906E 02	-0.	-0.	3.60
-0.160116E 03	-0.305876E 02	-0.768116E 02	0.365696E 02	-0.	-0.	3.70
-0.103716E 03	-0.324496E 02	-0.171326E 03	0.210366E 03	-0.	-0.	3.85
-0.327076E 02	-0.382406E 02	-0.170426E 03	0.186216E 03	0.	-0.	4.00
-0.751376E 02	0.386846E 02	-0.265856E 02	0.246546E 03	-0.	0.	4.20
-0.142666E 02	-0.473596E 01	0.110976E 03	0.971736E 02	-0.	-0.	4.50
-0.101686E 01	-0.112726E 02	0.175186E 03	0.536366E 02	-0.	-0.	4.70
-0.563346E 01	-0.224616E 02	0.159286E 03	0.149746E 02	-0.	-0.	4.80
-0.113596E 02	-0.119976E 02	0.132026E 03	0.833076E 01	-0.	-0.	4.96
-0.143046E 02	-0.544906E 01	0.125776E 03	0.902526E 01	-0.	-0.	5.00
-0.178686E 02	-0.639666E 01	0.106636E 03	-0.210386E 02	-0.	-0.	5.15
-0.193826E 02	-0.252786E 01	0.903916E 02	-0.316956E 02	-0.	0.	5.30
-0.197576E 02	0.102446E 01	0.731026E 02	-0.590676E 02	-0.	0.	5.50
-0.190486E 02	0.325906E 01	0.579486E 02	-0.628976E 02	-0.	0.	5.70
-0.181116E 02	0.535496E 01	0.441716E 02	-0.699016E 02	-0.	0.	5.85
-0.168426E 02	0.568926E 01	0.394846E 02	-0.663246E 02	-0.	0.	6.00
-0.165996E 02	0.601616E 01	0.368686E 02	-0.646726E 02	-0.	0.	6.03
-0.163466E 02	0.633566E 01	0.352666E 02	-0.670956E 02	-0.	0.	6.06
-0.160936E 02	0.766406E 01	0.336746E 02	-0.686906E 02	-0.	0.	6.08
-0.144636E 02	0.960356E 01	0.266306E 02	-0.698886E 02	-0.	0.	6.20
-0.125526E 02	0.111626E 02	0.151956E 02	-0.302626E 02	-0.	0.	6.60
-0.979656E 01	0.126796E 02	0.926246E 01	-0.452266E 02	-0.	0.	6.60
-0.197706E 01	-0.116656E 01	-0.270686E 02	0.161056E 02	0.	-0.	7.00
0.879646E 01	0.808646E 01	-0.608626E 02	-0.217236E 02	0.	0.	7.60
-0.106586E 02	0.104886E 02	-0.270756E 02	0.113146E 02	-0.	0.	8.30
-0.939736E 00	0.917556E 01	0.272986E 02	-0.797056E 01	-0.	0.	9.00
0.365706E 01	0.	0.815926E 01	0.	0.	0.	10.00

Table XVIII - - - Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 107,260 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMI SPAN: 27 SEGMENT NUMBER 14

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				
REAL	IMAGINARY	REAL	IMAGINARY			FREQUENCY CPS
0.921968E 01	0.142339E 02	0.188946E 02	0.837339E 02	-0.	-0.	0.10
0.209929E 02	0.119446E 02	0.122931E 03	0.696825E 02	-0.	-0.	0.30
0.247678E 02	0.776277E 01	0.149599E 03	0.619947E 02	-0.	-0.	0.36
0.299411E 02	0.259084E 01	0.174188E 03	0.164432E 02	-0.	-0.	0.44
0.330764E 02	-0.657468E 01	0.188908E 03	-0.234644E 02	-0.	0.	0.50
0.340875E 02	-0.109880E 02	0.196116E 03	-0.376208E 02	-0.	0.	0.60
0.340837E 02	-0.367268E 02	0.193116E 03	-0.864218E 02	-0.	0.	0.70
0.343566E 02	-0.221198E 02	0.195238E 03	-0.111308E 03	-0.	0.	0.80
0.334679E 02	-0.274568E 02	0.175618E 03	-0.134598E 03	-0.	0.	0.90
0.329117E 02	-0.407238E 02	0.164888E 03	-0.180408E 03	-0.	0.	1.00
0.309802E 02	-0.544278E 02	0.143998E 03	-0.220788E 03	-0.	0.	1.20
0.292678E 02	-0.624008E 02	0.127698E 03	-0.242228E 03	-0.	0.	1.36
0.281608E 02	-0.705868E 02	0.113928E 03	-0.263378E 03	-0.	0.	1.40
0.267448E 02	-0.793558E 02	0.110918E 03	-0.279308E 03	-0.	0.	1.45
0.257678E 02	-0.886738E 02	0.105968E 03	-0.288948E 03	-0.	0.	1.47
0.245928E 02	-0.983308E 02	0.100338E 03	-0.318498E 03	-0.	0.	1.50
0.209028E 02	-0.109698E 03	0.861368E 02	-0.355858E 03	-0.	0.	1.55
0.169888E 02	-0.130388E 03	0.695788E 02	-0.402298E 03	-0.	0.	1.60
0.141438E 01	-0.215958E 03	0.342378E 02	-0.569138E 03	-0.	-0.	1.63
-0.128868E 01	-0.628008E 02	-0.282348E 02	-0.204038E 03	-0.	0.	1.80
-0.329088E 01	0.138378E 03	-0.687888E 03	0.191368E 03	-0.	0.	1.90
-0.208678E 01	0.147728E 03	-0.390138E 03	0.165518E 03	-0.	0.	2.00
-0.577808E 02	0.123478E 03	-0.146738E 03	0.100098E 03	-0.	0.	2.10
-0.688488E 02	0.105018E 03	-0.800618E 02	0.644558E 02	-0.	0.	2.20
-0.731568E 02	0.972198E 02	-0.548518E 02	0.288448E 02	-0.	0.	2.30
-0.170398E 02	0.907138E 02	-0.488188E 02	0.583228E 01	0.	0.	2.35
-0.127908E 02	0.866738E 02	-0.464778E 02	-0.820358E 01	0.	0.	2.40
-0.122978E 02	0.850908E 02	-0.524658E 02	-0.134818E 02	0.	0.	2.45
-0.128358E 02	0.842528E 02	-0.570508E 02	-0.219998E 02	0.	0.	2.44
-0.169478E 02	0.861418E 02	-0.795548E 02	-0.132228E 02	0.	0.	2.47
-0.241218E 02	0.102788E 03	-0.100468E 03	0.250228E 02	0.	0.	2.50
-0.267318E 02	0.113868E 03	-0.105648E 03	0.422218E 02	0.	0.	2.54
-0.111438E 02	0.116358E 03	-0.778038E 02	0.283008E 02	0.	0.	2.58
0.944858E 01	0.116328E 03	-0.462428E 02	0.140528E 02	0.	0.	2.65
0.203058E 02	0.114928E 03	-0.383038E 02	-0.857308E 01	0.	0.	2.70
0.390878E 02	0.137158E 03	-0.368348E 02	-0.412618E 02	0.	0.	2.80
0.621758E 02	0.153088E 03	-0.479588E 02	-0.541108E 02	0.	0.	3.00
0.142158E 03	0.169288E 03	-0.791658E 02	-0.635678E 02	0.	0.	3.10
0.256678E 03	0.165488E 03	-0.115658E 03	-0.629198E 02	0.	0.	3.20
0.362288E 03	0.143988E 03	-0.152118E 03	-0.557698E 02	0.	0.	3.26
0.431058E 03	-0.237138E 01	-0.180658E 03	-0.975548E 01	0.	0.	3.28
0.446368E 03	-0.437668E 03	-0.244478E 03	0.114128E 03	0.	-0.	3.35
0.455258E 03	-0.602818E 03	-0.268658E 03	0.127678E 03	0.	-0.	3.40
-0.168678E 03	-0.447758E 03	-0.232828E 02	0.811458E 02	-0.	-0.	3.52
-0.240648E 03	-0.337978E 03	-0.188088E 02	0.500988E 02	-0.	-0.	3.56
-0.259888E 03	-0.178218E 03	-0.273098E 02	0.127868E 02	-0.	-0.	3.60
-0.253648E 03	-0.350998E 02	-0.697048E 02	0.331858E 02	-0.	-0.	3.70
-0.241778E 03	0.874438E 02	-0.155478E 03	0.190898E 03	-0.	-0.	3.85
-0.146338E 03	0.466408E 02	-0.154658E 03	0.168998E 03	0.	-0.	4.00
-0.721188E 02	0.109138E 03	-0.241268E 02	0.223738E 03	-0.	0.	4.20
0.161678E 02	0.274918E 02	0.100718E 03	0.881838E 02	-0.	-0.	4.50
0.695408E 02	0.643748E 01	0.158978E 03	0.486928E 02	-0.	-0.	4.70
0.955968E 02	-0.583418E 01	0.144548E 03	0.135888E 02	-0.	-0.	4.80
0.718748E 02	-0.760868E 01	0.119818E 03	0.739998E 01	-0.	-0.	4.96
0.188418E 02	-0.104958E 02	0.114138E 03	-0.819018E 01	-0.	-0.	5.00
0.109748E 02	-0.115848E 02	0.967698E 02	-0.191108E 02	-0.	-0.	5.15
0.525588E 01	-0.116788E 02	0.820288E 02	-0.287088E 02	-0.	0.	5.30
0.172058E-00	-0.111368E 02	0.663388E 02	-0.356438E 02	-0.	0.	5.40
-0.366588E 01	-0.105668E 02	0.525868E 02	-0.389288E 02	-0.	0.	5.70
-0.477328E 01	-0.988008E 01	0.437148E 02	-0.416948E 02	-0.	0.	5.85
-0.769588E 01	-0.979678E 01	0.344238E 02	-0.420388E 02	-0.	0.	6.00
-0.799818E 01	-0.963238E 01	0.338578E 02	-0.423998E 02	-0.	0.	6.03
-0.829358E 01	-0.950728E 01	0.320038E 02	-0.427388E 02	-0.	0.	6.06
-0.858628E 01	-0.893908E 01	0.315598E 02	-0.440038E 02	-0.	0.	6.08
-0.986008E 01	-0.900798E 01	0.241678E 02	-0.452728E 02	-0.	0.	6.20
-0.118488E 02	-0.707568E 01	0.137898E 02	-0.456118E 02	-0.	0.	6.40
-0.140128E 02	-0.408128E 01	0.794068E 01	-0.410428E 02	-0.	0.	6.60
-0.210008E 02	0.177958E 02	-0.245638E 02	0.147978E 02	0.	-0.	7.00
-0.295668E 02	0.385938E 01	-0.552308E 02	-0.197158E 02	0.	0.	7.40
-0.160948E 02	0.172148E 02	-0.245708E 02	0.104498E 02	-0.	0.	8.20
0.110208E 02	0.538958E 01	0.247728E 02	-0.723308E 01	-0.	0.	9.00
0.884978E 01	0.	0.740438E 01	0.	0.	0.	10.00

Table XVIII - - - Continued

(PSIAPS SINUSOIDAL GUST)

GROSS WEIGHT: 187,260 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMI SPAN: 40.06 SEGMENT NUMBER 8

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				
REAL	IMAGINARY	REAL	IMAGINARY			FREQUENCY CPS
0.322[illegible]E 01	0.15237E 02	0.18733E 02	0.85566E 02	-0.	-0.	0.10
0.716[illegible]E 02	0.12847E 02	0.12404E 03	0.71353E 02	-0.	-0.	0.30
0.246[illegible]E 02	0.80364E 01	0.15218E 03	0.43023E 02	-0.	-0.	0.36
0.316[illegible]E 02	0.35452E 01	0.17987E 03	0.16731E 02	-0.	0.	0.44
0.342[illegible]E 02	-0.36015E 01	0.19334E 03	-0.24724E 02	-0.	0.	0.50
0.360[illegible]E 02	-0.99239E 01	0.20138E 03	-0.60604E 02	-0.	0.	0.60
0.362[illegible]E 02	-0.15544E 02	0.19875E 03	-0.91188E 02	-0.	0.	0.70
0.356[illegible]E 02	-0.20791E 02	0.19087E 03	-0.11787E 03	-0.	0.	0.80
0.346[illegible]E 02	-0.26179E 02	0.18075E 03	-0.14280E 03	0.	-0.	0.90
0.361[illegible]E 02	-0.38992E 02	0.16964E 03	-0.19264E 03	0.	-0.	1.00
0.329[illegible]E 02	-0.52437E 02	0.14685E 03	-0.23612E 03	0.	-0.	1.20
0.319[illegible]E 02	-0.60446E 02	0.12840E 03	-0.25915E 03	0.	-0.	1.34
0.310[illegible]E 02	-0.68564E 02	0.11891E 03	-0.28160E 03	0.	-0.	1.40
0.298[illegible]E 02	-0.73294E 02	0.10916E 03	-0.29428E 03	0.	-0.	1.45
0.290[illegible]E 02	-0.78567E 02	0.10349E 03	-0.30812E 03	0.	-0.	1.47
0.279[illegible]E 02	-0.91114E 02	0.97051E 02	-0.34006E 03	0.	-0.	1.50
0.247[illegible]E 02	-0.10713E 03	0.80[illegible]22E 02	-0.37921E 03	0.	-0.	1.55
0.190[illegible]E 02	-0.12783E 03	0.57973E 02	-0.42770E 03	0.	-0.	1.60
0.[illegible]2[illegible]E 01	-0.21331E 03	0.22955E 02	-0.59674E 03	0.	-0.	1.65
-0.11916E 03	-0.66747E 02	-0.31780E 03	-0.19642E 03	-0.	-0.	1.80
-0.31520E 03	0.12853E 03	-0.73430E 03	0.20950E 03	-0.	0.	1.90
-0.19736E 03	0.13109E 03	-0.49695E 03	0.17217E 03	-0.	0.	2.00
-0.91429E 02	0.10403E 03	-0.17296E 03	0.93428E 02	-0.	0.	2.10
-0.44946E 02	0.87584E 02	-0.86665E 02	0.33463E 02	-0.	0.	2.20
-0.34105E 02	0.92781E 02	-0.82339E 02	0.38539E 02	-0.	0.	2.30
-0.26690E 02	0.86605E 02	-0.73914E 02	0.16811E 02	-0.	0.	2.35
-0.15350E 02	0.81525E 02	-0.61380E 02	0.17927E 01	-0.	0.	2.40
-0.12667E 02	0.79362E 02	-0.64102E 02	-0.38898E 01	-0.	0.	2.43
-0.12466E 02	0.75010E 02	-0.67521E 02	-0.13713E 02	-0.	0.	2.44
-0.15819E 02	0.75486E 02	-0.83081E 02	-0.78881E 01	0.	0.	2.47
-0.20435E 02	0.87515E 02	-0.10400E 03	0.22993E 02	0.	0.	2.50
-0.21204E 02	0.94909E 02	-0.10764E 03	0.34907E 02	0.	0.	2.54
-0.10224E 02	0.93134E 02	-0.83224E 02	0.17964E 02	0.	0.	2.58
0.65273E 01	0.89753E 02	-0.57544E 02	0.26547E 01	0.	0.	2.65
0.14442E 02	0.94185E 02	-0.52796E 02	-0.21773E 02	0.	0.	2.70
0.25641E 02	0.75843E 02	-0.57137E 02	-0.58160E 02	0.	0.	2.80
0.44078E 02	0.71332E 02	-0.94227E 02	-0.72633E 02	0.	0.	3.00
0.52691E 02	0.64806E 02	-0.13009E 03	-0.81549E 02	0.	0.	3.10
0.59558E 02	0.59269E 02	-0.19191E 03	-0.75181E 02	0.	0.	3.20
0.60207E 02	0.54005E 02	-0.25528E 03	-0.58869E 02	0.	0.	3.26
0.575179E 02	0.55547E 02	-0.30558E 03	0.32615E 02	0.	0.	3.29
0.42213E 02	0.84559E 02	-0.41881E 03	0.26983E 03	0.	0.	3.35
0.19062E 02	0.15331E 03	-0.45628E 03	0.30134E 03	0.	0.	3.40
0.11898E 01	0.14343E 03	0.27545E 02	0.21384E 03	0.	0.	3.52
0.15060E 03	0.13297E 03	0.46533E 02	0.15909E 03	0.	0.	3.56
0.17674E 03	0.10217E 03	0.40112E 02	0.88332E 02	0.	0.	3.60
0.24683E 03	-0.26122E 02	-0.14594E 01	0.78183E 02	0.	-0.	3.70
0.39066E 03	-0.42247E 03	-0.68716E 02	0.14944E 03	0.	-0.	3.85
0.29699E 03	-0.27404E 03	-0.74697E 02	0.14956E 03	0.	-0.	4.00
-0.50058E 03	-0.14089E 03	-0.53741E 02	0.28552E 03	-0.	-0.	4.20
-0.11593E 03	-0.69695E 02	0.13803E 03	0.94646E 02	-0.	-0.	4.50
-0.12838E 03	-0.45430E 02	0.20929E 03	0.44911E 02	-0.	-0.	4.70
-0.11957E 03	-0.20335E 02	0.18492E 03	0.43142E 01	-0.	-0.	4.80
-0.10427E 03	-0.15550E 02	0.14735E 03	-0.20169E 01	-0.	-0.	4.96
-0.60058E 01	-0.22293E 01	0.13910E 03	-0.17228E 02	-0.	-0.	5.00
-0.88831E 02	0.77575E 01	0.11464E 03	-0.26173E 02	-0.	0.	5.15
-0.78325E 02	0.17069E 02	0.94959E 02	-0.32366E 02	-0.	0.	5.30
-0.66728E 02	0.23993E 02	0.75529E 02	-0.35334E 02	-0.	0.	5.44
-0.58383E 02	0.27797E 02	0.60245E 02	-0.36186E 02	-0.	0.	5.70
-0.49695E 02	0.31044E 02	0.51425E 02	-0.36313E 02	-0.	0.	5.85
-0.43082E 02	0.31535E 02	0.43566E 02	-0.36271E 02	-0.	0.	6.00
-0.41980E 02	0.32008E 02	0.42344E 02	-0.36211E 02	-0.	0.	6.03
-0.40888E 02	0.32464E 02	0.41159E 02	-0.36136E 02	-0.	0.	6.06
-0.39803E 02	0.34316E 02	0.40007E 02	-0.35614E 02	-0.	0.	6.08
-0.35003E 02	0.36734E 02	0.35234E 02	-0.34201E 02	-0.	0.	6.18
-0.27212E 02	0.38432E 02	0.28719E 02	-0.32245E 02	-0.	0.	6.46
-0.19113E 02	0.38197E 02	0.23836E 02	-0.28438E 02	-0.	0.	6.60
0.2E47PF-00	0.87316E 01	0.20843E 02	-0.46723E 02	0.	0.	7.00
0.22146E 02	0.25986E 02	0.28386E 02	-0.26223E 02	0.	0.	7.46
0.45560E 01	0.13445E 02	-0.26153E 02	-0.94046E 01	0.	0.	8.20
-0.33670E 01	0.13788E 02	-0.12173E 02	-0.26803E 01	-0.	0.	9.00
0.93374E 01	0.	-0.11986E 02	0.	0.	0.	10.00

Table XVIII – – – Continued

(PSI/PS SINUSOIDAL GUST)

GROSS WEIGHT: 107,260 LB CUTOFF FREQUENCY: 16 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

PERCENT SEMISPAN 42.00 SEGMENT NUMBER 107

INCREMENTAL SHEAR @ ROOT				VERTICAL SHEAR @ ROOT		FREQUENCY CPS
REAL	IMAGINARY			REAL	IMAGINARY	
0.339105E 01	0.156105E 02	-0.	-0.	-0.160066E 02	-0.731105E 02	0.10
0.223333E 02	0.131345E 02	-0.	-0.	-0.105499E 03	-0.609685E 02	0.30
0.279303E 02	0.419385E 01	-0.	-0.	-0.130035E 03	-0.367605E 02	0.36
0.324165E 02	0.161635E 01	-0.	0.	-0.153685E 03	-0.142955E 02	0.44
0.363932E 02	-0.160255E 01	-0.	0.	-0.165195E 33	0.211255E 02	0.50
0.388845E 02	-0.991025E 01	-0.	0.	-0.172065E 03	0.517815E 02	0.60
0.387155E 02	-0.154615E 02	-0.	0.	-0.169825E 03	0.779165E 02	0.70
0.360125E 02	-0.205325E 02	-0.	0.	-0.163085E 03	0.100715E 03	0.80
0.350675E 02	-0.256995E 02	0.	-0.	-0.154435E 03	0.122025E 03	0.90
0.342155E 02	-0.298675E 02	0.	-0.	-0.146545E 03	0.144595E 03	1.00
0.332765E 02	-0.506275E 02	0.	-0.	-0.125475E 03	0.201755E 03	1.20
0.318485E 02	-0.580665E 02	0.	-0.	-0.109715E 03	0.221415E 03	1.34
0.310485E 02	-0.655745E 02	0.	-0.	-0.101515E 03	0.240615E 03	1.40
0.295105E 02	-0.702055E 02	0.	-0.	-0.932685E 02	0.251445E 03	1.45
0.291915E 02	-0.751815E 02	0.	-0.	-0.884255E 02	0.263275E 03	1.47
0.291755E 02	-0.870265E 02	0.	-0.	-0.829265E 02	0.290585E 03	1.50
0.295535E 02	-0.102165E 03	0.	-0.	-0.691425E 02	0.324015E 03	1.55
0.300075E 02	-0.121735E 03	0.	-0.	-0.495345E 02	0.365445E 03	1.60
0.304755E 02	-0.203115E 03	0.	-0.	-0.196145E 02	0.508175E 03	1.65
-0.307755E 02	-0.662395E 02	-0.	-0.	0.271565E 03	0.167835E 03	1.80
-0.295445E 02	0.118525E 03	-0.	0.	0.627415E 03	-0.179035E 03	1.90
-0.295415E 02	0.121545E 03	-0.	0.	0.347715E 03	-0.147115E 03	2.00
-0.284525E 02	0.160005E 03	-0.	0.	0.167775E 03	-0.815375E 02	2.10
-0.418125E 02	0.905565E 02	-0.	0.	0.740335E 02	-0.303015E 02	2.20
-0.419775E 02	0.451065E 02	-0.	0.	0.703535E 02	-0.329295E 02	2.30
-0.369355E 02	0.791955E 02	-0.	0.	0.631565E 02	-0.143645E 02	2.35
-0.361465E 02	0.760315E 02	-0.	0.	0.524655E 02	-0.159185E 01	2.40
-0.119575E 02	0.719235E 02	-0.	0.	0.547715E 02	0.332355E 01	2.45
-0.115455E 02	0.677855E 02	-0.	0.	0.576925E 02	0.117175E 02	2.44
-0.149235E 02	0.691655E 02	0.	0.	0.709875E 02	0.673995E 01	2.47
-0.211055E 02	0.717775E 02	0.	0.	0.688585E 02	-0.196475E 02	2.50
-0.221015E 02	0.695175E 02	0.	0.	0.919695E 02	-0.298265E 02	2.54
-0.107755E 02	0.680965E 02	0.	0.	0.711095E 02	-0.153695E 02	2.58
0.429685E 01	0.867255E 02	0.	0.	0.491685E 02	-0.226835E 01	2.65
0.162115E 02	0.791715E 02	0.	0.	0.451115E 02	0.186035E 02	2.70
0.253005E 02	0.707685E 02	0.	0.	0.488205E 02	0.496945E 02	2.80
0.496925E 02	0.660035E 02	0.	0.	0.805115E 02	0.620605E 02	3.00
0.518855E 02	0.592855E 02	0.	0.	0.111155E 03	0.696745E 02	3.20
0.497265E 02	0.536085E 02	0.	0.	0.163985E 03	0.642375E 02	3.28
0.494905E 02	0.494125E 02	0.	0.	0.218125E 03	0.503005E 02	3.26
0.489635E 02	0.481805E 02	0.	0.	0.261105E 03	-0.278695E 02	3.29
0.475565E 02	0.744805E 02	0.	0.	0.357855E 03	-0.230575E 03	3.35
0.191905E 02	0.161675E 03	0.	0.	0.389865E 03	-0.257675E 03	3.40
0.117705E 03	0.136625E 03	0.	0.	-0.225355E 02	-0.184425E 03	3.52
0.142895E 03	0.124355E 03	0.	0.	-0.397595E 02	-0.135935E 03	3.56
0.149235E 03	0.961935E 02	0.	0.	-0.342735E 02	-0.794765E 02	3.60
0.237445E 03	0.296815E 02	0.	-0.	0.124695E 01	-0.666925E 02	3.70
0.331395E 03	-0.605095E 03	0.	-0.	0.587135E 02	-0.127695E 03	3.85
0.279105E 03	-0.262155E 03	0.	-0.	0.643825E 02	-0.126945E 03	4.00
-0.595025E 02	-0.140195E 03	-0.	-0.	0.459185E 02	-0.243965E 03	4.20
0.115465E 03	-0.669605E 02	-0.	-0.	-0.117945E 03	-0.809685E 02	4.50
-0.127905E 03	0.428435E 02	-0.	-0.	-0.178835E 03	-0.382035E 02	4.70
-0.113425E 03	0.186605E 02	-0.	-0.	-0.159005E 03	-0.364625E 01	4.80
-0.102515E 03	-0.138745E 02	-0.	-0.	-0.125905E 03	0.172335E 01	4.96
-0.895255E 02	-0.126245E 01	-0.	-0.	-0.114855E 03	0.147205E 02	5.00
0.845535E 02	0.807145E 01	-0.	0.	-0.979545E 02	0.223635E 02	5.15
0.761875E 02	0.165905E 02	-0.	0.	-0.811365E 02	0.276555E 02	5.30
0.646255E 02	0.228075E 02	-0.	0.	-0.665145E 02	0.301905E 02	5.50
-0.568095E 02	0.261665E 02	-0.	0.	-0.514755E 02	0.309195E 02	5.70
-0.496455E 02	0.290015E 02	-0.	0.	-0.439395E 02	0.310275E 02	5.85
-0.427265E 02	0.294275E 02	0.	0.	-0.372245E 02	0.309915E 02	6.00
-0.413235E 02	0.298835E 02	-0.	0.	-0.361805E 02	0.309405E 02	6.05
-0.403205E 02	0.302315E 02	-0.	0.	-0.351675E 02	0.308765E 02	6.06
-0.393195E 02	0.316245E 02	-0.	0.	-0.341835E 02	0.304305E 02	6.08
-0.368235E 02	0.330895E 02	-0.	0.	-0.301055E 02	0.292225E 02	6.20
-0.278105E 02	0.353185E 02	-0.	0.	-0.244395E 02	0.275515E 02	6.40
-0.207285E 02	0.352775E 02	-0.	0.	-0.201665E 02	0.262995E 02	6.60
-0.667255E 01	0.166605E 02	0.	0.	-0.178095E 02	0.304945E 02	7.00
0.1 5165E 02	0.256965E 02	0.	0.	-0.262565E 02	0.224065E 02	7.40
0.352175E 01	0.194975E 02	0.	0.	0.223545E 02	0.803555E 01	8.20
0.845665E 00	0.130015E 02	-0.	0.	0.104015E 02	0.229025E 01	9.00
0.111665E 02	0.	0.	0.	0.192425E 02	0.	10.00

Table XVIII --- Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 107,260 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

BODY BALANCE STATION: 540 SEGMENT NUMBER 17

INCREMENTAL SHEAR STRESS						
REAL	IMAGINARY					FREQUENCY CPS
-0.18744E-01	-0.56730E 00	0.	0.	0.	0.	0.10
-0.10561E 01	-0.41030E-00	0.	0.	0.	0.	0.20
-0.12628E 01	-0.15013E-00	0.	0.	0.	0.	0.30
-0.13875E 01	0.61359E-01	0.	-0.	0.	-0.	0.40
-0.14238E 01	0.35005E-00	0.	-0.	0.	-0.	0.50
-0.13790E 01	0.55578E 00	0.	-0.	0.	-0.	0.60
-0.12736E 01	0.69612E 00	0.	-0.	0.	-0.	0.70
-0.11541E 01	0.79702E 00	0.	-0.	0.	-0.	0.80
-0.10431E 01	0.86307E 00	0.	-0.	0.	-0.	0.90
-0.94720E 00	0.97962E 00	0.	-0.	0.	-0.	1.00
-0.81058E 00	0.10819E 01	0.	-0.	0.	-0.	1.10
-0.74640E 00	0.11396E 01	0.	-0.	0.	-0.	1.20
-0.72374E 00	0.11982E 01	0.	-0.	0.	-0.	1.30
-0.70505E 00	0.12322E 01	0.	-0.	0.	-0.	1.40
-0.69518E 00	0.12682E 01	0.	-0.	0.	-0.	1.50
-0.68452E 00	0.13594E 01	0.	-0.	0.	-0.	1.60
-0.65883E 00	0.14793E 01	0.	-0.	0.	-0.	1.70
-0.62177E 00	0.16209E 01	0.	-0.	0.	-0.	1.80
-0.56095E 00	0.22900E 01	0.	-0.	0.	-0.	1.90
0.21512E-00	0.15409E 01	-0.	-0.	-0.	-0.	2.00
0.15780E 01	0.25628E-00	-0.	-0.	-0.	-0.	2.10
0.99722E 00	0.20042E-00	-0.	-0.	-0.	-0.	2.20
0.36559E-00	0.35724E-00	-0.	-0.	-0.	-0.	2.30
0.65785E-01	0.55122E 00	-0.	-0.	-0.	-0.	2.40
-0.52279E-01	0.59644E 00	-0.	-0.	-0.	-0.	2.50
-0.70477E-01	0.68965E 00	-0.	-0.	-0.	-0.	2.59
-0.92722E-01	0.75802E 00	0.	-0.	0.	-0.	2.60
-0.69766E-01	0.78576E 00	-0.	-0.	-0.	-0.	2.63
-0.47820E-01	0.83524E 00	-0.	-0.	-0.	-0.	2.64
0.50328E-01	0.79130E 00	-0.	-0.	-0.	-0.	2.67
0.19333E-00	0.55898E 00	-0.	-0.	-0.	-0.	2.68
0.24186E-00	0.42460E-00	-0.	-0.	-0.	-0.	2.74
0.77424E-01	0.46483E-00	-0.	-0.	-0.	-0.	2.78
-0.15676E-00	0.53391E 00	0.	-0.	0.	-0.	2.65
-0.25236E-00	0.65558E 00	0.	-0.	0.	-0.	2.70
-0.37805E-00	0.83749E 00	0.	-0.	0.	-0.	2.80
-0.68174E 00	0.89972E 00	0.	-0.	0.	-0.	3.00
-0.10167E 01	0.99665E 00	0.	-0.	0.	-0.	3.10
-0.17704E 01	0.12275E 01	0.	-0.	0.	-0.	3.20
-0.27196E 01	0.15811E 01	0.	-0.	0.	-0.	3.26
-0.35629E 01	0.34340E 01	0.	-0.	0.	-0.	3.29
-0.56797E 01	0.84924E 01	0.	-0.	0.	-0.	3.35
-0.49616E 01	0.10881E 02	0.	-0.	0.	-0.	3.45
0.50802E 01	0.92636E 01	-0.	-0.	-0.	-0.	3.52
0.41136E 01	0.81326E 01	-0.	-0.	-0.	-0.	3.56
0.72931E 01	0.62744E 01	-0.	-0.	-0.	-0.	3.60
0.56272E 01	0.12151E 01	-0.	-0.	-0.	-0.	3.70
0.15589E 02	-0.16700E 02	-0.	0.	-0.	0.	3.85
0.17309E 02	-0.94617E 01	-0.	0.	-0.	0.	4.00
-0.88812E 01	0.56045E 01	0.	-0.	0.	-0.	4.20
-0.60395E-00	0.19367E-00	0.	-0.	0.	-0.	4.30
0.25759E 01	-0.82772E 00	-0.	0.	-0.	0.	4.70
0.19428E 01	-0.13196E 01	-0.	0.	-0.	0.	4.80
0.10720E 01	-0.13468E 01	-0.	0.	-0.	0.	4.96
0.90382E 00	-0.13141E 01	-0.	0.	-0.	0.	5.00
0.68213E-00	-0.11901E 01	-0.	0.	-0.	0.	5.15
0.17549E-00	-0.10032E 01	-0.	0.	-0.	0.	5.30
-0.60646E-01	-0.81876E 00	-0.	0.	-0.	0.	5.45
-0.15725E-00	-0.69857E 00	0.	0.	0.	0.	5.70
-0.19890E-00	-0.58294E 00	0.	0.	0.	0.	5.85
-0.21508E-00	-0.56623E 00	0.	0.	0.	0.	6.00
-0.21537E-00	-0.56588E 00	0.	0.	0.	0.	6.03
-0.21497E-00	-0.52788E 00	0.	0.	0.	0.	6.06
-0.21390E-00	-0.45135E-00	0.	0.	0.	0.	6.08
-0.20107E-00	-0.34159E-00	0.	0.	0.	0.	6.20
-0.15221E-00	-0.25352E-00	0.	0.	0.	0.	6.50
-0.65765E-01	-0.18955E-00	0.	0.	0.	0.	6.60
0.29049E-00	-0.12628E 01	-0.	0.	-0.	0.	7.00
0.10407E 01	-0.81816E 00	-0.	0.	-0.	0.	7.40
-0.24913E 01	0.93176E 00	0.	-0.	0.	-0.	8.20
0.88968E 00	-0.68075E-01	-0.	-0.	-0.	-0.	9.00
0.45398E-00	0.	-0.	0.	-0.	0.	10.00

Table XVIII - - - Concluded

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 107,260 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.85

BODY BALANCE STATION: 820 SEGMENT NUMBER 1

INCREMENTAL AXIAL STRESS						FREQUENCY
REAL		IMAGINARY				CPS
0.	0.	0.12938E 02	0.44903E 02	0.	0.	0.10
0.	0.	0.76771E 02	0.36895E 02	0.	0.	0.30
0.	0.	0.92098E 02	0.18922E 02	0.	0.	0.36
0.	0.	0.10575E 03	0.33791E 01	0.	0.	0.44
0.	-0.	0.11117E 03	-0.19423E 02	0.	-0.	0.50
0.	-0.	0.11209E 03	-0.37300E 02	0.	-0.	0.60
0.	-0.	0.10771E 03	-0.51609E 02	0.	-0.	0.70
0.	-0.	0.10133E 03	-0.62954E 02	0.	-0.	0.80
0.	-0.	0.94472E 02	-0.72893E 02	0.	-0.	0.90
0.	-0.	0.88327E 02	-0.91744E 02	0.	-0.	1.00
0.	-0.	0.77336E 02	-0.10794E 03	0.	-0.	1.20
0.	-0.	0.70429E 02	-0.11643E 03	0.	-0.	1.34
0.	-0.	0.67086E 02	-0.12473E 03	0.	-0.	1.40
0.	-0.	0.63840E 02	-0.12938E 03	0.	-0.	1.45
0.	-0.	0.62006E 02	-0.13445E 03	0.	-0.	1.47
0.	-0.	0.59919E 02	-0.14007E 03	0.	-0.	1.50
0.	-0.	0.56752E 02	-0.14024E 03	0.	-0.	1.55
0.	-0.	0.47449E 02	-0.17771E 03	0.	-0.	1.60
0.	-0.	0.36299E 02	-0.24062E 03	0.	-0.	1.69
-0.	-0.	-0.74462E 02	-0.11736E 03	-0.	-0.	1.80
-0.	0.	-0.21665E 03	0.14138E 02	-0.	0.	1.90
-0.	0.	-0.11427E 03	0.23438E 01	-0.	0.	2.00
-0.	-0.	-0.37579E 02	-0.27002E 02	-0.	-0.	2.10
-0.	-0.	-0.92994E 01	-0.33639E 02	-0.	-0.	2.20
-0.	-0.	-0.81244E 01	-0.38227E 02	-0.	-0.	2.30
-0.	-0.	-0.73869E 01	-0.70743E 02	-0.	-0.	2.35
-0.	-0.	-0.73994E 01	-0.79980E 02	-0.	-0.	2.40
-0.	-0.	-0.11945E 02	-0.82118E 02	-0.	-0.	2.43
-0.	-0.	-0.15127E 02	-0.87229E 02	-0.	-0.	2.44
-0.	-0.	-0.27321E 02	-0.82019E 02	-0.	-0.	2.47
-0.	-0.	-0.43299E 02	-0.59380E 02	-0.	-0.	2.50
-0.	-0.	-0.47462E 02	-0.49909E 02	-0.	-0.	2.54
-0.	-0.	-0.51698E 02	-0.60359E 02	-0.	-0.	2.58
-0.	-0.	-0.14665E 02	-0.71248E 02	-0.	-0.	2.65
-0.	-0.	-0.11443E 02	-0.90096E 02	-0.	-0.	2.70
-0.	-0.	-0.13919E 02	-0.12441E 03	-0.	-0.	2.80
-0.	-0.	-0.35313E 02	-0.14187E 03	-0.	-0.	2.90
-0.	-0.	-0.53425E 02	-0.13914E 03	-0.	-0.	3.10
-0.	-0.	-0.79631E 02	-0.16834E 03	-0.	-0.	3.20
-0.	-0.	-0.10079E 03	-0.17203E 03	-0.	-0.	3.26
-0.	-0.	-0.11498E 03	-0.17178E 03	-0.	-0.	3.29
-0.	-0.	-0.14258E 03	-0.13931E 03	-0.	-0.	3.35
-0.	-0.	-0.16954E 03	-0.19683E 03	-0.	-0.	3.46
-0.	-0.	-0.18403E 03	-0.21296E 03	-0.	-0.	3.52
-0.	-0.	-0.21710E 03	-0.22387E 03	-0.	-0.	3.56
-0.	-0.	-0.25812E 03	-0.22324E 03	-0.	-0.	3.60
-0.	-0.	-0.40206E 03	0.21689E 02	-0.	-0.	3.70
-0.	0.	-0.35924E 03	0.[illegible]701E 03	0.	0.	3.85
-0.	0.	-0.63481E 03	0.[illegible]78F 03	-0.	0.	4.00
0.	-0.	0.47463[illegible] 03	-0.1836[illegible] 03	0.	-0.	4.20
0.	0.	0.77330F 02	0.33971E [illegible]	0.	0.	4.50
-0.	0.	-0.47036E 02	0.49872E 02	-0.	0.	4.70
-0.	0.	-0.18377E 02	0.76346E 02	-0.	0.	4.80
0.	0.	0.17586F 02	0.74433E 02	0.	0.	4.96
0.	0.	0.24010E 02	0.43590E 02	0.	0.	5.00
0.	0.	0.39459F 02	0.49948F 02	0.	0.	5.15
0.	0.	0.47425F 02	0.33203E 02	0.	0.	5.30
0.	0.	0.50569E 02	0.18212E 02	0.	0.	[illegible]
0.	0.	0.48819E 02	0.89888E 01	0.	0.	5.70
0.	0.	0.45827E 02	0.49444E-00	0.	0.	5.85
0.	-0.	0.41318E 02	-0.86580E 00	0.	-0.	6.00
0.	-0.	0.40432F 02	-0.21520F 01	0.	-0.	6.03
0.	-0.	0.39515E 02	-0.34247E 01	0.	-0.	6.06
0.	-0.	0.38569E 02	-0.87508E 01	0.	-0.	6.08
0.	-0.	0.33968E 02	-0.18183E 02	0.	-0.	6.20
0.	-0.	0.24967F 02	-0.22000E 02	0.	-0.	6.40
0.	-0.	0.13719F 02	-0.24904E 02	0.	-0.	6.60
-0.	0.	-0.21693E 02	0.37364F 02	-0.	0.	7.00
-0.	0.	-0.77494F 02	0.12184E 02	-0.	0.	7.60
0.	-0.	0.95470F 02	-0.17787E 02	0.	-0.	8.20
-0.	-0.	-0.15572E 02	-0.10826E 02	-0.	-0.	9.00
-0.	0.	-0.14218E 02	0.	-0.	0.	10.00

Table XIX Stress Frequency Response Functions (Analysis Condition 5)

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.50

PERCENT SEMI SPAN: 27 SEGMENT NUMBER 10

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				FREQUENCY CPS
REAL	IMAGINARY	REAL	IMAGINARY			
0.586288E 00	-0.677016E 00	-0.771316E 01	0.563036E 01	0.	-0.	0.10
0.341146E 02	-0.913468E 01	0.319233E 33	-0.732606E 02	-0.	0.	0.30
0.232629E 02	-0.197796E 02	0.262716E 03	-0.109756E 03	-0.	0.	0.56
0.273798E 02	-0.1630 02	0.211396E 03	-0.125086E 03	-0.	0.	0.44
0.204796E 02	-0.163228E 02	0.187126E 03	-0.147176E 03	-0.	0.	0.50
0.176706E 02	-0.184507E 02	0.[illegible]E 03	-0.169446E 03	-0.	0.	0.60
0.159678E 02	-0.212786E 02	0.144546E 33	-0.196596E 03	-0.	0.	0.70
0.144746E 02	-0.249886E 02	0.129846E 03	-0.231486E 03	-0.	0.	0.80
0.131106E 02	-0.305146E 02	0.115276E 03	-0.281296E 03	-0.	0.	0.90
0.115606E 02	-0.551606E 02	0.957336E 02	-0.487986E 03	-0.	0.	1.00
0.273586E 01	-0.107406E 03	0.152776E 01	-0.979746E 03	0.	0.	1.20
0.726506E 02	-0.673736E 02	-0.539716E 03	-0.485386E 03	0.	-0.	1.34
0.187946E 03	0.744636E 02	-0.141636E 04	0.570926E 03	0.	-0.	1.40
0.151086E 03	0.860526E 02	-0.111796E 04	0.712326E 03	-0.	-0.	1.45
0.107056E 03	0.873096E 02	-0.810326E 03	0.697466E 03	-0.	0.	1.47
0.733396E 02	0.761506E 02	-0.537346E 03	0.560756E 03	-0.	0.	1.50
0.510926E 02	0.613096E 02	-0.361736E 03	0.439936E 03	-0.	0.	1.55
0.374296E 02	0.518966E 02	-0.111336E 03	0.342726E 03	-0.	0.	1.60
0.797886E 01	0.365826E 02	-0.693156E 02	0.205496E 03	-0.	0.	1.65
0.509866E 02	0.319116E 02	0.251366E 02	0.156076E 03	0.	0.	1.80
0.402536E 02	0.292666E 02	0.360516E 02	0.118256E 03	0.	0.	1.90
0.355466E 02	0.279166E 02	0.430746E 02	0.923406E 02	0.	0.	2.00
0.327466E 02	0.265176E 02	0.478116E 02	0.726606E 02	0.	0.	2.10
0.309086E 02	0.962756E 01	0.506796E 02	0.563966E 02	0.	0.	2.20
0.295596E 02	0.456306E 01	0.526446E 02	0.511006E 02	0.	0.	2.30
0.561346E 02	-0.433076E 01	0.274186E 32	0.421376E 02	0.	-0.	2.35
0.686086E 02	-0.195726E 02	0.173876E 02	0.600846E 02	0.	-0.	2.40
0.761366E 02	-0.245796E 02	0.122396E 02	0.657746E 02	0.	-0.	2.45
0.765356E 02	-0.458636E 02	0.122656E 02	0.779136E 02	0.	-0.	2.44
0.662106E 02	-0.511476E 02	0.215976E 02	0.778956E 02	0.	-0.	2.47
0.575806E 02	-0.572436E 02	0.379196E 02	0.694266E 02	0.	-0.	2.50
0.406586E 02	-0.890366E 02	0.508176E 32	0.527226E 02	0.	-0.	2.54
0.244536E 02	-0.138676E 03	0.530616E 02	0.429736E 02	0.	-0.	2.58
0.364506E 02	-0.765946E 02	0.466356E 02	0.414066E 02	-0.	-0.	2.65
0.723636E 02	-0.193866E 02	0.472786E 02	0.345056E 02	-0.	-0.	2.70
0.833796E 02	0.638186E 01	0.500126E 02	0.232726E 02	-0.	0.	2.80
0.454236E 02	0.117936E 02	0.555636E 02	0.179576E 02	-0.	0.	3.00
0.366256E 02	0.176826E 02	0.536756E 02	0.[illegible]95286E 01	-0.	0.	3.10
0.[illegible]366E 01	0.280346E 02	0.830366E 32	-0.284186E 02	-0.	0.	3.20
0.449076E 02	0.417996E 02	[illegible]97796E 32	-0.[illegible]06476E 02	-0.	0.	3.26
0.645136E 02	0.665186E 02	[illegible]130E 02	-0.799206E 02	-0.	0.	3.29
0.290186E 02	0.765866E 02	0.327856E 02	-0.552996E 02	-0.	0.	3.35
0.506236E 01	0.647716E 02	0.550636E 01	-0.224916E 02	-0.	0.	3.46
0.925116E 02	-0.130106E 32	0.159656E 31	-0.182276E 02	0.	-0.	3.52
0.877126E 02	-0.370466E 02	0.513646E 01	-0.170526E 02	0.	-0.	3.56
0.513736E 02	-0.269826E 02	0.747166E 01	-0.162336E 02	0.	-0.	3.60
0.793826E 01	-0.120346E 02	0.891196E 01	-0.162086E 32	-0.	-0.	3.70
0.644836E 01	-0.481946E 01	0.857396E 01	-0.172496E 02	-0.	-0.	3.85
0.447776E 01	-0.433816E 01	0.774746E 01	-0.194086E 02	-0.	0.	4.00
0.617656E 01	0.365096E 01	0.358736E 01	-0.245866E 02	-0.	0.	4.20
0.429466E 01	0.466776E 01	-0.662576E 01	-0.286326E 02	-0.	0.	4.30
0.284676E 01	0.499746E 01	-0.241826E 02	-0.286766E 02	0.	0.	4.70
0.171876E 01	0.430156E 01	-0.439736E 02	0.476806E 02	0.	-0.	4.80
0.[illegible]E-01	0.393816E 01	-0.776956E 02	0.747166E 02	0.	-0.	4.96
0.179286E-00	0.436766E 01	-0.496636E 32	0.471786E 02	0.	-0.	5.00
0.233736E-00	0.466206E 01	0.197536E 02	0.212786E 02	-0.	-0.	5.15
0.715626E 00	0.456396E 01	0.243176E 02	0.818416E 01	-0.	0.	5.30
0.[illegible]E 02	0.390016E 01	0.223166E 32	0.127346E 01	-0.	0.	[illegible]
0.[illegible]E 01	0.253436E 01	0.[illegible]E 02	-0.428296E 01	-0.	0.	5.70
0.621126E 01	-0.366976E 01	0.252156E 02	-0.239406E 02	-0.	0.	5.85
0.[illegible]E 02	-0.602696E 01	0.303816E 02	-0.307026E 02	0.	0.	6.00
0.[illegible]E 01	-0.869[illegible]E 01	0.282376E 02	-0.382916E 02	0.	0.	6.05
0.[illegible]E 01	-0.101096E 02	0.224446E 02	-0.432216E 02	0.	-0.	6.06
0.366916E 01	-0.291706E 01	0.125956E 32	-0.212616E 02	-0.	0.	6.08
0.[illegible]E 01	0.171506E 01	-0.146586E 02	-0.428166E 01	-0.	0.	6.20
0.[illegible]E 01	0.209886E 01	-0.773176E 01	-0.383216E 01	-0.	0.	6.46
0.[illegible]E-02	0.153316E 01	-0.[illegible]E 01	-0.263026E 01	0.	0.	6.66
0.[illegible]E 01	0.765946E 00	-0.292326E 01	-0.[illegible]E 01	0.	0.	7.00
0.[illegible]E 01	-0.[illegible]E-00	-0.262296E 01	0.376096E-01	0.	-0.	7.46
0.[illegible]E 01	-0.109706E 01	-0.[illegible]E 01	0.833136E 00	0.	-0.	8.20
0.979286E 00	-0.[illegible]E 01	-0.[illegible]E 01	0.[illegible]E 00	0.	-0.	9.00
0.[illegible]E-00	0.	-0.[illegible]E-00	0.	-0.	0.	10.00

Table XIX --- Continued

(PSI/PS SINUSOIDAL GUSTI

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.50

PERCENT SEMISPAN 27 SEGMENT NUMBER 14

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				FREQUENCY
REAL	IMAGINARY	REAL	IMAGINARY			CPS
-0.21933E 01	0.24398E-00	-0.49995E 01	0.51093E 01	0.	-0.	0.10
0.10818E 01	-0.23679E 02	0.28955E 01	-0.56482E 02	-0.	0.	0.30
0.49248E 02	-0.37185E 02	0.23941E 03	-0.99592E 02	-0.	0.	0.50
0.70908E 02	-0.42091E 02	0.19234E 03	-0.11423E 03	-0.	0.	0.70
0.62334E 02	-0.48514E 02	0.15981E 03	-0.13356E 03	-0.	0.	0.90
0.53491E 02	-0.55296E 02	0.14692E 03	-0.19376E 03	-0.	0.	0.90
0.48263E 02	-0.63688E 02	0.13125E 03	-0.17840E 03	-0.	0.	0.90
0.43649E 02	-0.74619E 02	0.11792E 03	-0.21006E 03	-0.	0.	0.80
0.39741E 02	-0.90527E 02	0.10463E 03	-0.25527E 03	-0.	0.	0.90
0.33899E 02	-0.15525E 03	0.87763E 02	-0.44283E 03	-0.	0.	1.00
0.57572E 01	-0.29304E 03	0.13844E 31	-0.79834E 03	0.	0.	1.20
-0.14441E 01	-0.17107E 03	-0.48377E 03	-0.43865E 03	0.	-0.	1.34
-0.66096E 01	0.17790E 03	-0.12671E 04	0.51810E 01	0.	-0.	1.40
-0.39533E 01	0.22944E 03	-0.13709E 04	0.64641E 03	-0.	-0.	1.45
-0.27505E 01	0.22927E 03	-0.73577E 03	0.63293E 01	-0.	0.	1.47
-0.19493E 01	0.19750E 03	-0.48817E 31	0.53887E 03	-0.	0.	1.50
-0.84974E 02	0.14983E 03	-0.21935E 03	0.39923E 03	-0.	0.	1.55
-0.60327E 02	0.12761E 03	-0.10259E 03	0.32008E 03	-0.	0.	1.60
-0.17441E 01	0.76512E 02	-0.44752E 02	0.19648E 03	-0.	0.	1.65
0.10491E 02	0.60980E 02	0.18264E 02	0.13981E 03	0.	0.	1.80
0.18802E 02	0.50621E 02	0.30901E 02	0.10731E 03	0.	0.	1.90
0.29724E 02	0.43900E 02	0.36347E 02	0.83605E 02	0.	0.	2.00
0.33541E 02	0.37342E 02	0.37942E 02	0.65738E 02	0.	0.	2.10
0.45887E 02	0.15681E 02	0.36733E 02	0.51178E 02	0.	0.	2.20
0.66104E 02	0.92765E 01	0.31267E 02	0.46372E 02	0.	0.	2.30
0.61585E 02	-0.43501E 00	0.25264E 02	0.47313E 02	0.	-0.	2.35
0.77014E 02	-0.15188E 02	0.19779E 02	0.54525E 02	0.	-0.	2.40
0.83658E 02	-0.23420E 02	0.11136E 02	0.59689E 02	0.	-0.	2.45
0.86088E 02	-0.38899E 02	0.11111E 02	0.70341E 02	0.	-0.	2.44
0.77779E 02	-0.44857E 02	0.19539E 02	0.70688E 02	0.	-0.	2.47
0.71623E 02	-0.54661E 02	0.14410E 02	0.59370E 02	0.	-0.	2.30
0.79428E 02	-0.99629E 02	0.44115E 02	0.47844E 02	0.	-0.	2.50
0.87114E 02	-0.16091E 03	0.48134E 02	0.39002E 02	0.	-0.	2.58
-0.36834E 02	-0.88548E 02	0.42133E 02	0.37650E 02	-0.	-0.	2.65
-0.86276E 02	-0.24137E 02	0.42934E 02	0.33316E 02	-0.	-0.	2.70
-0.70064E 02	0.57482E 00	0.45385E 02	0.21118E 02	-0.	0.	2.80
-0.50714E 02	0.54294E 01	0.50422E 02	0.16296E 02	-0.	0.	3.00
-0.54192E 02	0.17434E 02	0.47284E 02	0.35871E 01	-0.	0.	3.10
-0.73160E 02	0.50514E 02	0.75155E 02	-0.25789E 02	-0.	0.	3.20
-0.99908E 02	0.89906E 02	0.88747E 02	-0.55036E 02	-0.	0.	3.26
-0.92931E 02	0.13375E 03	0.80856E 02	-0.71709E 02	-0.	0.	3.29
-0.32908E 02	0.12796E 03	0.29753E 02	-0.55183E 02	-0.	0.	3.30
0.15367E 02	0.67227E 02	0.50821E 01	-0.20376E 02	-0.	0.	3.60
0.13261E 01	-0.69256E 01	0.14449E 01	-0.16540E 02	0.	-0.	3.52
0.12548E 01	-0.38263E 02	0.46543E 01	-0.15510E 02	0.	-0.	3.56
0.81114E 02	-0.31249E 02	0.67401E 01	-0.14731E 02	0.	-0.	3.60
0.26273E 02	-0.17925E 02	0.60873E 01	-0.14708E 02	-0.	-0.	3.70
0.86497E 01	-0.12662E 02	0.77853E 01	-0.15653E 02	-0.	-0.	3.80
0.13301E 01	-0.99900E 01	0.61954E 01	-0.17694E 02	-0.	0.	3.88
-0.23904E-00	-0.10458E 02	0.12551E 01	-0.22311E 02	-0.	0.	4.00
-0.58184E 01	-0.12172E 02	-0.60127E 01	-0.25983E 02	-0.	0.	4.10
-0.15305E 02	-0.10692E 02	-0.21945E 02	-0.26026E 02	0.	0.	4.20
-0.26437E 02	0.32698E 02	-0.39932E 02	0.43269E 02	0.	-0.	4.30
-0.65451E 02	0.48479E 02	-0.73537E 02	0.67803E 02	0.	-0.	4.96
-0.28911E 02	0.32326E 02	-0.45069E 02	0.42813E 02	0.	-0.	5.02
0.12220E 02	0.17012E 02	0.17935E 02	0.19309E 02	-0.	-0.	5.15
0.14489E 02	0.95862E 01	0.22067E 02	0.74269E 01	-0.	0.	5.30
0.15103E 02	0.43965E 01	0.20794E 02	0.11556E 01	-0.	0.	5.40
0.15900E 02	0.45885E-00	0.20231E 02	-0.38866E 01	-0.	0.	5.70
0.18419E 02	-0.13037E 02	0.22901E 02	-0.21362E 02	-0.	0.	5.8
0.22431E 02	-0.18089E 02	0.27573E 02	-0.27936E 02	0.	0.	6.00
0.21033E 02	-0.23139E 02	0.25624E 02	-0.34749E 02	0.	0.	6.05
0.17123E 02	-0.26820E 02	0.20385E 02	-0.39222E 02	0.	-0.	6.08
0.10837E 02	-0.11940E 02	0.11433E 02	-0.19296E 02	-0.	0.	6.08
-0.81683E 01	-0.19676E 01	-0.13120E 02	-0.57002E 01	-0.	0.	6.08
-0.32929E 01	-0.63879E 00	-0.70141E 31	-0.34775E 01	-0.	0.	6.66
-0.92626E 00	-0.42853E-00	-0.41389E 01	-0.22108E 31	0.	0.	6.80
0.54355E-00	-0.46600E-00	-0.26501E 01	-0.13882E 01	0.	0.	7.00
0.49492E-00	-0.32562E-00	-0.23932E 01	0.33948E-01	0.	-0.	7.60
0.37053E-00	-0.13961E-00	-0.18764E 31	0.75605E 00	0.	-0.	8.00
0.41144E-00	-0.20479E-00	-0.98685E 00	0.72689E 00	0.	-0.	9.00
0.69494E 00	0.	-0.15226E-00	0.	-0.	0.	10.00

Table XIX - - - Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.50

PERCENT SEMISPAN: 40.06 SEGMENT NUMBER 8

INCREMENTAL SHEAR STRESS		INCREMENTAL AXIAL STRESS				FREQUENCY CPS
REAL	IMAGINARY	REAL	IMAGINARY			
-0.147108E 01	0.529838E-01	-0.901965E 01	0.635078E 01	-0.	-0.	0.10
0.752898E 02	-0.168811E 02	0.107888E 03	-0.736988E 02	0.	-0.	0.30
0.[illegible]466E 02	-0.244928E 02	0.253998E 03	-0.106868E 03	0.	-0.	0.50
0.442628E 02	-0.273198E 02	0.204928E 03	-0.123038E 03	0.	-0.	0.64
0.[illegible]847E 02	-0.323568E 02	0.188768E 03	-0.144368E 03	0.	-0.	0.90
0.[illegible]507E 02	-0.372498E 02	0.155938E 03	-0.180528E 03	0.	-0.	0.60
0.320028E 02	-0.436148E 02	0.138578E 03	-0.193368E 03	0.	-0.	0.70
0.291478E 02	-0.515838E 02	0.121778E 03	-0.227998E 03	0.	-0.	0.80
0.263838E 02	-0.639478E 02	0.108618E 03	-0.276258E 03	0.	-0.	0.90
0.228558E 02	-0.115618E 03	0.896758E 02	-0.477028E 03	0.	-0.	1.00
0.[illegible]663E 01	-0.220548E 03	-0.644636E 01	-0.852978E 03	0.	-0.	1.20
-0.[illegible]33E 01	-0.[illegible]83E 03	-3.[illegible]33E 03	-0.[illegible]466E 03	-0.	-0.	1.34
-0.[illegible]900E 01	0.[illegible]71E 03	-0.[illegible]97AE 04	0.[illegible]884E 03	-0.	0.	1.40
-0.[illegible]922E 01	0.[illegible]34E 03	-0.[illegible]49E 04	0.[illegible]268E 03	-0.	0.	1.45
-0.[illegible]845E 01	0.[illegible]93E 03	-0.[illegible]39E 03	0.[illegible]524E 03	-0.	0.	1.47
-0.[illegible]569E 01	0.[illegible]97E 03	-3.[illegible]94E 03	0.[illegible]81E 03	-0.	0.	1.50
-0.[illegible]465E 02	0.125008E 03	-3.[illegible]13E 03	0.42975E 03	-0.	0.	1.55
-0.[illegible]08E 02	0.[illegible]01E 03	-0.[illegible]46E 03	0.[illegible]21E 03	-0.	0.	1.60
-0.[illegible]89E 02	0.690[illegible]E 02	-3.[illegible]24E 02	0.200698E 03	-0.	0.	1.65
0.[illegible]65E 01	0.[illegible]38E 02	0.[illegible]03E 02	0.[illegible]05E 03	0.	0.	1.80
0.[illegible]79E 02	0.[illegible]27E 02	0.[illegible]33E 02	0.[illegible]46E 03	0.	0.	1.90
0.[illegible]07E 02	0.[illegible]04E 02	0.[illegible]71E 02	0.[illegible]63E 02	0.	0.	2.00
0.[illegible]96E 02	0.[illegible]33E 02	0.[illegible]21E 02	0.[illegible]97E 02	0.	0.	2.10
0.[illegible]73E 02	0.[illegible]66E 02	0.[illegible]47E 02	0.[illegible]25E 02	0.	0.	2.20
0.[illegible]09E 02	0.[illegible]67E 02	0.[illegible]13E 01	0.[illegible]15E 02	0.	0.	2.30
0.[illegible]94E 02	0.[illegible]49E 02	0.[illegible]79E 02	0.[illegible]69E 02	0.	0.	2.35
0.[illegible]66E 02	0.[illegible]72E 01	0.[illegible]94E 01	0.[illegible]39E 02	0.	-0.	2.40
0.[illegible]13E 02	-0.[illegible]33E 01	0.[illegible]61E 01	0.[illegible]41E 02	0.	-0.	2.45
0.[illegible]87E 02	-0.[illegible]77E 02	0.[illegible]39E 01	0.[illegible]13E 02	0.	-0.	2.44
0.[illegible]83E 02	-0.[illegible]66E 02	0.[illegible]71E 01	0.[illegible]73E 02	0.	-0.	2.47
0.[illegible]64E 02	-0.[illegible]17E 02	0.[illegible]85E 02	0.[illegible]93E 02	0.	-0.	2.50
0.[illegible]33E 02	-0.[illegible]00E 02	0.[illegible]29E 02	0.[illegible]11E 03	0.	-0.	2.54
0.[illegible]48E 02	-0.[illegible]97E 02	0.[illegible]66E 02	0.[illegible]87E 03	0.	-0.	2.58
-0.[illegible]52E 01	-0.[illegible]73E 02	0.[illegible]69E 02	0.[illegible]39E 02	-0.	-0.	2.65
-0.[illegible]93E 02	0.[illegible]6E 01	0.[illegible]31E 02	0.[illegible]62E 02	-0.	-0.	2.70
-0.[illegible]28E 02	0.[illegible]95E 02	0.[illegible]71E 02	0.[illegible]52E 02	-0.	0.	2.80
0.[illegible]51E 02	0.[illegible]62E 02	0.[illegible]34E 03	0.[illegible]67E 02	0.	0.	3.00
0.[illegible]21E 02	0.[illegible]93E 01	0.[illegible]72E 03	0.[illegible]35E 02	0.	0.	3.10
0.[illegible]90E 02	-0.[illegible]02E 02	0.[illegible]47E 03	-0.[illegible]29E 02	0.	-0.	3.20
0.[illegible]73E 03	-0.[illegible]99E 03	0.[illegible]14E 03	-0.[illegible]78E 03	0.	-0.	3.26
0.[illegible]26E 03	-0.[illegible]96E 03	0.[illegible]27E 03	-0.[illegible]92E 03	0.	-0.	3.29
0.[illegible]62E 02	-0.[illegible]06E 03	0.[illegible]54E 02	-0.[illegible]63E 03	0.	-0.	3.35
-0.[illegible]59E 02	-0.[illegible]20E 02	-0.[illegible]61E 02	-0.[illegible]33E 02	-0.	-0.	3.40
-0.[illegible]58E 03	-0.[illegible]74E 01	-0.[illegible]53E 02	-0.[illegible]10E 02	-0.	-0.	3.52
-0.[illegible]77E 03	0.[illegible]3E 02	-0.[illegible]41E 02	-0.[illegible]28E 02	-0.	0.	3.56
-0.[illegible]40E 02	0.[illegible]20E 02	-0.[illegible]57E 02	-0.[illegible]03E 02	-0.	0.	3.60
-0.[illegible]76E 02	0.[illegible]91E 02	-0.[illegible]94E 02	-0.[illegible]59E 02	-0.	0.	3.70
-0.[illegible]78E 02	0.[illegible]09E 02	-0.[illegible]13E 02	-0.[illegible]89E 02	-0.	0.	3.85
-0.[illegible]06E 02	0.[illegible]83E 02	-0.[illegible]52E 02	-0.[illegible]01E 01	-0.	0.	4.00
-0.[illegible]96E 02	0.[illegible]00E 02	-0.[illegible]49E 02	0.[illegible]93E 00	-0.	0.	4.20
-0.[illegible]93E 01	0.[illegible]96E 02	-0.[illegible]52E 01	0.[illegible]23E 01	-0.	0.	4.30
0.[illegible]67E 01	0.[illegible]76E 02	0.[illegible]57E 01	0.[illegible]50F 01	0.	0.	4.70
0.[illegible]09E 02	-0.[illegible]13E 01	0.[illegible]72E 02	-0.[illegible]87E 02	0.	-0.	4.80
0.[illegible]96E 02	-0.[illegible]61E 02	0.[illegible]51E 02	-0.[illegible]70E 02	0.	-0.	4.96
0.[illegible]62E 02	0.[illegible]37E 01	0.[illegible]53E 02	-0.[illegible]38E 02	0.	-0.	5.00
-0.[illegible]77E 01	0.[illegible]39E 01	-0.[illegible]72E 02	-0.[illegible]30E 02	-0.	-0.	5.19
-0.[illegible]37E 01	0.[illegible]29E 01	-0.[illegible]33E 02	-0.[illegible]66E 01	-0.	0.	5.30
-0.[illegible]23E 01	0.[illegible]99E 01	-0.[illegible]54E 02	-0.[illegible]45E 01	-0.	0.	[illegible]
-0.[illegible]71E 01	0.[illegible]52E 01	-0.[illegible]65E 02	0.98607E-01	-0.	0.	5.70
-0.[illegible]98E 00	0.[illegible]19E 01	-0.[illegible]93E 01	-0.[illegible]76E 00	-0.	0.	5.85
-0.[illegible]17E 00	0.[illegible]52E 01	-0.[illegible]81E 01	-0.[illegible]20E 01	-0.	0.	6.00
-0.[illegible]30E-00	0.[illegible]6E 02	-0.[illegible]94E 01	-0.[illegible]57E 01	-0.	0.	6.05
0.[illegible]54E 00	0.[illegible]31E 02	-0.[illegible]63E 01	-0.[illegible]09E 01	-0.	0.	6.06
0.[illegible]59E 01	0.[illegible]79E 01	-0.[illegible]37E 01	0.[illegible]86E 01	-0.	0.	6.08
0.[illegible]55E 01	0.[illegible]19E 01	-0.[illegible]17E 01	0.[illegible]18E 01	0.	0.	6.20
0.[illegible]38E 01	0.[illegible]83E 01	-0.[illegible]47E 01	0.[illegible]45E 01	0.	0.	6.40
0.[illegible]80E 01	0.[illegible]31E 00	-0.[illegible]63E 01	0.[illegible]06E 01	0.	0.	6.60
0.[illegible]53E 01	-0.[illegible]20E 01	-0.[illegible]34E 01	0.[illegible]98E 01	0.	-0.	7.00
0.[illegible]07E 01	-0.[illegible]91E 01	0.[illegible]34E-00	0.[illegible]33E 01	0.	-0.	7.60
0.[illegible]62E 01	-0.[illegible]63E 01	0.[illegible]44E 01	-0.[illegible]59E 00	0.	-0.	8.20
0.[illegible]49E-00	-0.[illegible]65E 01	0.[illegible]19E 01	-0.[illegible]55E 01	0.	-0.	9.80
-0.[illegible]21E 01	0.	0.[illegible]79E-00	0.	-0.	0.	10.00

Table XIX – – – Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.50

PERCENT SEMISPAN: 40.06 SEGMENT NUMBER 107

INCREMENTAL SHEAR STRESS				INCREMENTAL AXIAL STRESS		
REAL	IMAGINARY			REAL	IMAGINARY	FREQUENCY CPS
-0.136698E 01	-0.104578E-01	-0.	-0.	0.684946E 01	-9.542628E 01	0.10
0.477488E 02	-0.161078E 02	0.	-0.	-0.263038E 03	0.604078E 02	0.30
0.549188E 02	-0.232928E 02	0.	-0.	-0.216928E 03	0.913028E 02	0.36
0.441798E 02	-0.244198E 02	0.	-0.	-0.175098E 03	0.105128E 03	0.46
0.390168E 02	-0.304308E 02	0.	-0.	-0.154438E 03	0.123358E 03	0.50
0.339168E 02	-0.351988E 02	0.	-0.	-0.133238E 03	0.142288E 03	0.60
0.304278E 02	-0.409688E 02	0.	-0.	-0.118498E 03	0.165198E 03	0.70
0.279538E 02	-0.486278E 02	0.	-0.	-0.105718E 03	0.199468E 03	0.80
0.252908E 02	-0.549808E 02	0.	-0.	-0.928018E 02	0.224678E 03	0.90
0.221398E 02	-0.608858E 03	0.	-0.	-0.264508E 02	0.407538E 03	1.00
0.914628E 01	-0.208018E 03	0.	-0.	0.586948E 01	0.725808E 03	1.20
-0.120998E 03	-0.122438E 03	-0.	-0.	0.441388E 03	0.990108E 03	1.34
-0.334188E 03	0.136748E 03	-0.	0.	0.119008E 04	-0.488048E 03	1.40
-0.290578E 03	0.172998E 03	-0.	0.	0.981618E 03	-0.690378E 03	1.45
-0.270308E 03	0.177818E 03	-0.	0.	0.677438E 03	-0.545648E 03	1.47
-0.137108E 03	0.143958E 03	-0.	0.	0.446068E 03	-0.468928E 03	1.50
-0.435608E 02	0.116958E 03	-0.	0.	0.200958E 03	-0.367198E 03	1.55
-0.303578E 02	0.972858E 02	-0.	0.	0.952368E 02	-0.294118E 03	1.60
-0.131708E 02	0.644558E 02	-0.	0.	0.434108E 02	-0.174068E 03	1.65
0.867758E 01	0.534768E 02	0.	0.	-0.116238E 02	-0.127068E 03	1.80
0.156098E 02	0.462278E 02	0.	0.	-0.216028E 02	-0.998788E 02	1.90
0.214978E 02	0.412798E 02	0.	0.	-0.247118E 02	-0.790048E 02	2.00
0.278198E 02	0.372418E 02	0.	0.	-0.234318E 02	-0.639948E 02	2.10
0.343818E 02	0.301978E 02	0.	0.	-0.167018E 02	-0.690598E 02	2.20
0.429718E 02	0.267498E 02	0.	0.	-0.634998E 01	-0.675988E 02	2.30
0.477188E 02	0.149978E 02	0.	0.	-0.115178E 02	-0.642518E 02	2.35
0.717408E 02	0.119928E 01	0.	-0.	-0.553628E 01	-0.207508E 02	2.40
0.778678E 02	-0.652908E 01	0.	-0.	-0.144928E 01	-0.748838E 02	2.43
0.781438E 02	-0.210628E 02	0.	-0.	-0.126798E 01	-0.831458E 02	2.44
0.712968E 02	-0.257158E 02	0.	-0.	-0.692498E 01	-0.841398E 02	2.47
0.630138E 02	-0.311368E 02	0.	-0.	-0.194528E 02	-0.858498E 02	2.50
0.655798E 02	-0.565988E 02	0.	-0.	-0.181388E 02	-0.898098E 02	2.54
0.702748E 02	-0.937628E 02	0.	-0.	-0.167898E 02	-0.105848E 03	2.58
-0.973098E 01	-0.447428E 02	-0.	-0.	-0.566238E 02	-0.806918E 02	2.65
-0.393058E 02	-0.115818E 01	-0.	-0.	-0.749608E 02	-0.559538E 02	2.70
-0.272488E 02	0.167518E 02	-0.	0.	-0.741408E 02	-0.446468E 02	2.80
0.174238E 02	0.177248E 02	0.	0.	-0.857378E 02	-0.403018E 02	3.00
0.352918E 02	0.193438E 01	0.	0.	-0.109988E 03	-0.121638E 02	3.10
0.787248E 02	-0.519948E 02	0.	-0.	-0.167018E 03	0.205818E 02	3.20
0.116988E 03	-0.112288E 03	0.	-0.	-0.212028E 03	0.157038E 03	3.26
0.107308E 03	-0.160018E 03	0.	-0.	-0.191588E 03	0.205858E 03	3.29
0.949868E 01	-0.127518E 03	0.	-0.	-0.406198E 02	0.136918E 03	3.35
-0.487998E 02	-0.531798E 02	-0.	-0.	0.312888E 02	0.491588E 02	3.40
-0.116678E 03	-0.406818E 01	-0.	-0.	0.223528E 02	0.457438E 02	3.52
-0.109338E 03	0.181698E 02	-0.	0.	0.161838E 02	0.447118E 02	3.56
-0.808868E 02	0.203428E 02	-0.	0.	0.179068E 02	0.312768E 02	3.60
-0.430238E 02	0.172468E 02	-0.	0.	0.196768E 02	0.188488E 02	3.70
-0.245718E 02	0.163798E 02	-0.	0.	0.161828E 02	0.116978E 02	3.85
-0.187018E 02	0.141498E 02	-0.	0.	0.130208E 02	0.581168E 01	4.00
-0.121778E 02	0.160868E 02	-0.	0.	0.981698E 01	-0.676568E 00	4.20
-0.440908E 01	0.159218E 02	-0.	0.	0.483558E 01	-0.447928E 01	4.50
0.418038E 00	0.151408E 02	0.	0.	-0.254368E 01	-0.470378E 01	4.70
0.447788E 01	0.362378E 01	0.	-0.	-0.103158E 02	0.218628E 02	4.80
0.109778E 02	0.360628E-00	0.	-0.	-0.219678E 02	0.319308E 02	4.96
0.725608E 01	0.913558E 01	0.	-0.	-0.136288E 02	0.207958E 02	5.00
-0.179138E 01	0.406598E 01	-0.	-0.	0.122808E 02	0.100228E 02	5.15
-0.416878E 00	0.676828E 01	-0.	-0.	0.136148E 02	0.404718E 01	5.30
0.111328E 01	0.638198E 01	-0.	0.	0.114108E 02	0.101218E 01	5.45
0.248178E 01	0.595078E 01	-0.	0.	0.918198E 01	-0.442538E 01	5.70
0.413528E 01	0.591108E 01	-0.	0.	0.250028E 01	0.993638E 00	5.85
0.342368E 01	0.603828E 01	-0.	0.	0.582888E 01	0.109958E 01	6.00
0.381498E 01	0.615818E 01	-0.	0.	0.590278E 01	0.158688E 01	6.03
0.414278E 01	0.614888E 01	-0.	0.	0.633678E 01	0.178218E 01	6.06
0.440718E 01	0.641828E 01	-0.	0.	0.214058E 01	0.332328E 01	6.08
0.586868E 01	0.302828E 01	0.	0.	0.852018E 01	-0.338518E 01	6.20
0.597528E 01	0.190668E 01	0.	0.	0.611208E 01	-0.399098E 01	6.40
0.588638E 01	-0.566298E-01	0.	0.	0.446508E 01	-0.431898E 01	6.60
0.560818E 01	-0.166188E 01	0.	-0.	0.192548E 01	0.260368E 01	7.00
0.488628E 01	-0.362878E 01	0.	-0.	0.120348E-00	0.165198E 01	7.40
0.354908E 01	-0.378568E 01	0.	-0.	-0.161[illegible]	0.889198E-00	8.20
-0.580058E-01	-0.218938E 01	0.	-0.	-0.193[illegible] 01	0.196708E 01	9.00
-0.209218E 01	0.	-0.	0.	-0.184[illegible]E-00	0.	10.00

Table XIX --- Continued

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 3 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.50

BODY BALANCE STATION: 540 SEGMENT NUMBER 17

INCREMENTAL SHEAR STRESS

REAL	IMAGINARY					FREQUENCY CPS
-0.413A2E-00	0.218**E 01	0.	-0.	0.	-0.	0.10
-0.170556 02	0.475256 01	0.	-0.	0.	-0.	0.20
-0.123536 02	0.510646 01	0.	-0.	0.	-0.	0.30
-0.101396 02	0.501926 01	0.	-0.	0.	-0.	0.40
-0.917326 01	0.46[illegible]E 01	0.	-0.	0.	-0.	0.50
-0.842876 01	0.[illegible] 01	0.	-0.	0.	-0.	0.60
-0.829776 01	0.546096 01	0.	-0.	0.	-0.	0.70
-0.843126 01	0.587836 01	0.	-0.	0.	-0.	0.80
-0.888226 01	0.[illegible]E 01	0.	-0.	0.	-0.	0.90
-0.893326 01	0.150416 02	0.	-0.	0.	-0.	1.00
-0.617706 01	0.272506 02	0.	-0.	0.	-0.	1.10
0.394876 01	0.195916 02	-0.	-0.	-0.	-0.	1.20
0.265866 02	-0.[illegible]E 01	-0.	0.	-0.	0.	1.30
0.223256 02	-0.108306 02	-0.	0.	-0.	0.	1.40
0.131566 02	-0.106606 02	-0.	0.	-0.	0.	1.50
0.816096 01	-0.706196 01	-0.	0.	-0.	0.	1.60
-0.176556 01	-0.368726 01	0.	-0.	0.	0.	1.70
-0.535926 01	-0.[illegible]E 00	0.	-0.	0.	-0.	1.80
-0.723716 01	0.[illegible]E 01	0.	-0.	0.	-0.	1.90
-0.937666 01	0.[illegible]E 01	0.	-0.	0.	-0.	2.00
-0.961316 01	0.120246 02	0.	-0.	0.	-0.	2.10
-0.949476 01	0.151116 02	0.	-0.	0.	-0	2.20
-0.913096 01	0.183916 02	0.	-0.	0.	-0	2.30
-0.872536 01	0.231426 02	0.	-0.	0.	-0.	2.40
-0.811136 01	0.253156 02	0.	-0.	0.	-0.	2.50
-0.[illegible]E 01	0.276706 02	0.	-0.	0.	-0.	2.60
-0.627266 01	0.292456 02	0.	-0.	0.	-0.	2.70
-0.577006 01	0.299396 02	0.	-0.	0.	-0.	2.80
-0.[illegible]E 01	0.311976 02	0.	-0.	0.	-0.	2.90
-0.519026 01	0.329356 02	0.	-0.	0.	-0.	3.00
-0.[illegible]E 01	0.[illegible]E 02	0.	-0.	0.	-0.	3.10
-0.757166 01	0.[illegible]E 02	0.	-0.	0.	-0.	3.20
-0.[illegible]E 01	0.[illegible]E 02	0.	-0.	0.	-0.	3.30
0.191336 02	0.[illegible]E 02	-0.	-0.	-0.	-0.	3.40
0.311206 02	0.[illegible]E 02	-0.	-0.	-0.	-0.	3.50
0.369496 02	0.[illegible]E 02	-0.	-0.	-0.	-0.	3.60
0.[illegible]E 02	0.[illegible]E 02	-0.	-0.	-0.	-0.	3.70
0.108766 03	0.[illegible]E 02	-0.	-0.	-0.	-0.	3.80
0.196316 03	-0.[illegible]E 02	-0.	0.	-0.	0.	3.90
0.[illegible]E 03	-0.[illegible]E 03	-0.	0.	-0.	0.	4.00
0.[illegible]E 03	-0.[illegible]E 03	-0.	0.	-0.	0.	4.10
0.272966 02	-0.[illegible]E 03	-0.	0.	-0.	0.	4.20
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	4.30
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	4.40
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	4.50
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	4.60
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	4.70
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	4.80
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	4.90
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	5.00
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	5.10
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	5.20
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	5.30
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	5.40
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	5.50
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	5.60
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	5.70
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	5.80
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	5.90
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	6.00
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	6.10
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	6.20
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	6.30
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	6.40
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	6.50
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	6.60
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	6.70
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	6.80
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	6.90
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	7.00
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	7.10
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	7.20
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	7.30
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	7.40
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	7.50
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	7.60
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	7.70
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	7.80
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	7.90
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	8.00
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	8.10
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	8.20
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	8.30
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	8.40
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	8.50
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	8.60
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	8.70
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	8.80
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	8.90
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	9.00
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	9.10
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	9.20
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	9.30
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	9.40
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	9.50
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	9.60
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	9.70
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	9.80
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	9.90
-0.[illegible]E 02	-0.[illegible]E 02	0.	0.	0.	0.	10.00

Table XIX – – – Concluded

(PSI/FPS SINUSOIDAL GUST)

GROSS WEIGHT: 297,000 LB CUTOFF FREQUENCY: 10 CPS
ALTITUDE: 24,000 FT
MACH NUMBER: 0.50

BODY BALANCE STATION: 820 SEGMENT NUMBER 1

		INCREMENTAL AXIAL STRESS				FREQUENCY
		REAL	IMAGINARY			CPS
-0.	-0.	-0.665327E 00	-0.373947E 01	-0.	-0.	0.10
0.	-0.	0.111113E 03	-0.273427E 02	0.	-0.	0.30
0.	-0.	0.894632E 02	-0.365707E 02	0.	-0.	0.36
0.	-0.	0.727351E 02	-0.403611E 02	0.	-0.	0.44
0.	-0.	0.667756E 02	-0.459865E 02	0.	-0.	0.50
0.	-0.	0.582756E 02	-0.528307E 02	0.	-0.	0.60
0.	-0.	0.564931E 02	-0.621099E 02	0.	-0.	0.70
0.	-0.	0.526777E 02	-0.747311E 02	0.	-0.	0.80
0.	-0.	0.501855E 02	-0.931737E 02	0.	-0.	0.90
0.	-0.	0.456033E 02	-0.169799E 03	0.	-0.	1.00
0.	-0.	0.184322E 02	-0.308107E 03	0.	-0.	1.20
-0.	-0.	-0.166453E 03	-0.173677E 03	-0.	-0.	1.34
-0.	0.	-0.465556E 03	0.186899E 03	-0.	0.	1.40
-0.	0.	-0.382335E 03	0.234277E 03	-0.	0.	1.45
-0.	0.	-0.254722E 03	0.227888E 03	-0.	0.	1.47
-0.	0.	-0.150511E 03	0.178247E 03	-0.	0.	1.50
-0.	0.	-0.594449E 02	0.134007E 03	-0.	0.	1.55
-0.	0.	-0.139178E 02	0.101721E 03	-0.	0.	1.60
0.	0.	0.809951E 01	0.413277E 02	0.	0.	1.65
0.	0.	0.311133E 02	0.168867E 02	0.	0.	1.80
0.	-0.	0.361133E 02	-0.299709E 01	0.	-0.	1.90
0.	-0.	0.331107E 02	-0.220647E 02	0.	-0.	2.00
0.	-0.	0.288035E 02	-0.355159E 02	0.	-0.	2.10
0.	-0.	0.270227E 02	-0.436787E 02	0.	-0.	2.20
0.	-0.	0.533987E 01	-0.486637E 02	0.	-0.	2.30
-0.	-0.	-0.790345E-01	-0.495046E 02	-0.	-0.	2.35
-0.	-0.	-0.169135E 02	-0.461746E 02	-0.	-0.	2.40
-0.	-0.	-0.215993E 02	-0.399222E 02	-0.	-0.	2.43
-0.	-0.	-0.226156E 02	-0.246397E 02	-0.	-0.	2.44
-0.	-0.	-0.162594E 02	-0.262197E 02	-0.	-0.	2.47
0.	-0.	0.584613E 00	-0.421317E 02	0.	-0.	2.50
0.	-0.	0.968113E 01	-0.577217E 02	0.	-0.	2.54
0.	-0.	0.659331E 01	-0.733097E 02	0.	-0.	2.58
-0.	-0.	-0.170111E 02	-0.801017E 02	-0.	-0.	2.65
-0.	-0.	-0.123647E 02	-0.972177E 02	-0.	-0.	2.70
-0.	-0.	-0.614098E 02	-0.131617E 03	-0.	-0.	2.80
-0.	-0.	-0.136437E 03	-0.137537E 03	-0.	-0.	3.00
-0.	-0.	-0.239337E 03	-0.557567E 02	-0.	-0.	3.10
-0.	0.	-0.459457E 03	0.228717E 03	-0.	0.	3.20
-0.	0.	-0.493557E 03	0.532287E 03	-0.	0.	3.26
-0.	0.	-0.566657E 03	0.705447E 03	-0.	0.	3.29
-0.	0.	-0.602997E 03	0.657557E 03	-0.	0.	3.35
0.	0.	0.209337E 03	0.142427E 03	0.	0.	3.45
0.	0.	0.157117E 03	0.140957E 03	0.	0.	3.52
0.	0.	0.133537E 03	0.130767E 03	0.	0.	3.56
0.	0.	0.141237E 03	0.751637E 02	0.	0.	3.60
0.	0.	0.142487E 03	0.236997E 02	0.	0.	3.70
0.	-0.	0.119377E 03	-0.518257E 01	0.	-0.	3.85
0.	-0.	0.963737E 02	-0.263777E 02	0.	-0.	4.00
0.	-0.	0.685557E 02	-0.426447E 02	0.	-0.	4.20
0.	-0.	0.359137E 02	-0.479467E 02	0.	-0.	4.30
0.	-0.	0.131567E 02	-0.475517E 02	0.	-0.	4.70
-0.	-0.	-0.226337E 01	-0.142637E 02	-0.	-0.	4.80
-0.	-0.	-0.264377E 02	-0.211997E 01	-0.	-0.	4.96
-0.	-0.	-0.166557E 02	-0.133587E 02	-0.	-0.	5.00
0.	-0.	0.629127E 01	-0.226287E 02	0.	-0.	5.15
0.	-0.	0.176987E-00	-0.241667E 02	0.	-0.	5.30
-0.	-0.	-0.116767E 02	-0.198037E 02	-0.	-0.	5.50
-0.	-0.	-0.255567E 02	-0.100337E 02	-0.	-0.	5.70
-0.	0.	-0.493327E 02	0.336827E 02	-0.	0.	5.85
-0.	0.	-0.585297E 02	0.503607E 02	-0.	0.	6.00
-0.	0.	-0.563667E 02	0.675727E 02	-0.	0.	6.09
-0.	0.	-0.417237E 02	0.767107E 02	-0.	0.	6.06
-0.	0.	-0.194797E 02	0.275647E 02	-0.	0.	6.00
0.	-0.	0.383117E 02	-0.505597E 01	0.	-0.	6.20
0.	-0.	0.171767E 02	-0.818177E 01	0.	-0.	6.40
0.	-0.	0.603697E 01	-0.804037E 01	0.	-0.	6.60
-0.	-0.	-0.207347E 01	-0.971717E 01	-0.	-0.	7.00
-0.	-0.	-0.419767E 01	-0.952367E 00	-0.	-0.	7.60
-0.	-0.	-0.426457E 01	-0.764827E-02	-0.	-0.	8.20
-0.	0.	-0.416537E 01	0.134607E 01	-0.	0.	9.80
-0.	0.	-0.382207E 01	0.	-0.	0.	10.00

APPENDIX VI
STRESS RESPONSE PARAMETERS AND ZERO-CROSSING RATES

Table XX. Stress Response Parameters and Zero-Crossing Rates (Analysis Condition 1)

GROSS WEIGHT: 297,000 LB
MACH NUMBER: 0.85
ALTITUDE: 24,000 FT

Location		Segment number	Axial stress		Shear stress	
Body station	Percent semispan		A (psi)	N_0 (Zero crossings per second)	A (psi)	N_0 (Zero crossings per second)
SCALE OF TURBULENCE: 1,000 FT CUTOFF FREQUENCY 10 CPS						
---	27	10	421	1.02	62	1.81
---	27	14	382	1.02	152	1.25
---	40.06	8	397	1.06	111	1.32
---	40.06	107	359	1.06	106	1.30
540	---	S-17	0	0	31.17	2.64
820	---	S-1	159	1.38	0	0
SCALE OF TURBULENCE: 3,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	339	0.896	47.5	1.64
---	27	14	308	0.886	122	1.09
---	40.06	8	318	0.921	87.6	1.16
---	40.06	107	272	0.921	84.1	1.15
540	---	S-17	0	0	24.09	2.37
820	---	S-1	128	1.19	0	0
SCALE OF TURBULENCE: 5,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	293	0.863	40.7	1.62
---	27	14	266	0.863	105	1.06
---	40.06	8	274	0.903	75.4	1.14
---	40.06	107	234	0.903	72.4	1.12
540	---	S-17	0	0	20.67	2.33
820	---	S-1	111	1.16	0	0

Table XX --- Concluded

GROSS WEIGHT: 297,000 LB
MACH NUMBER: 0.85
ALTITUDE: 24,000 FT

Location		Segment number	Axial stress		Shear stress	
Body station	Percent semispan		A (psi)	N_0 (Zero crossings per second)	A (psi)	N_0 (Zero crossings per second)
SCALE OF TURBULENCE: 1,000 CUTOFF FREQUENCY: 15 CPS						
---	27	10	421	1.02	62	1.82
---	27	14	382	1.02	152	1.25
---	40.06	8	397	1.06	111	1.33
---	40.06	107	339	1.06	106	1.31
540	---	S-17	0	0	31.17	2.64
820	---	S-1	159	1.38	0	0
SCALE OF TURBULENCE: 1,000 FT CUTOFF FREQUENCY: 20 CPS						
---	27	10	421	1.04	62	1.82
---	27	14	382	1.04	152	1.22
---	40.06	8	397	1.04	111	1.30
---	40.06	107	339	1.04	106	1.30
540	---	S-17	0	0	31.17	2.61
820	---	S-1	159	1.39	0	0

Table XXI. Stress Response Parameters and Zero-Crossing Rates (Analysis Condition 2)

GROSS WEIGHT: 268,000 LB
MACH NUMBER: 0.85
ALTITUDE: 24,000 FT

Location		Segment number	Axial stress		Shear stress	
Body station	Percent semispan		A (psi)	N_0 (Zero crossings per second)	A (psi)	N_0 (Zero crossings per second)
SCALE OF TURBULENCE: 1,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	377	1.03	71	2.21
---	27	14	342	1.03	152	1.50
---	40.06	8	342	1.03	111	1.79
---	40.06	107	293	1.03	107	1.75
540	---	S-17	0	0	43.56	3
820	---	S-1	179	2.02	0	0
SCALE OF TURBULENCE: 3,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	312	0.868	52.9	2.06
---	27	14	283	0.868	121	1.30
---	40.06	8	283	0.863	86.6	1.59
---	40.06	107	242	0.863	83.6	1.55
540	---	S-17	0	0	32.44	2.80
820	---	S-1	143	1.76	0	0
SCALE OF TURBULENCE: 5,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	270	0.846	45.1	2.03
---	27	14	245	0.846	105	1.28
---	40.06	8	245	0.841	74.3	1.56
---	40.06	107	210	0.841	71.9	1.52
540	---	S-17	0	0	27.69	2.76
820	---	S-1	123	1.73	0	0

Table XXII. Stress Response Parameters and Zero-Crossing Rates (Analysis Condition 3)

GROSS WEIGHT: 190,590 LB
MACH NUMBER: 0.85
ALTITUDE: 24,000 FT

Location		Segment number	Axial stress		Shear stress	
Body station	Percent semispan		A (psi)	N_0 (Zero crossings per second)	A (psi)	N_0 (Zero crossings per second)
SCALE OF TURBULENCE: 1,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	304	1.15	58.1	2.34
---	27	14	276	1.15	121	1.62
---	40.06	8	274	1.22	95.2	2.09
---	40.06	107	234	1.22	91.6	2.08
540	---	S-17	0	0	51.4	2.55
820	---	S-1	177	2.07	0	0
SCALE OF TURBULENCE: 3,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	239	1.02	41.5	2.28
---	27	14	217	1.02	92.1	1.48
---	40.06	8	215	1.09	70.3	1.97
---	40.06	107	183	1.09	68	1.95
540	---	S-17	0	0	39.2	2.32
820	---	S-1	138	1.85	0	0
SCALE OF TURBULENCE: 5,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	206	1	35.1	2.27
---	27	14	187	1	78.8	1.45
---	40.06	8	184	1.07	59.9	1.95
---	40.06	107	157	1.07	58	1.92
540	---	S-17	0	0	33.6	2.28
820	---	S-1	118	1.82	0	0

Table XXIII Stress Response Parameters and Zero-Crossing Rates (Analysis Condition 4)

GROSS WEIGHT: 107,260 LB
MACH NUMBER: 0.85
ALTITUDE: 24,000 FT

Location		Segment number	Axial stress		Shear stress	
Body station	Percent semispan		A (psi)	K_0 (Zero crossings per second)	A (psi)	N_0 (Zero crossings per second)
SCALE OF TURBULENCE: 1,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	177	1.39	58.1	3.14
---	27	14	161	1.39	77.9	2.89
---	40.06	8	169	1.50	63.2	2.93
---	40.06	107	145	1.50	60.5	2.91
540	---	S-17	0	0	31.25	3.46
820	---	S-1	116	2.90	0	0
SCALE OF TURBULENCE: 3,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	135	1.27	40.5	3.12
---	27	14	122	1.27	54.8	2.85
---	40.06	8	128	1.37	44.8	2.86
---	40.06	107	110	1.37	43.1	2.84
540	---	S-17	0	0	22.39	3.34
820	---	S-1	85.8	2.73	0	0
SCALE OF TURBULENCE: 5,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	115	1.25	34.2	3.12
---	27	14	105	1.25	46.3	2.85
---	40.06	8	110	1.36	38	2.85
---	40.06	107	93.8	1.36	36.5	2.82
540	---	S-17	0	0	18.99	3.33
820	---	S-1	73.1	2.70	0	0

Table XXIV. Stress Response Parameters and Zero-Crossing Rates (Analysis Condition 5)

GROSS WEIGHT: 297,000 LB
MACH NUMBER: 0.50
ALTITUDE: 24,000 FT

Location		Segment number	Axial stress		Shear stress	
Body station	Percent semispan		A (psi)	N_0 (Zero crossings per second)	A (psi)	N_0 (Zero crossings per second)
SCALE OF TURBULENCE: 1,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	226	1.08	29.5	1.53
---	27	14	205	1.08	76.7	1.21
---	40.06	8	221	1.10	56.6	1.34
---	40.06	107	189	1.10	53.3	1.33
540	---	S-17	0	0	21.1	3.08
820	---	S-1	88.1	1.87	0	0
SCALE OF TURBULENCE: 3,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	158	1.08	20.6	1.54
---	27	14	144	1.08	53.6	1.18
---	40.06	8	154	1.08	39.5	1.34
---	40.06	107	132	1.08	37.2	1.34
540	---	S-17	0	0	14.68	3.08
820	---	S-1	61.5	1.85	0	0
SCALE OF TURBULENCE: 5,000 FT CUTOFF FREQUENCY: 10 CPS						
---	27	10	133	1.07	17.3	1.52
---	27	14	121	1.07	45.3	1.20
---	40.06	8	130	1.10	33.3	1.34
---	40.06	107	111	1.10	31.4	1.31
540	---	S-17	0	0	12.4	3.06
820	---	S-1	59.9	1.86	0	0

Table XXV. Incremental Limit Allowable Stresses

Location		Segment number	Analysis condition									
			1 Gross wt: 297,000 lb Mach number: 0.85		2 Gross wt: 268,000 lb Mach number: 0.85		3 Gross wt: 190,590 lb Mach number: 0.85		4 Gross wt: 107,000 lb Mach number: 0.85		5 Gross wt: 297,000 lb Mach number: 0.50	
Body station	Percent semispan		Axial stress (psi)	Shear stress (psi)	Axial stress (psi)	Shear stress (psi)	Axial stress (psi)	Shear stress (psi)	Axial stress (psi)	Shear stress (psi)	Axial stress (psi)	Shear stress (psi)
SCALE OF TURBULENCE: 1,000 FEET												
---	27	10	24,700	3,800	24,400	4,500	29,400	5,600	33,500	10,300	23,500	3,000
---	27	14	24,100	9,500	23,600	10,500	27,200	12,500	31,000	15,100	23,500	9,000
---	40.06	8	24,100	6,600	23,600	7,600	27,700	10,000	32,400	11,100	22,300	5,700
---	40.06	107	18,000	5,800	17,500	6,500	20,400	7,900	23,200	9,900	18,200	5,300
540	---	S-17	---	4,190	---	4,190	---	4,190	---	5,635	---	4,190
820	---	S-1	22,100	---	21,900	---	23,400	---	27,700	---	25,700	---
SCALE OF TURBULENCE: 3,000 FEET												
---	27	10	24,800	3,500	24,500	4,100	29,600	4,900	34,300	9,000	23,500	3,000
---	27	14	24,000	9,500	23,400	10,500	27,400	12,400	31,100	15,100	23,500	9,000
---	40.06	8	24,000	6,700	23,600	7,300	27,800	9,600	32,300	11,300	22,300	5,900
---	40.06	107	18,300	5,700	17,800	6,100	20,900	7,500	24,200	9,300	18,200	5,300
540	---	S-17	---	4,190	---	4,190	---	4,190	---	5,635	---	4,190
820	---	S-1	22,100	---	21,900	---	23,400	---	27,700	---	25,700	---
SCALE OF TURBULENCE: 5,000 FEET												
---	27	10	24,700	3,800	24,500	4,200	29,500	5,100	34,100	9,100	23,500	3,100
---	27	14	24,100	9,500	23,800	10,100	27,900	11,600	31,500	14,400	23,600	8,600
---	40.06	8	24,300	5,300	23,700	7,300	28,200	9,100	32,600	10,700	22,300	5,800
---	40.06	107	18,300	5,500	17,900	6,000	21,100	7,300	24,300	9,000	18,200	5,100
540	---	S-17	---	4,190	---	4,190	---	4,190	---	5,635	---	4,190
820	---	S-1	22,100	---	21,900	---	23,400	---	27,700	---	25,700	---

APPENDIX VIII
CORRELATION COEFFICIENTS BETWEEN AXIAL AND SHEAR STRESSES

Table XXVI. Correlation Coefficients Between Axial and Shear Stresses

Location		W_c = 10 cps			W_c = 15 cps	W_c = 20 cps
Percent wing semispan	Segment number	L = 1,000 ft	L = 3,000 ft	L = 5,000 ft	L = 1,000 ft	L = 1,000 ft
		ANALYSIS CONDITION 1				
27	10	0.835	0.866	0.871	−0.835	−0.835
27	14	0.961	0.971	0.972	0.961	0.961
40.06	8	0.962	0.971	0.972	0.962	0.962
40.06	107	−0.962	−0.971	−0.972	−0.962	−0.962
		ANALYSIS CONDITION 2				
27	10	0.746	0.780	0.786	---	
27	14	0.941	0.956	0.958		
40.06	8	0.887	0.910	0.913		
40.06	107	−0.894	−0.916	−0.919		
		ANALYSIS CONDITION 3				
27	10	0.673	0.687	0.689	---	
27	14	0.922	0.935	0.937		
40.06	8	0.831	0.851	0.854		
40.06	107	−0.837	−0.859	−0.862		
		ANALYSIS CONDITION 4				
27	10	−0.0127	−0.0490	−0.0558	---	
27	14	0.475	0.493	0.495		
40.06	8	0.575	0.598	0.602		
40.06	107	−0.585	−0.611	−0.615		
		ANALYSIS CONDITION 5				
27	10	0.904	0.905	0.905	---	
27	14	0.975	0.975	0.975		
40.06	8	0.972	0.972	0.972		
40.06	107	−0.972	−0.972	−0.972		

APPENDIX IX
STRESS INFLUENCE COEFFICIENTS

(a) 27 PERCENT WING SEMISPAN, SEGMENT NUMBER 10

$$\begin{Bmatrix} \text{Skin Stress} \\ \text{Shear Stress} \end{Bmatrix} = \begin{bmatrix} 0.00107 \ \frac{PSI}{In\text{-}Lb} & 0 & 0 \\ 77 \times 10^{-6} \ \frac{PSI}{In\text{-}Lb} & 0.0228 \ \frac{PSI}{Lb} & 865 \times 10^{-6} \ \frac{PSI}{In\text{-}Lb} \end{bmatrix} \begin{Bmatrix} \text{Bending Moment} \\ \text{Shear} \\ \text{Torsion} \end{Bmatrix}$$

(b) 27 PERCENT WING SEMISPAN, SEGMENT NUMBER 14

$$\begin{Bmatrix} \text{Skin Stress} \\ \text{Shear Stress} \end{Bmatrix} = \begin{bmatrix} 0.000971 \ \frac{PSI}{In\text{-}Lb} & 0 & 0 \\ 188 \times 10^{-6} \ \frac{PSI}{In\text{-}Lb} & 0.0655 \ \frac{PSI}{Lb} & 865 \times 10^{-6} \ \frac{PSI}{In\text{-}Lb} \end{bmatrix} \begin{Bmatrix} \text{Bending Moment} \\ \text{Shear} \\ \text{Torsion} \end{Bmatrix}$$

(c) 40.06 PERCENT SEMISPAN, SEGMENT NUMBER 8

$$\begin{Bmatrix} \text{Skin Stress} \\ \text{Shear Stress} \end{Bmatrix} = \begin{bmatrix} 0.00158 \ \frac{PSI}{In\text{-}Lb} & 0 & 0 \\ 123 \times 10^{-6} \ \frac{PSI}{In\text{-}Lb} & 0.0359 \ \frac{PSI}{Lb} & 1370 \times 10^{-6} \ \frac{PSI}{In\text{-}Lb} \end{bmatrix} \begin{Bmatrix} \text{Bending Moment} \\ \text{Shear} \\ \text{Torsion} \end{Bmatrix}$$

(d) 40.06 PERCENT SEMISPAN, SEGMENT NUMBER 107

$$\begin{Bmatrix} \text{Segment Stress} \\ \text{Shear Stress} \end{Bmatrix} = \begin{bmatrix} -0.00135 \ \frac{PSI}{In\text{-}Lb} & 0 & 0 \\ 43.4 \times 10^{-6} \ \frac{PSI}{In\text{-}Lb} & 0.0525 \ \frac{PSI}{Lb} & 1286 \times 10^{-6} \ \frac{PSI}{In\text{-}Lb} \end{bmatrix} \begin{Bmatrix} \text{Bending Moment} \\ \text{Shear} \\ \text{Torsion} \end{Bmatrix}$$

(e) BODY BALANCE STATION 540, STRINGER S-7

$$\begin{Bmatrix} \text{Axial Stress} \\ \\ \text{Shear Stress} \end{Bmatrix} = \begin{bmatrix} 0 & 0 \\ \\ 0 & 0.0516 \ \frac{\text{PSI}}{\text{Lb}} \end{bmatrix} \begin{Bmatrix} \text{Bending Moment} \\ \\ \text{Shear} \end{Bmatrix}$$

(f) BODY BALANCE STATION 820, STRINGER S-1

$$\begin{Bmatrix} \text{Axial Stress} \\ \\ \text{Shear Stress} \end{Bmatrix} = \begin{bmatrix} 0.000302 \ \frac{\text{PSI}}{\text{In-Lb}} & 0 \\ \\ 0 & 0 \end{bmatrix} \begin{Bmatrix} \text{Bending Moment} \\ \\ \text{Shear} \end{Bmatrix}$$

Sign Convention

+ Segment Stress – Tension
+ Bending Moment – Tension in lower skin
+ Shear – Outboard wing sheared up relative to inboard wing
+ Torsion – Leading edge up

REFERENCES

1. D. Espey and A. Laier, External Loads Criteria, D-16809, Vol. I, The Boeing Company, April 1956

2. Military Specification, Airplane Strength and Rigidity, MIL-A-8860 (ASG), U. S. Air Force, May 1960

3. R. E. Baum and J. R. Newell, Jr., Mass Properties for Power Spectral Gust Analysis, D6-18249, The Boeing Company, September 1965

4. D. O. Neilson and E. Plunkett, Ground Vibration Test of the KC-135 Airplane, T6-1044, The Boeing Company, December 1957

5. D. R. Magee and W. W. Bingham, Ground Vibration Test of the 707-321 Airplane, T6-1588, The Boeing Company, June 1959

6. J. T. Rogers, Review of 707 Design Aeroelastic Analysis Based on Comparison with Measured Flight Loads on the KC-135 Airplane, D6-1042, The Boeing Company, September 1958

7. L. D. Richmond, A Rational Method of Obtaining Three-Dimensional Unsteady Aerodynamic Derivatives of Intersecting Airfoils in Subsonic Flow, D6-7401, The Boeing Company, April 1962

8. J. C. Houbolt, R. Steiner, and K. G. Pratt, Dynamic Response of Airplanes to Atmospheric Turbulence Including Flight Data on Input and Response, TR R-199, National Aeronautics and Space Administration, 1965

9. R. Coffman, G. Gillette, G. Houlihan, Fuselage Stress Analysis, D-16811, Vol. II, The Boeing Company, May 1957

10. A. R. Wright, Wing Stress Analysis, D6-16810, Vol. I, The Boeing Company, January 1957

11. J. R. Fuller et al., Contribution to the Development of a Power Spectral Gust Design Procedure for Civil Aircraft, FAA-ADS-54, Contract FA-WA-4768, January 1966

12. T. A. Montgomery, External and Internal Loads for C-135 Airplane, D6-7267, Vol. II, The Boeing Company, April 1961

13. A. W. Byrski, Design Loads Criteria for Growth 707-100/200 Series Airplanes, D6-3212, Vol. II, The Boeing Company, July 1959

DOCUMENT CONTROL DATA–R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author)
The Boeing Company
Commercial Airplane Division
Renton, Washington

2a REPORT SECURITY CLASSIFICATION
unclassified

2b GROUP
none

3 REPORT TITLE
Volume 1.
KC-135 Power Spectral Vertical Gust Load Analysis
Detailed Analysis and Results

4 DESCRIPTIVE NOTES (Type of report and inclusive dates)
Final Report July 1965 to March 1966

5 AUTHOR(S) (Last name, first name, initial)

Latz, Robert N.

6 REPORT DATE	7a TOTAL NO. OF PAGES	7b NO. OF REFS.
July 1966	121	13

8a CONTRACT OR GRANT NO.	9a ORIGINATOR'S REPORT NUMBER(S)
AF 33 (615) - 2454	AFFDL-TR-66-57, Vol. I
b PROJECT NO. System No. 5 (611367 62405334)	
c Project No. 1367	9b OTHER REPORT NO.(S) (Any other numbers that may be assigned this report)
d Task No. 136702	D6-18252

10 AVAILABILITY/LIMITATION NOTICES
This document is subject to special export controls and each transmittal to foreign governments or foreing nationals may be made only with proper approval of the Air Force Flight Dynamics Laboratory (FDTR), Wright-Patterson AFB, Ohio 45433.

11 SUPPLEMENTARY NOTES

12 SPONSORING MILITARY ACTIVITY
Air Force Flight Dynamics Laboratory, Research and Technology Division, Air Force Systems Command, Wright-Patterson AFB, Ohio

13 ABSTRACT

This report presents the results of an aniysis to obtain the stress response parameters (level of stress per level of turbulence) and zero-crossing rates at two wing stations and two body stations of the KC-135 airplane where the margins of safety for gusts are minimum. Five combinations of gross weight, speed, and altitude were selected. The results of the computer analysis pre sent the effects of changes in scale of turbulence and upper cutoff frequency on the response parameters and zero-crossing rates. Results indicate a large reduction in stress response parameter and small reduction in zero-crossing rate with increasing scale of turbulence. Variatons of upper cutoff frequence above the highest modal frequency used in the analysis indicate negligible change in eigher stress response parameter or zero-crossing rates. The ratios of incremental limit allowable stress to stress response parameter obtained over a wide range of gross weight, speed, and scale of turbulence result in a minimum value of 53. This document (volume I) presents the analyses and specific results described above. Volume II presents response parameters, zero-crossing rates, frequency response functions, and power spectra of bending moment, shear, and torsion.

DD FORM 1 JAN 64 1473

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Gust Loads **Power Spectra** **Stresses** **Response Parameters** **Zero Crossings** **Analysis**						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization *(corporate author)* issuing the report.

2*a*. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2*b*. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7*a*. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7*b*. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8*a*. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8*b*, 8*c*, & 8*d*. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9*a*. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9*b*. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers *(either by the originator or by the sponsor)*, also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as.

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring *(paying for)* the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as *(TS)*, *(S)*, *(C)*, *or (U)*.

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

SUPPLEMENTARY

INFORMATION

Errata

AD- 802 114
AD 802 114

AFFDL TR-66-57
VOLUME I

KC-135 POWER SPECTRAL VERTICAL GUST LOAD ANALYSIS

DETAILED ANALYSIS AND RESULTS VOLUME I

ROBERT N. LATZ
THE BOEING COMPANY

"This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with proper approval of the Air Force Flight Dynamics Laboratory (FDTR), Wright-Patterson AFB, Ohio 45433."